



Industrial Synchronous Belts



ContiTech – Industrial synchronous belts demanded by the most demanding industries.

ContiTech

Continental AG has been in the rubber product business for over 130 years and is the second largest automotive supplier in Europe. ContiTech is Continental AG's engineered rubber products group and is a leader in OE-quality power transmission technology involving timing belts, v-belts, flat belts, and multi-rib belts.

Known around the globe for innovation, ContiTech has always led the way with new products and technologies, including the use of materials such as Kevlar, fiberglass, and polyester reinforcing fibers – in addition to HSN and EPDM compounds.

CONTI® SYNCHROCHAIN	4-7
CONTI® SYNCHROFORCE CXP	8-21
CONTI® SYNCHROFORCE CXA	22
CONTI® SYNCHROFORCE EXTREME	23
CONTI® SYNCHROBELT	24-45
CONTI® SYNCHROCOLOR	46
CONTI® SYNCHROTWIN	47-55
CONTI® SYNCHROTWIN CXP	56
CONTI® SYNCHROLINE	57
CONTI® SYNCHRODRIVE	58-61
CONTI® SYNCHROFLEX/ CONTI® SYNCHROFLEX GEN III	62
CONTI® SYNCHRODRIVE N10	63
CONTI® POLYFLAT	64-65
CONTI® VSM-1/VSM-3	66-67
CONTI® SUITE	68
INTERCHANGE GUIDE	69-74



CRP Industries Inc.

More than 60 years ago, Continental AG became CRP's very first supplier partner. Now, that partnership has been extended to include the ContiTech line of industrial synchronous belts. Used for a variety of applications including printers, copiers, washers/dryers, HVAC, conveyor belts, and elevators, ContiTech industrial synchronous belts are constructed specifically to handle the rigorous demands of the industrial market.

CRP Industrial is proud to be a part of Continental AG's heritage here in North America. And we are even prouder still to now add the ContiTech Industrial Synchronous Belt line to our other NAFTA product offerings including industrial hoses and motors.



Why CRP?

Today, no one offers a more unique Synchronous Belt Program than CRP. Constructed from a wide variety of materials and available in a range of tooth profiles, our line of industrial synchronous belts are a perfect fit for any industrial application or operating condition.

Quality Control

ContiTech is an ISO/TS 16949:2002 certified manufacturing company. And CRP is an ISO9001:2008 certified company. What that means is that our customers can rest assured that we have a quality management system in place that delivers service satisfaction from start to finish.

Fast Delivery

Each year, CRP ships millions of ContiTech branded products. Because of our strategically placed warehouses in Cranbury, New Jersey; Fremont, California; Mississauga, Ontario; and Puebla, Mexico, we can deliver OE-quality products like ContiTech faster and more cost effectively than ever before throughout the NAFTA market.

Brand Values

At CRP, we pay great attention to the products we carry, the people we work with, and the way in which we conduct business. In fact, the greatest products we offer our customers are quality, service, and trust.



ContiTech in the Continental Corporation

ContiTech Power Transmission Group

Continental AG

Continental is one of the world's leading automotive industry suppliers. As a supplier of tires, brake control systems, driving dynamics control systems, driver assistance systems, sensors, systems and components for the powertrain and chassis, instrumentation, info-tainment solutions, vehicle electronics and technical elastomer products, the company contributes to enhanced driving safety and environmental protection.

Continental is also an expert partner in networked auto-mobile communication. With its six divisions – Chassis & Safety, Powertrain, Interior, Passenger and Light Truck Tires, Commercial Vehicle Tires and ContiTech – Continental is a continuous driving force for future mobility concepts, and not just in the automotive industry. The company employs about 150,000 people in 46 countries.

Division ContiTech

ContiTech is a global technology partner when it comes to innovations made from rubber and plastics. With its high-tech products and systems, ContiTech is a development partner and original equipment supplier to the automotive and many other industries. Focusing on eco-friendly and resource-efficient products and manufacturing processes, the company exploits the global market and growth opportunities. With its forward-looking products and advanced developments, it has the right tools to deal with challenges, now and in the future.

Innovative drive solutions for industrial applications

ContiTech Power Transmission Group is a developer, manufacturer and supplier of power transmission belts, components and complete belt drive systems – for motor vehicles, machinery and equipment – and is in demand around the world as a development and service partner for original equipment and spares business.

In the **Industry market segment** we develop innovative power transmission belts and implement customer-specific drive solutions for industrial original equipment. Our application-focused testing technology backs up the product development process and protects resources and the environment.

▫ Research and Development

In accordance with the requirements of industry we draw up the economic and environmental performance parameters demanded by the market for V-belts, multiple V-ribbed belts and synchronous belts in order to maximize performance, technical design, safety and convenience.

▫ Material technology and design


We use the synergies available within the corporation to achieve our drive solutions with their sophisticated material technology and design, opening up almost unlimited scope for machinery and equipment manufacturers.

▫ Logistics and services

We hold more than 10,000 sizes and types in stock for sale. The worldwide distribution is assured by more than 100 partners. Furthermore, we are represented in all the relevant markets throughout the world. Our sales organizations work hand-in-hand with customers to guarantee the optimum solutions for their specific problems.

▫ Environmental and quality management

Certificated to QS 9000, ISO 14001 and EN ISO 9001, we operate R&D, testing and manufacturing facilities at a number of locations around the world.




CONTI® SYNCHROCHAIN

Heavy-duty synchronous belt

for extreme, ultra high-power applications

CTD



Special treated fabric

Polyurethane teeth

Tension member Aramide cord with S/Z twists wound in pairs

Polyurethane backing

Profile

C8M
C14M

Properties:

- ▶ temperature range, depending on application, from -40°F to 212°F (-40°C to +100°C)
- ▶ suitable for tropical climates
- ▶ resistant to aging and ozone
- ▶ withstands reverse flexing
- ▶ resistant to oils, grease and fuel
- ▶ conditionally resistant to acid and lye
- ▶ raw materials and production are silicone free



CONTI SYNCHROCHAIN®

CTD 8M				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
CTD8M-640-12	36.69	80	25.20	0.02
CTD8M-640-21	66.02	80	25.20	0.04
CTD8M-640-36	114.27	80	25.20	0.06
CTD8M-640-62	188.06	80	25.20	0.12
CTD8M-720-12	41.37	90	28.35	0.12
CTD8M-720-21	71.71	90	28.35	0.21
CTD8M-720-36	119.29	90	28.35	0.35
CTD8M-720-62	199.96	90	28.35	0.61
CTD8M-800-12	44.82	100	31.50	0.13
CTD8M-800-21	84.35	100	31.50	0.23
CTD8M-800-36	129.90	100	31.50	0.39
CTD8M-800-62	220.83	100	31.50	0.68
CTD8M-896-12	49.51	112	35.28	0.15
CTD8M-896-21	85.41	112	35.28	0.26
CTD8M-896-36	145.20	112	35.28	0.44
CTD8M-896-62	238.65	112	35.28	0.76
CTD8M-920-12	51.13	115	36.22	0.15
CTD8M-920-21	89.22	115	36.22	0.26
CTD8M-920-36	150.62	115	36.22	0.45
CTD8M-920-62	246.40	115	36.22	0.78
CTD8M-960-12	53.84	120	37.80	0.15
CTD8M-960-21	95.56	120	37.80	0.27
CTD8M-960-36	159.64	120	37.80	0.46
CTD8M-960-62	259.31	120	37.80	0.80
CTD8M-1000-12	54.51	125	39.37	0.16
CTD8M-1000-21	96.74	125	39.37	0.29
CTD8M-1000-36	161.94	125	39.37	0.49
CTD8M-1000-62	264.76	125	39.37	0.84
CTD8M-1040-12	56.32	130	40.94	0.05
CTD8M-1040-21	97.22	130	40.94	0.09
CTD8M-1040-36	164.70	130	40.94	0.15
CTD8M-1040-62	268.15	130	40.94	0.25
CTD8M-1120-12	57.12	140	44.09	0.05
CTD8M-1120-21	97.91	140	44.09	0.09
CTD8M-1120-36	168.17	140	44.09	0.15
CTD8M-1120-62	273.24	140	44.09	0.25
CTD8M-1200-12	58.31	150	47.24	0.12
CTD8M-1200-21	101.98	150	47.24	0.21
CTD8M-1200-36	170.44	150	47.24	0.36
CTD8M-1200-62	282.52	150	47.24	0.62
CTD8M-1224-12	63.55	153	48.19	0.19
CTD8M-1224-21	104.48	153	48.19	0.32
CTD8M-1224-36	174.73	153	48.19	0.56
CTD8M-1224-62	292.91	153	48.19	0.96

CTD 8M				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
CTD8M-1280-12	65.19	160	50.39	0.21
CTD8M-1280-21	108.51	160	50.39	0.37
CTD8M-1280-36	179.36	160	50.39	0.63
CTD8M-1280-62	303.96	160	50.39	1.08
CTD8M-1440-12	68.38	180	56.69	0.24
CTD8M-1440-21	112.61	180	56.69	0.41
CTD8M-1440-36	188.80	180	56.69	0.71
CTD8M-1440-62	321.44	180	56.69	1.22
CTD8M-1600-12	71.01	200	62.99	0.16
CTD8M-1600-21	120.76	200	62.99	0.28
CTD8M-1600-36	211.68	200	62.99	0.48
CTD8M-1600-62	353.67	200	62.99	0.83
CTD8M-1760-12	75.73	220	69.29	0.18
CTD8M-1760-21	133.83	220	69.29	0.31
CTD8M-1760-36	226.94	220	69.29	0.54
CTD8M-1760-62	391.61	220	69.29	0.92
CTD8M-1792-12	78.97	224	70.55	0.18
CTD8M-1792-21	136.77	224	70.55	0.31
CTD8M-1792-36	230.46	224	70.55	0.54
CTD8M-1792-62	398.67	224	70.55	0.93
CTD8M-2000-12	86.15	250	78.74	0.20
CTD8M-2000-21	149.83	250	78.74	0.36
CTD8M-2000-36	258.08	250	78.74	0.61
CTD8M-2000-62	422.92	250	78.74	1.06
*CTD8M-2240-12	104.98	280	88.19	0.37
*CTD8M-2240-21	179.08	280	88.19	0.64
*CTD8M-2240-36	290.04	280	88.19	1.10
*CTD8M-2240-62	496.77	280	88.19	1.89
CTD8M-2400-12	105.00	300	94.49	0.39
CTD8M-2400-21	185.79	300	94.49	0.69
CTD8M-2400-36	306.99	300	94.49	1.18
CTD8M-2400-62	535.70	300	94.49	2.03
CTD8M-2520-12	109.06	315	99.21	0.41
CTD8M-2520-21	188.50	315	99.21	0.72
CTD8M-2520-36	315.17	315	99.21	1.24
CTD8M-2520-62	539.67	315	99.21	2.13
CTD8M-2840-12	113.85	355	111.81	0.28
CTD8M-2840-21	203.50	355	111.81	0.50
CTD8M-2840-36	339.17	355	111.81	0.84
CTD8M-2840-62	573.24	355	111.81	1.45
CTD8M-3200-12	130.25	400	125.98	0.32
CTD8M-3200-21	231.85	400	125.98	0.56
CTD8M-3200-36	370.81	400	125.98	0.97
CTD8M-3200-62	641.11	400	125.98	1.67

* Contact CRP for availability

CTD 8M				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
CTD8M-3600-12	141.68	450	141.73	0.36
CTD8M-3600-21	258.65	450	141.73	0.63
CTD8M-3600-36	414.23	450	141.73	1.09
CTD8M-3600-62	727.24	450	141.73	1.87
CTD8M-4000-12	161.67	500	157.48	0.40
CTD8M-4000-21	280.13	500	157.48	0.71
CTD8M-4000-36	456.01	500	157.48	1.21
CTD8M-4000-62	793.39	500	157.48	2.08
*CTD8M-4480-12	185.66	560	176.38	0.45
*CTD8M-4480-21	305.91	560	176.38	0.81
*CTD8M-4480-36	506.15	560	176.38	1.35
*CTD8M-4480-62	872.77	560	176.38	2.33

CTD 14M				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
CTD14M-994-20	191.63	71	39.13	0.30
CTD14M-994-37	356.09	71	39.13	0.55
CTD14M-994-68	614.57	71	39.13	1.02
CTD14M-994-90	779.67	71	39.13	1.34
CTD14M-994-125	1,034.01	71	39.13	1.87
CTD14M-1120-20	214.56	80	44.09	0.34
CTD14M-1120-37	392.59	80	44.09	0.62
CTD14M-1120-68	681.54	80	44.09	1.14
CTD14M-1120-90	884.30	80	44.09	1.51
CTD14M-1120-125	1,193.49	80	44.09	2.10
CTD14M-1190-20	217.96	85	46.85	0.36
CTD14M-1190-37	402.55	85	46.85	0.66
CTD14M-1190-68	725.67	85	46.85	1.21
CTD14M-1190-90	903.59	85	46.85	1.60
CTD14M-1190-125	1,224.19	85	46.85	2.23
CTD14M-1260-20	228.59	90	49.61	0.38
CTD14M-1260-37	423.85	90	49.61	0.71
CTD14M-1260-68	733.86	90	49.61	1.30
CTD14M-1260-90	938.42	90	49.61	1.72
CTD14M-1260-125	1,267.53	90	49.61	2.39
CTD14M-1400-20	231.32	100	55.12	0.42
CTD14M-1400-37	432.96	100	55.12	0.78
CTD14M-1400-68	794.18	100	55.12	1.43
CTD14M-1400-90	973.33	100	55.12	1.89
CTD14M-1400-125	1,339.43	100	55.12	2.62

* Contact CRP for availability

CTD 14M				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
CTD14M-1568-20	252.34	112	61.73	0.47
CTD14M-1568-37	455.26	112	61.73	0.87
CTD14M-1568-68	795.09	112	61.73	1.60
CTD14M-1568-90	1,064.50	112	61.73	2.11
CTD14M-1568-125	1,424.53	112	61.73	2.93
CTD14M-1610-20	260.10	115	63.39	0.49
CTD14M-1610-37	461.31	115	63.39	0.90
CTD14M-1610-68	831.60	115	63.39	1.65
CTD14M-1610-90	1,064.77	115	63.39	2.19
CTD14M-1610-125	1,425.45	115	63.39	3.04
CTD14M-1750-20	260.62	125	68.90	0.52
CTD14M-1750-37	494.55	125	68.90	0.97
CTD14M-1750-68	870.79	125	68.90	1.78
CTD14M-1750-90	1,116.65	125	68.90	2.36
CTD14M-1750-125	1,510.35	125	68.90	3.28
CTD14M-1890-20	276.39	135	74.41	0.57
CTD14M-1890-37	502.65	135	74.41	1.05
CTD14M-1890-68	874.43	135	74.41	1.93
CTD14M-1890-90	1,157.07	135	74.41	2.55
CTD14M-1890-125	1,543.93	135	74.41	3.55
CTD14M-1960-20	280.27	140	77.52	0.59
CTD14M-1960-37	517.53	140	77.52	1.09
CTD14M-1960-68	897.50	140	77.52	2.01
CTD14M-1960-90	1,172.80	140	77.52	2.66
CTD14M-1960-125	1,603.42	140	77.52	3.70
CTD14M-2100-20	301.22	150	82.68	0.63
CTD14M-2100-37	559.04	150	82.68	1.16
CTD14M-2100-68	981.91	150	82.68	2.14
CTD14M-2100-90	1,259.12	150	82.68	2.83
CTD14M-2100-125	1,753.92	150	82.68	3.93
CTD14M-2240-20	315.55	160	88.19	0.67
CTD14M-2240-37	588.47	160	88.19	1.25
CTD14M-2240-68	1,069.89	160	88.19	2.29
CTD14M-2240-90	1,342.31	160	88.19	3.03
CTD14M-2240-125	1,890.47	160	88.19	4.21
*CTD14M-2310-20	328.41	165	90.94	0.69
*CTD14M-2310-37	612.68	165	90.94	1.28
*CTD14M-2310-68	1,080.41	165	90.94	2.35
*CTD14M-2310-90	1,356.58	165	90.94	3.11
*CTD14M-2310-125	1,891.28	165	90.94	4.33
CTD14M-2380-20	339.72	170	93.70	0.71
CTD14M-2380-37	625.90	170	93.70	1.32
CTD14M-2380-68	1,095.41	170	93.70	2.43
CTD14M-2380-90	1,426.66	170	93.70	3.21
CTD14M-2380-125	1,943.92	170	93.70	4.46

CTD 14M				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
*CTD14M-2450-20	342.47	175	96.46	0.73
*CTD14M-2450-37	636.14	175	96.46	1.36
*CTD14M-2450-68	1,161.09	175	96.46	2.49
*CTD14M-2450-90	1,466.54	175	96.46	3.30
*CTD14M-2450-125	1,969.01	175	96.46	4.58
CTD14M-2520-20	347.24	180	99.21	0.75
CTD14M-2520-37	650.50	180	99.21	1.40
CTD14M-2520-68	1,168.42	180	99.21	2.57
CTD14M-2520-90	1,501.45	180	99.21	3.40
CTD14M-2520-125	2,014.50	180	99.21	4.72
*CTD14M-2590-20	359.63	185	101.97	0.78
*CTD14M-2590-37	675.38	185	101.97	1.43
*CTD14M-2590-68	1,174.71	185	101.97	2.64
*CTD14M-2590-90	1,591.58	185	101.97	3.49
*CTD14M-2590-125	2,110.68	185	101.97	4.85
CTD14M-2660-20	376.97	190	104.72	0.80
CTD14M-2660-37	704.02	190	104.72	1.47
CTD14M-2660-68	1,231.43	190	104.72	2.71
CTD14M-2660-90	1,621.34	190	104.72	3.58
CTD14M-2660-125	2,225.96	190	104.72	4.98
CTD14M-2800-20	391.10	200	110.24	0.84
CTD14M-2800-37	739.15	200	110.24	1.55
CTD14M-2800-68	1,281.93	200	110.24	2.85
CTD14M-2800-90	1,668.89	200	110.24	3.77
CTD14M-2800-125	2,265.99	200	110.24	5.24
CTD14M-3136-20	405.90	224	123.46	0.94
CTD14M-3136-37	745.06	224	123.46	1.74
CTD14M-3136-68	1,387.27	224	123.46	3.19
CTD14M-3136-90	1,784.54	224	123.46	4.22
CTD14M-3136-125	2,457.11	224	123.46	5.86
CTD14M-3304-20	452.55	236	130.08	1.00
CTD14M-3304-37	824.36	236	130.08	1.85
CTD14M-3304-68	1,474.34	236	130.08	3.39
CTD14M-3304-90	1,957.78	236	130.08	4.49
CTD14M-3304-125	2,656.73	236	130.08	6.23
CTD14M-3500-20	463.86	250	137.80	1.05
CTD14M-3500-37	849.33	250	137.80	1.94
CTD14M-3500-68	1,582.47	250	137.80	3.56
CTD14M-3500-90	1,982.56	250	137.80	4.72
CTD14M-3500-125	2,705.86	250	137.80	6.55
CTD14M-3850-20	471.70	275	151.57	1.15
CTD14M-3850-37	895.79	275	151.57	2.13
CTD14M-3850-68	1,600.56	275	151.57	3.92
CTD14M-3850-90	2,091.15	275	151.57	5.18
CTD14M-3850-125	2,742.04	275	151.57	7.20



* Contact CRP for availability


CTD 14M				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
CTD14M-3920-20	493.84	280	154.33	1.17
CTD14M-3920-37	898.87	280	154.33	2.17
CTD14M-3920-68	1,666.63	280	154.33	3.99
CTD14M-3920-90	2,183.62	280	154.33	5.28
CTD14M-3920-125	2,952.92	280	154.33	7.34
CTD14M-4410-20	554.39	315	173.62	1.32
CTD14M-4410-37	999.65	315	173.62	2.44
CTD14M-4410-68	1,766.76	315	173.62	4.49
CTD14M-4410-90	2,380.40	315	173.62	5.94
CTD14M-4410-125	3,236.85	315	173.62	8.25

CONTI® SYNCHROFORCE CXP

Heavy-duty synchronous belt

for high power transmission at high speeds

HTD	STD
	
Profile	Profile
3M	S8M
5M	
8M	
14M	
Properties:	
<ul style="list-style-type: none">▶ conditionally resistant to oil▶ temperature range, depending on application, from -4°F to 212°F (-20°C to +100°C)▶ electrically conductive to ISO 9563▶ suitable for tropical climates▶ resistant to aging and ozone	



CONTI SYNCHROFORCE® CXP

HTD 3M-CXP				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
111-3M-CXP-06	4.93	37	4.37	0.003
111-3M-CXP-09	6.44	37	4.37	0.005
111-3M-CXP-15	10.65	37	4.37	0.009
117-3M-CXP-06	4.96	39	4.61	0.003
117-3M-CXP-09	6.47	39	4.61	0.005
117-3M-CXP-15	10.72	39	4.61	0.009
129-3M-CXP-06	5.01	43	5.08	0.003
129-3M-CXP-09	6.52	43	5.08	0.005
129-3M-CXP-15	10.85	43	5.08	0.010
141-3M-CXP-06	5.07	47	5.55	0.005
141-3M-CXP-09	6.57	47	5.55	0.007
141-3M-CXP-15	10.98	47	5.55	0.011
144-3M-CXP-06	5.08	48	5.67	0.005
144-3M-CXP-09	6.58	48	5.67	0.007
144-3M-CXP-15	11.01	48	5.67	0.011
150-3M-CXP-06	5.25	50	5.91	0.005
150-3M-CXP-09	6.80	50	5.91	0.007
150-3M-CXP-15	11.04	50	5.91	0.012
156-3M-CXP-06	5.27	52	6.14	0.008
156-3M-CXP-09	6.84	52	6.14	0.012
156-3M-CXP-15	11.22	52	6.14	0.020
159-3M-CXP-06	5.30	53	6.26	0.005
159-3M-CXP-09	6.86	53	6.26	0.008
159-3M-CXP-15	11.30	53	6.26	0.013
168-3M-CXP-06	5.39	56	6.61	0.005
168-3M-CXP-09	6.96	56	6.61	0.008
168-3M-CXP-15	11.35	56	6.61	0.013
174-3M-CXP-06	5.40	58	6.85	0.006
174-3M-CXP-09	7.03	58	6.85	0.008
174-3M-CXP-15	11.42	58	6.85	0.014
177-3M-CXP-06	5.41	59	6.97	0.006
177-3M-CXP-09	7.05	59	6.97	0.008
177-3M-CXP-15	11.50	59	6.97	0.014
180-3M-CXP-06	5.49	60	7.09	0.006
180-3M-CXP-09	7.16	60	7.09	0.009
180-3M-CXP-15	11.64	60	7.09	0.014
186-3M-CXP-06	5.49	62	7.32	0.007
186-3M-CXP-09	7.23	62	7.32	0.011
186-3M-CXP-15	11.67	62	7.32	0.018
192-3M-CXP-06	5.50	64	7.56	0.008
192-3M-CXP-09	7.30	64	7.56	0.013
192-3M-CXP-15	11.70	64	7.56	0.021

HTD 3M-CXP				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
201-3M-CXP-06	5.50	67	7.91	0.010
201-3M-CXP-09	7.40	67	7.91	0.016
201-3M-CXP-15	11.75	67	7.91	0.026
204-3M-CXP-06	5.58	68	8.03	0.006
204-3M-CXP-09	7.41	68	8.03	0.010
204-3M-CXP-15	12.06	68	8.03	0.016
210-3M-CXP-06	5.60	70	8.27	0.007
210-3M-CXP-09	7.46	70	8.27	0.011
210-3M-CXP-15	12.11	70	8.27	0.017
213-3M-CXP-06	5.61	71	8.39	0.007
213-3M-CXP-09	7.48	71	8.39	0.011
213-3M-CXP-15	12.14	71	8.39	0.018
216-3M-CXP-06	5.62	72	8.50	0.007
216-3M-CXP-09	7.50	72	8.50	0.011
216-3M-CXP-15	12.16	72	8.50	0.018
225-3M-CXP-06	5.65	75	8.86	0.007
225-3M-CXP-09	7.62	75	8.86	0.011
225-3M-CXP-15	12.29	75	8.86	0.018
234-3M-CXP-06	5.75	78	9.21	0.008
234-3M-CXP-09	7.71	78	9.21	0.011
234-3M-CXP-15	12.33	78	9.21	0.019
240-3M-CXP-06	5.81	80	9.45	0.008
240-3M-CXP-09	7.77	80	9.45	0.012
240-3M-CXP-15	12.35	80	9.45	0.020
246-3M-CXP-06	5.84	82	9.69	0.008
246-3M-CXP-09	7.80	82	9.69	0.012
246-3M-CXP-15	12.40	82	9.69	0.020
252-3M-CXP-06	5.85	84	9.92	0.008
252-3M-CXP-09	7.83	84	9.92	0.012
252-3M-CXP-15	12.67	84	9.92	0.021
255-3M-CXP-06	6.04	85	10.04	0.009
255-3M-CXP-09	7.86	85	10.04	0.013
255-3M-CXP-15	12.70	85	10.04	0.023
261-3M-CXP-06	6.05	87	10.28	0.009
261-3M-CXP-09	7.93	87	10.28	0.013
261-3M-CXP-15	12.72	87	10.28	0.023
267-3M-CXP-06	6.06	89	10.51	0.009
267-3M-CXP-09	7.99	89	10.51	0.013
267-3M-CXP-15	12.74	89	10.51	0.023
270-3M-CXP-06	6.07	90	10.63	0.009
270-3M-CXP-09	8.05	90	10.63	0.014
270-3M-CXP-15	12.85	90	10.63	0.023

HTD 3M-CXP				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
285-3M-CXP-06	6.11	95	11.22	0.010
285-3M-CXP-09	8.33	95	11.22	0.015
285-3M-CXP-15	13.42	95	11.22	0.024
294-3M-CXP-06	6.15	98	11.57	0.010
294-3M-CXP-09	8.34	98	11.57	0.015
294-3M-CXP-15	13.53	98	11.57	0.025
300-3M-CXP-06	6.17	100	11.81	0.010
300-3M-CXP-09	8.34	100	11.81	0.015
300-3M-CXP-15	13.61	100	11.81	0.025
312-3M-CXP-06	6.20	104	12.28	0.011
312-3M-CXP-09	8.35	104	12.28	0.017
312-3M-CXP-15	13.74	104	12.28	0.028
318-3M-CXP-06	6.28	106	12.52	0.010
318-3M-CXP-09	8.41	106	12.52	0.016
318-3M-CXP-15	14.01	106	12.52	0.026
321-3M-CXP-06	6.31	107	12.64	0.010
321-3M-CXP-09	8.46	107	12.64	0.016
321-3M-CXP-15	14.02	107	12.64	0.027
336-3M-CXP-06	6.45	112	13.23	0.011
336-3M-CXP-09	8.70	112	13.23	0.017
336-3M-CXP-15	14.04	112	13.23	0.028
339-3M-CXP-06	6.51	113	13.35	0.011
339-3M-CXP-09	8.73	113	13.35	0.017
339-3M-CXP-15	14.14	113	13.35	0.028
357-3M-CXP-06	6.65	119	14.06	0.013
357-3M-CXP-09	8.74	119	14.06	0.019
357-3M-CXP-15	14.33	119	14.06	0.032
363-3M-CXP-06	6.69	121	14.29	0.012
363-3M-CXP-09	9.00	121	14.29	0.018
363-3M-CXP-15	14.66	121	14.29	0.030
384-3M-CXP-06	6.70	128	15.12	0.013
384-3M-CXP-09	9.17	128	15.12	0.019
384-3M-CXP-15	15.18	128	15.12	0.032
390-3M-CXP-06	6.93	130	15.35	0.013
390-3M-CXP-09	9.20	130	15.35	0.019
390-3M-CXP-15	15.32	130	15.35	0.032
393-3M-CXP-06	6.94	131	15.47	0.013
393-3M-CXP-09	9.20	131	15.47	0.020
393-3M-CXP-15	15.36	131	15.47	0.034
396-3M-CXP-06	6.95	132	15.59	0.014
396-3M-CXP-09	9.20	132	15.59	0.021
396-3M-CXP-15	15.40	132	15.59	0.035

HTD 3M-CXP				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
420-3M-CXP-06	7.04	140	16.54	0.015
420-3M-CXP-09	9.22	140	16.54	0.022
420-3M-CXP-15	15.74	140	16.54	0.037
432-3M-CXP-06	7.08	144	17.01	0.015
432-3M-CXP-09	9.23	144	17.01	0.023
432-3M-CXP-15	15.91	144	17.01	0.038
435-3M-CXP-06	7.12	145	17.13	0.015
435-3M-CXP-09	9.39	145	17.13	0.023
435-3M-CXP-15	16.02	145	17.13	0.038
447-3M-CXP-06	7.16	149	17.60	0.015
447-3M-CXP-09	9.51	149	17.60	0.023
447-3M-CXP-15	16.10	149	17.60	0.038
474-3M-CXP-06	7.19	158	18.66	0.016
474-3M-CXP-09	9.66	158	18.66	0.024
474-3M-CXP-15	16.37	158	18.66	0.039
477-3M-CXP-06	7.22	159	18.78	0.016
477-3M-CXP-09	9.74	159	18.78	0.024
477-3M-CXP-15	16.41	159	18.78	0.039
480-3M-CXP-06	7.24	160	18.90	0.016
480-3M-CXP-09	9.82	160	18.90	0.024
480-3M-CXP-15	16.45	160	18.90	0.040
486-3M-CXP-06	7.36	162	19.13	0.017
486-3M-CXP-09	9.85	162	19.13	0.026
486-3M-CXP-15	16.53	162	19.13	0.043
489-3M-CXP-06	7.37	163	19.25	0.016
489-3M-CXP-09	9.96	163	19.25	0.024
489-3M-CXP-15	16.71	164	19.25	0.039
495-3M-CXP-06	7.38	165	19.49	0.017
495-3M-CXP-09	10.00	165	19.49	0.025
495-3M-CXP-15	16.76	165	19.49	0.041
501-3M-CXP-06	7.39	167	19.72	0.017
501-3M-CXP-09	10.04	167	19.72	0.025
501-3M-CXP-15	16.80	167	19.72	0.042
513-3M-CXP-06	7.45	171	20.20	0.017
513-3M-CXP-09	10.18	171	20.20	0.026
513-3M-CXP-15	17.28	171	20.20	0.043
522-3M-CXP-06	7.46	174	20.55	0.017
522-3M-CXP-09	10.28	174	20.55	0.026
522-3M-CXP-15	17.35	174	20.55	0.044
525-3M-CXP-06	7.46	175	20.67	0.017
525-3M-CXP-09	10.31	175	20.67	0.026
525-3M-CXP-15	17.37	175	20.67	0.044

HTD 3M-CXP				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
537-3M-CXP-06	7.76	179	21.14	0.018
537-3M-CXP-09	10.37	179	21.14	0.024
537-3M-CXP-15	17.43	179	21.14	0.045
564-3M-CXP-06	7.98	188	22.20	0.019
564-3M-CXP-09	10.47	188	22.20	0.028
564-3M-CXP-15	17.50	188	22.20	0.047
570-3M-CXP-06	8.00	190	22.44	0.019
570-3M-CXP-09	10.55	190	22.44	0.028
570-3M-CXP-15	17.69	190	22.44	0.047
597-3M-CXP-06	8.05	199	23.50	0.021
597-3M-CXP-09	10.88	199	23.50	0.032
597-3M-CXP-15	18.44	199	23.50	0.053
600-3M-CXP-06	8.06	200	23.62	0.021
600-3M-CXP-09	10.91	200	23.62	0.032
600-3M-CXP-15	18.47	200	23.62	0.053
606-3M-CXP-06	8.10	202	23.86	0.020
606-3M-CXP-09	10.93	202	23.86	0.030
606-3M-CXP-15	18.55	202	23.86	0.050
612-3M-CXP-06	8.12	204	24.09	0.020
612-3M-CXP-09	10.96	204	24.09	0.031
612-3M-CXP-15	18.86	204	24.09	0.051
615-3M-CXP-06	8.15	205	24.21	0.021
615-3M-CXP-09	11.10	205	24.21	0.031
615-3M-CXP-15	18.92	205	24.21	0.052
633-3M-CXP-06	8.22	211	24.92	0.021
633-3M-CXP-09	11.37	211	24.92	0.032
633-3M-CXP-15	19.03	211	24.92	0.053
669-3M-CXP-06	8.28	223	26.34	0.022
669-3M-CXP-09	11.62	223	26.34	0.033
669-3M-CXP-15	19.57	223	26.34	0.056
708-3M-CXP-06	8.51	236	27.87	0.023
708-3M-CXP-09	12.04	236	27.87	0.035
708-3M-CXP-15	19.79	236	27.87	0.058
711-3M-CXP-06	8.53	237	27.99	0.024
711-3M-CXP-09	12.07	237	27.99	0.036
711-3M-CXP-15	19.81	237	27.99	0.059
738-3M-CXP-06	8.71	246	29.06	0.025
738-3M-CXP-09	12.32	246	29.06	0.037
738-3M-CXP-15	20.30	246	29.06	0.062
753-3M-CXP-06	8.81	251	29.65	0.026
753-3M-CXP-09	12.46	251	29.65	0.039
753-3M-CXP-15	20.57	251	29.65	0.066

HTD 3M-CXP				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
822-3M-CXP-06	9.28	274	32.36	0.027
822-3M-CXP-09	13.11	274	32.36	0.041
822-3M-CXP-15	21.83	274	32.36	0.068
843-3M-CXP-06	9.33	281	33.19	0.028
843-3M-CXP-09	13.17	281	33.19	0.042
843-3M-CXP-15	22.22	281	33.19	0.070
882-3M-CXP-06	9.97	294	34.72	0.029
882-3M-CXP-09	13.31	294	34.72	0.044
882-3M-CXP-15	22.99	294	34.72	0.073
945-3M-CXP-06	10.33	315	37.20	0.031
945-3M-CXP-09	13.92	315	37.20	0.047
945-3M-CXP-15	24.36	315	37.20	0.079
960-3M-CXP-06	10.45	320	37.80	0.032
960-3M-CXP-09	14.10	320	37.80	0.048
960-3M-CXP-15	24.53	320	37.80	0.081
1002-3M-CXP-06	10.79	334	39.45	0.033
1002-3M-CXP-09	14.59	334	39.45	0.050
1002-3M-CXP-15	25.02	334	39.45	0.083
1041-3M-CXP-06	10.97	347	40.98	0.034
1041-3M-CXP-09	14.98	347	40.98	0.051
1041-3M-CXP-15	25.50	347	40.98	0.085
1068-3M-CXP-06	11.10	356	42.50	0.035
1068-3M-CXP-09	15.25	356	42.50	0.053
1068-3M-CXP-15	25.83	356	42.50	0.089
1071-3M-CXP-06	11.11	357	42.17	0.036
1071-3M-CXP-09	15.28	357	42.17	0.054
1071-3M-CXP-15	25.87	357	42.17	0.091
1125-3M-CXP-06	11.37	375	44.29	0.037
1125-3M-CXP-09	15.83	375	44.29	0.056
1125-3M-CXP-15	26.53	375	44.29	0.094
1176-3M-CXP-06	11.62	392	46.30	0.038
1176-3M-CXP-09	16.35	392	46.30	0.058
1176-3M-CXP-15	27.15	392	46.30	0.099
1245-3M-CXP-06	11.96	415	49.02	0.039
1245-3M-CXP-09	17.05	415	49.02	0.060
1245-3M-CXP-15	27.99	415	49.02	0.100
1500-3M-CXP-06	13.22	500	59.06	0.040
1500-3M-CXP-09	19.64	500	59.06	0.062
1500-3M-CXP-15	31.09	500	59.06	0.104
1569-3M-CXP-06	13.56	523	61.77	0.043
1569-3M-CXP-09	20.34	523	61.77	0.065
1569-3M-CXP-15	31.93	523	61.77	0.110

CONTI SYNCHROFORCE® CXP

HTD 5M-CXP				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
200-5M-CXP-09	9.85	40	7.87	0.017
200-5M-CXP-15	13.69	40	7.87	0.025
200-5M-CXP-25	21.78	40	7.87	0.042
225-5M-CXP-09	10.08	45	8.86	0.018
225-5M-CXP-15	14.35	45	8.86	0.028
225-5M-CXP-25	22.71	45	8.86	0.047
265-5M-CXP-09	10.46	53	10.43	0.020
265-5M-CXP-15	15.41	53	10.43	0.033
265-5M-CXP-25	24.20	53	10.43	0.055
275-5M-CXP-09	10.55	55	10.83	0.021
275-5M-CXP-15	15.67	55	10.83	0.034
275-5M-CXP-25	24.57	55	10.83	0.057
285-5M-CXP-09	10.65	57	11.22	0.022
285-5M-CXP-15	15.93	57	11.22	0.036
285-5M-CXP-25	24.94	57	11.22	0.060
295-5M-CXP-09	10.79	59	11.61	0.023
295-5M-CXP-15	16.33	59	11.61	0.038
295-5M-CXP-25	25.50	59	11.61	0.063
300-5M-CXP-09	11.26	60	11.81	0.025
300-5M-CXP-15	17.12	60	11.81	0.041
300-5M-CXP-25	26.62	60	11.81	0.068
330-5M-CXP-09	11.26	66	12.99	0.026
330-5M-CXP-15	17.44	66	12.99	0.043
330-5M-CXP-25	27.06	66	12.99	0.071
350-5M-CXP-09	11.26	70	13.78	0.026
350-5M-CXP-15	17.65	70	13.78	0.044
350-5M-CXP-25	27.36	70	13.78	0.073
375-5M-CXP-09	11.59	75	14.76	0.028
375-5M-CXP-15	17.89	75	14.76	0.047
375-5M-CXP-25	28.75	75	14.76	0.079
385-5M-CXP-09	11.78	77	15.16	0.029
385-5M-CXP-15	17.94	77	15.16	0.049
385-5M-CXP-25	28.92	77	15.16	0.082
390-5M-CXP-09	11.88	78	15.35	0.029
390-5M-CXP-15	17.97	78	15.35	0.049
390-5M-CXP-25	29.00	78	15.35	0.800
400-5M-CXP-09	12.07	80	15.75	0.030
400-5M-CXP-15	18.02	80	15.75	0.050
400-5M-CXP-25	29.17	80	15.75	0.084
405-5M-CXP-09	12.13	81	15.94	0.300
405-5M-CXP-15	18.15	81	15.94	0.510
405-5M-CXP-25	29.31	81	15.94	0.860

HTD 5M-CXP				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
425-5M-CXP-09	12.36	85	16.73	0.032
425-5M-CXP-15	18.65	85	16.73	0.053
425-5M-CXP-25	29.87	85	16.73	0.089
450-5M-CXP-09	12.73	90	17.72	0.034
450-5M-CXP-15	19.56	90	17.72	0.057
450-5M-CXP-25	31.57	90	17.72	0.094
460-5M-CXP-09	13.21	92	18.11	0.035
460-5M-CXP-15	20.17	92	18.11	0.058
460-5M-CXP-25	31.68	92	18.11	0.096
475-5M-CXP-09	13.36	95	18.70	0.036
475-5M-CXP-15	20.23	95	18.70	0.060
475-5M-CXP-25	31.87	95	18.70	0.100
500-5M-CXP-09	13.43	100	19.69	0.037
500-5M-CXP-15	20.96	100	19.69	0.062
500-5M-CXP-25	32.97	100	19.69	0.103
525-5M-CXP-09	13.70	105	20.67	0.039
525-5M-CXP-15	21.70	105	20.67	0.065
525-5M-CXP-25	35.31	105	20.67	0.107
535-5M-CXP-09	13.81	107	21.06	0.040
535-5M-CXP-15	22.00	107	21.06	0.066
535-5M-CXP-25	36.24	107	21.06	0.110
550-5M-CXP-09	13.98	110	21.65	0.041
550-5M-CXP-15	22.06	110	21.65	0.068
550-5M-CXP-25	36.78	110	21.65	0.114
565-5M-CXP-09	14.14	113	22.24	0.043
565-5M-CXP-15	22.11	113	22.24	0.071
565-5M-CXP-25	37.32	113	22.24	0.118
600-5M-CXP-09	14.52	120	23.62	0.044
600-5M-CXP-15	23.00	120	23.62	0.074
600-5M-CXP-25	37.69	120	23.62	0.123
615-5M-CXP-09	14.83	123	24.21	0.046
615-5M-CXP-15	23.58	123	24.21	0.077
615-5M-CXP-25	38.75	123	24.21	0.129
620-5M-CXP-09	15.04	124	24.41	0.047
620-5M-CXP-15	23.73	124	24.41	0.078
620-5M-CXP-25	38.97	124	24.41	0.131
630-5M-CXP-09	15.46	126	24.80	0.048
630-5M-CXP-15	24.03	126	24.80	0.079
630-5M-CXP-25	39.42	126	24.80	0.133
635-5M-CXP-09	15.67	127	25.00	0.048
635-5M-CXP-15	24.18	127	25.00	0.080
635-5M-CXP-25	39.64	127	25.00	0.135

CONTI SYNCHROFORCE® CXP

HTD 5M-CXP				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
665-5M-CXP-09	15.76	133	26.18	0.049
665-5M-CXP-15	25.24	133	26.18	0.082
665-5M-CXP-25	41.55	133	26.18	0.137
700-5M-CXP-09	16.14	140	27.56	0.052
700-5M-CXP-15	25.72	140	27.56	0.086
700-5M-CXP-25	41.62	140	27.56	0.141
710-5M-CXP-09	16.25	142	27.95	0.053
710-5M-CXP-15	25.86	142	27.95	0.088
710-5M-CXP-25	41.64	142	27.95	0.146
740-5M-CXP-09	16.67	148	29.13	0.055
740-5M-CXP-15	26.78	148	29.13	0.091
740-5M-CXP-25	43.61	148	29.13	0.152
755-5M-CXP-09	16.91	151	29.72	0.560
755-5M-CXP-15	27.01	151	29.72	0.930
755-5M-CXP-25	44.05	151	29.72	0.156
800-5M-CXP-09	17.63	160	31.50	0.059
800-5M-CXP-15	27.71	160	31.50	0.099
800-5M-CXP-25	45.38	160	31.50	0.164
835-5M-CXP-09	18.01	167	32.87	0.063
835-5M-CXP-15	28.76	167	32.87	0.105
835-5M-CXP-25	47.29	167	32.87	0.175
840-5M-CXP-09	18.06	168	33.07	0.064
840-5M-CXP-15	28.88	168	33.07	0.108
840-5M-CXP-25	47.45	168	33.07	0.179
860-5M-CXP-09	18.26	172	33.86	0.066
860-5M-CXP-15	29.34	172	33.86	0.110
860-5M-CXP-25	48.09	172	33.86	0.183
890-5M-CXP-09	18.55	178	35.04	0.067
890-5M-CXP-15	30.04	178	35.04	0.112
890-5M-CXP-25	49.06	178	35.04	0.187
900-5M-CXP-09	18.82	180	35.43	0.068
900-5M-CXP-15	30.14	180	35.43	0.114
900-5M-CXP-25	49.64	180	35.43	0.191
925-5M-CXP-09	19.49	185	36.42	0.070
925-5M-CXP-15	30.40	185	36.42	0.116
925-5M-CXP-25	51.08	185	36.42	0.194
950-5M-CXP-09	19.66	190	37.40	0.070
950-5M-CXP-15	31.71	190	37.40	0.117
950-5M-CXP-25	51.99	190	37.40	0.195
1000-5M-CXP-09	20.44	200	39.37	0.074
1000-5M-CXP-15	32.20	200	39.37	0.123
1000-5M-CXP-25	52.73	200	39.37	0.206

HTD 5M-CXP				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
1050-5M-CXP-09	21.34	210	41.34	0.079
1050-5M-CXP-15	34.11	210	41.34	0.132
1050-5M-CXP-25	54.76	210	41.34	0.220
1125-5M-CXP-09	21.85	225	44.29	0.085
1125-5M-CXP-15	36.37	225	44.29	0.142
1125-5M-CXP-25	58.65	225	44.29	0.236
1200-5M-CXP-09	22.68	240	47.24	0.090
1200-5M-CXP-15	38.19	240	47.24	0.150
1200-5M-CXP-25	62.59	240	47.24	0.255
1270-5M-CXP-09	23.45	254	50.00	0.096
1270-5M-CXP-15	39.89	254	50.00	0.160
1270-5M-CXP-25	66.27	254	50.00	0.266
1420-5M-CXP-09	24.75	284	55.91	0.107
1420-5M-CXP-15	41.33	284	55.91	0.179
1420-5M-CXP-25	69.91	284	55.91	0.298
1500-5M-CXP-09	26.34	300	59.06	0.120
1500-5M-CXP-15	43.62	300	59.06	0.186
1500-5M-CXP-25	73.38	300	59.06	0.311
1595-5M-CXP-09	28.22	319	62.80	0.118
1595-5M-CXP-15	46.34	319	62.80	0.197
1595-5M-CXP-25	77.50	319	62.80	0.328
1690-5M-CXP-09	30.11	338	66.54	0.125
1690-5M-CXP-15	48.48	338	66.54	0.208
1690-5M-CXP-25	82.75	338	66.54	0.347
1800-5M-CXP-09	31.23	360	70.87	0.136
1800-5M-CXP-15	50.77	360	70.87	0.229
1800-5M-CXP-25	86.72	360	70.87	0.401
2000-5M-CXP-09	33.27	400	78.74	0.148
2000-5M-CXP-15	54.93	400	78.74	0.247
2000-5M-CXP-25	93.95	400	78.74	0.411

HTD 8M-CXP				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
288-8M-CXP-20	24.48	36	11.34	0.062
288-8M-CXP-30	33.96	36	11.34	0.110
288-8M-CXP-50	49.69	36	11.34	0.172
288-8M-CXP-85	80.56	36	11.34	0.289
304-8M-CXP-20	24.88	38	12.00	0.066
304-8M-CXP-30	34.60	38	12.00	0.114
304-8M-CXP-50	51.03	38	12.00	0.180
304-8M-CXP-85	82.96	38	12.00	0.303
352-8M-CXP-20	26.08	44	13.86	0.078
352-8M-CXP-30	36.52	44	13.86	0.126
352-8M-CXP-50	55.05	44	13.86	0.204
352-8M-CXP-85	90.16	44	13.86	0.345
376-8M-CXP-20	26.68	47	14.80	0.084
376-8M-CXP-30	37.48	47	14.80	0.132
376-8M-CXP-50	57.06	47	14.80	0.216
376-8M-CXP-85	93.76	47	14.80	0.366
416-8M-CXP-20	27.28	50	15.75	0.090
416-8M-CXP-30	38.44	50	15.75	0.138
416-8M-CXP-50	59.07	50	15.75	0.228
416-8M-CXP-85	97.36	50	15.75	0.387
424-8M-CXP-20	27.88	53	16.69	0.096
424-8M-CXP-30	39.40	53	16.69	0.144
424-8M-CXP-50	61.08	53	16.69	0.240
424-8M-CXP-85	100.96	53	16.69	0.408
472-8M-CXP-20	29.07	59	18.58	0.106
472-8M-CXP-30	41.33	59	18.58	0.159
472-8M-CXP-50	65.12	59	18.58	0.266
472-8M-CXP-85	108.15	59	18.58	0.452
480-8M-CXP-20	29.27	60	18.90	0.108
480-8M-CXP-30	41.71	60	18.90	0.162
480-8M-CXP-50	65.79	60	18.90	0.270
480-8M-CXP-85	109.35	60	18.90	0.459
560-8M-CXP-20	31.26	70	22.05	0.125
560-8M-CXP-30	45.52	70	22.05	0.188
560-8M-CXP-50	72.52	70	22.05	0.313
560-8M-CXP-85	121.34	70	22.05	0.533
600-8M-CXP-20	33.71	75	23.62	0.134
600-8M-CXP-30	48.19	75	23.62	0.201
600-8M-CXP-50	76.62	75	23.62	0.334
600-8M-CXP-85	130.54	75	23.62	0.568
624-8M-CXP-20	34.37	78	24.57	0.139
624-8M-CXP-30	49.56	78	24.57	0.208
624-8M-CXP-50	79.16	78	24.57	0.347
624-8M-CXP-85	132.49	78	24.57	0.593

HTD 8M-CXP				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
640-8M-CXP-20	34.81	80	25.20	0.142
640-8M-CXP-30	50.47	80	25.20	0.214
640-8M-CXP-50	80.85	80	25.20	0.356
640-8M-CXP-85	133.79	80	25.20	0.606
656-8M-CXP-20	35.40	82	25.83	0.149
656-8M-CXP-30	50.72	82	25.83	0.221
656-8M-CXP-50	81.65	82	25.83	0.367
656-8M-CXP-85	135.67	82	25.83	0.629
688-8M-CXP-20	36.58	86	27.09	0.157
688-8M-CXP-30	51.21	86	27.09	0.230
688-8M-CXP-50	83.26	86	27.09	0.385
688-8M-CXP-85	139.44	86	27.09	0.691
720-8M-CXP-20	37.76	90	28.35	0.160
720-8M-CXP-30	51.70	90	28.35	0.239
720-8M-CXP-50	84.87	90	28.35	0.399
720-8M-CXP-85	143.20	90	28.35	0.678
776-8M-CXP-20	40.22	97	30.55	0.172
776-8M-CXP-30	56.03	97	30.55	0.258
776-8M-CXP-50	91.58	97	30.55	0.429
776-8M-CXP-85	152.27	97	30.55	0.730
784-8M-CXP-20	40.57	98	30.87	0.174
784-8M-CXP-30	56.65	98	30.87	0.260
784-8M-CXP-50	92.54	98	30.87	0.434
784-8M-CXP-85	150.46	98	30.87	0.738
800-8M-CXP-20	41.27	100	31.50	0.177
800-8M-CXP-30	57.89	100	31.50	0.266
800-8M-CXP-50	94.46	100	31.50	0.443
800-8M-CXP-85	156.16	100	31.50	0.752
880-8M-CXP-20	44.03	110	34.65	0.194
880-8M-CXP-30	60.67	110	34.65	0.291
880-8M-CXP-50	99.56	110	34.65	0.486
880-8M-CXP-85	166.12	110	34.65	0.826
912-8M-CXP-20	44.83	114	35.91	0.199
912-8M-CXP-30	62.01	114	35.91	0.300
912-8M-CXP-50	102.25	114	35.91	0.501
912-8M-CXP-85	168.58	114	35.91	0.843
920-8M-CXP-20	45.03	115	36.22	0.203
920-8M-CXP-30	62.35	115	36.22	0.304
920-8M-CXP-50	102.92	115	36.22	0.507
920-8M-CXP-85	169.20	115	36.22	0.862
960-8M-CXP-20	46.04	120	37.80	0.212
960-8M-CXP-30	64.48	120	37.80	0.317
960-8M-CXP-50	109.46	120	37.80	0.529
960-8M-CXP-85	182.22	120	37.80	0.899

HTD 8M-CXP				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
1008-8M-CXP-20	47.83	126	39.69	0.222
1008-8M-CXP-30	67.10	126	39.69	0.333
1008-8M-CXP-50	110.92	126	39.69	0.555
1008-8M-CXP-85	189.03	126	39.69	0.943
1040-8M-CXP-20	49.02	130	40.94	0.229
1040-8M-CXP-30	68.84	130	40.94	0.343
1040-8M-CXP-50	111.89	130	40.94	0.572
1040-8M-CXP-85	193.57	130	40.94	0.972
1120-8M-CXP-20	49.58	140	44.09	0.246
1120-8M-CXP-30	73.14	140	44.09	0.369
1120-8M-CXP-50	119.53	140	44.09	0.615
1120-8M-CXP-85	205.94	140	44.09	1.045
1200-8M-CXP-20	52.73	150	47.24	0.263
1200-8M-CXP-30	75.80	150	47.24	0.394
1200-8M-CXP-50	126.69	150	47.24	0.657
1200-8M-CXP-85	209.82	150	47.24	1.118
1280-8M-CXP-20	56.21	160	50.39	0.281
1280-8M-CXP-30	82.27	160	50.39	0.421
1280-8M-CXP-50	129.79	160	50.39	0.701
1280-8M-CXP-85	223.11	160	50.39	1.192
1304-8M-CXP-20	57.25	163	51.34	0.286
1304-8M-CXP-30	84.21	163	51.34	0.429
1304-8M-CXP-50	130.72	163	51.34	0.715
1304-8M-CXP-85	227.10	163	51.34	1.215
1328-8M-CXP-20	58.29	166	52.28	0.291
1328-8M-CXP-30	86.15	166	52.28	0.437
1328-8M-CXP-50	131.65	166	52.28	0.729
1328-8M-CXP-85	231.09	166	52.28	1.238
1360-8M-CXP-20	59.68	170	53.54	0.298
1360-8M-CXP-30	88.74	170	53.54	0.448
1360-8M-CXP-50	132.89	170	53.54	0.748
1360-8M-CXP-85	236.41	170	53.54	1.269
1424-8M-CXP-20	62.46	178	56.06	0.312
1424-8M-CXP-30	93.92	178	56.06	0.470
1424-8M-CXP-50	135.37	178	56.06	0.786
1424-8M-CXP-85	247.05	178	56.06	1.331
1440-8M-CXP-20	61.12	180	56.69	0.315
1440-8M-CXP-30	90.37	180	56.69	0.472
1440-8M-CXP-50	143.30	180	56.69	0.787
1440-8M-CXP-85	242.62	180	56.69	1.338
1520-8M-CXP-20	62.78	190	59.84	0.341
1520-8M-CXP-30	90.77	190	59.84	0.513
1520-8M-CXP-50	153.80	190	59.84	0.851
1520-8M-CXP-85	249.05	190	59.84	1.467

HTD 8M-CXP				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
1600-8M-CXP-20	65.33	200	62.99	0.349
1600-8M-CXP-30	96.49	200	62.99	0.524
1600-8M-CXP-50	158.28	200	62.99	0.873
1600-8M-CXP-85	264.56	200	62.99	1.485
1760-8M-CXP-20	70.09	220	69.29	0.384
1760-8M-CXP-30	102.06	220	69.29	0.576
1760-8M-CXP-50	171.70	220	69.29	0.960
1760-8M-CXP-85	281.34	220	69.29	1.631
1800-8M-CXP-20	73.32	225	70.87	0.393
1800-8M-CXP-30	104.76	225	70.87	0.589
1800-8M-CXP-50	177.24	225	70.87	0.981
1800-8M-CXP-85	294.11	225	70.87	1.668
2000-8M-CXP-20	81.93	250	78.74	0.436
2000-8M-CXP-30	117.27	250	78.74	0.654
2000-8M-CXP-50	195.72	250	78.74	1.089
2000-8M-CXP-85	327.33	250	78.74	1.852
2248-8M-CXP-20	89.48	281	88.50	0.486
2248-8M-CXP-30	130.43	281	88.50	0.710
2248-8M-CXP-50	212.52	281	88.50	1.206
2248-8M-CXP-85	362.34	281	88.50	2.003
2400-8M-CXP-20	94.10	300	94.49	0.522
2400-8M-CXP-30	138.49	300	94.49	0.783
2400-8M-CXP-50	222.81	300	94.49	1.305
2400-8M-CXP-85	383.80	300	94.49	2.218
2800-8M-CXP-20	106.26	350	110.24	0.616
2800-8M-CXP-30	159.70	350	110.24	0.974
2800-8M-CXP-50	249.89	350	110.24	1.564
2800-8M-CXP-85	440.27	350	110.24	2.783
3008-8M-CXP-20	112.58	376	118.43	0.665
3008-8M-CXP-30	170.73	376	118.43	1.073
3008-8M-CXP-50	263.97	376	118.43	1.699
3008-8M-CXP-85	469.63	376	118.43	3.077
3408-8M-CXP-20	124.73	426	134.17	0.759
3408-8M-CXP-30	191.94	426	134.17	1.263
3408-8M-CXP-50	291.05	426	134.17	1.959
3408-8M-CXP-85	526.09	426	134.17	3.642
3808-8M-CXP-20	136.88	476	149.92	0.853
3808-8M-CXP-30	213.15	476	149.92	1.453
3808-8M-CXP-50	318.13	476	149.92	2.219
3808-8M-CXP-85	582.55	476	149.92	4.207

CONTI SYNCHROFORCE® CXP

HTD 14M-CXP				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
966-14M-CXP-40	223.81	69	38.03	0.094
966-14M-CXP-55	292.44	69	38.03	0.129
966-14M-CXP-85	418.45	69	38.03	0.199
966-14M-CXP-115	547.75	69	38.03	0.270
966-14M-CXP-170	817.28	69	38.03	0.399
1050-14M-CXP-40	232.50	75	41.34	0.423
1050-14M-CXP-55	301.19	75	41.34	0.581
1050-14M-CXP-85	435.78	75	41.34	0.898
1050-14M-CXP-115	572.72	75	41.34	1.215
1050-14M-CXP-170	855.83	75	41.34	1.797
1190-14M-CXP-40	246.97	85	46.85	0.971
1190-14M-CXP-55	315.77	85	46.85	1.335
1190-14M-CXP-85	464.66	85	46.85	2.063
1190-14M-CXP-115	614.33	85	46.85	2.791
1190-14M-CXP-170	920.07	85	46.85	4.127
1400-14M-CXP-40	263.35	100	55.12	1.139
1400-14M-CXP-55	346.22	100	55.12	1.565
1400-14M-CXP-85	510.39	100	55.12	2.419
1400-14M-CXP-115	669.19	100	55.12	3.273
1400-14M-CXP-170	1,011.50	100	55.12	4.839
1610-14M-CXP-40	281.67	115	63.39	1.305
1610-14M-CXP-55	389.84	115	63.39	1.794
1610-14M-CXP-85	567.07	115	63.39	2.773
1610-14M-CXP-115	765.86	115	63.39	3.751
1610-14M-CXP-170	1,068.20	115	63.39	5.545
1778-14M-CXP-40	311.43	127	70.00	0.356
1778-14M-CXP-55	400.96	127	70.00	0.489
1778-14M-CXP-85	598.63	127	70.00	0.756
1778-14M-CXP-115	784.16	127	70.00	1.023
1778-14M-CXP-170	1,150.24	127	70.00	1.512
1890-14M-CXP-40	324.10	135	74.41	1.528
1890-14M-CXP-55	420.12	135	74.41	2.101
1890-14M-CXP-85	617.79	135	74.41	3.247
1890-14M-CXP-115	851.67	135	74.41	4.393
1890-14M-CXP-170	1,241.16	135	74.41	6.494
2100-14M-CXP-40	341.38	150	82.68	1.695
2100-14M-CXP-55	470.27	150	82.68	2.331
2100-14M-CXP-85	685.30	150	82.68	3.602
2100-14M-CXP-115	942.09	150	82.68	4.873
2100-14M-CXP-170	1,316.88	150	82.68	7.204

HTD 14M-CXP				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
2310-14M-CXP-40	366.78	165	90.94	1.862
2310-14M-CXP-55	501.04	165	90.94	2.560
2310-14M-CXP-85	731.83	165	90.94	3.956
2310-14M-CXP-115	1,005.82	165	90.94	5.352
2310-14M-CXP-170	1,428.31	165	90.94	7.912
2450-14M-CXP-40	377.83	175	96.46	1.973
2450-14M-CXP-55	512.48	175	96.46	2.713
2450-14M-CXP-85	780.26	175	96.46	4.192
2450-14M-CXP-115	1,041.99	175	96.46	5.672
2450-14M-CXP-170	1,511.12	175	96.46	8.384
2590-14M-CXP-40	403.24	185	101.97	2.084
2590-14M-CXP-55	534.75	185	101.97	2.865
2590-14M-CXP-85	812.51	185	101.97	4.428
2590-14M-CXP-115	1,063.62	185	101.97	5.991
2590-14M-CXP-170	1,548.75	185	101.97	8.857
2800-14M-CXP-40	437.75	200	110.24	2.251
2800-14M-CXP-55	579.44	200	110.24	3.095
2800-14M-CXP-85	870.03	200	110.24	4.784
2800-14M-CXP-115	1,156.38	200	110.24	6.472
2800-14M-CXP-170	1,710.00	200	110.24	9.567
3150-14M-CXP-40	476.70	225	124.02	2.529
3150-14M-CXP-55	635.88	225	124.02	3.478
3150-14M-CXP-85	957.75	225	124.02	5.375
3150-14M-CXP-115	1,308.84	225	124.02	7.272
3150-14M-CXP-170	1,838.38	225	124.02	10.750
3360-14M-CXP-40	508.56	240	132.28	2.657
3360-14M-CXP-55	680.12	240	132.28	3.654
3360-14M-CXP-85	984.60	240	132.28	5.647
3360-14M-CXP-115	1,357.69	240	132.28	7.640
3360-14M-CXP-170	1,931.32	240	132.28	11.294
3500-14M-CXP-40	524.70	250	137.80	2.808
3500-14M-CXP-55	700.97	250	137.80	3.861
3500-14M-CXP-85	1,045.51	250	137.80	5.967
3500-14M-CXP-115	1,415.09	250	137.80	8.073
3500-14M-CXP-170	2,032.86	250	137.80	11.934
3668-14M-CXP-40	539.11	262	144.41	2.941
3668-14M-CXP-55	729.14	262	144.41	4.044
3668-14M-CXP-85	1,088.32	262	144.41	6.250
3668-14M-CXP-115	1,466.26	262	144.41	8.456
3668-14M-CXP-170	2,455.89	262	144.41	12.500

CONTI SYNCHROFORCE® CXP

HTD 14M-CXP				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
3850-14M-CXP-40	554.71	275	151.57	3.086
3850-14M-CXP-55	759.66	275	151.57	4.243
3850-14M-CXP-85	1,134.70	275	151.57	6.557
3850-14M-CXP-115	1,521.69	275	151.57	8.871
3850-14M-CXP-170	2,289.17	275	151.57	13.114
4326-14M-CXP-40	638.08	309	170.31	3.465
4326-14M-CXP-55	847.63	309	170.31	4.764
4326-14M-CXP-85	1,262.15	309	170.31	7.362
4326-14M-CXP-115	1,733.74	309	170.31	9.961
4326-14M-CXP-170	2,549.08	309	170.31	14.724
4578-14M-CXP-40	653.36	327	180.24	3.664
4578-14M-CXP-55	896.65	327	180.24	5.039
4578-14M-CXP-85	1,346.20	327	180.24	7.787
4578-14M-CXP-115	1,805.38	327	180.24	10.535
4578-14M-CXP-170	2,570.82	327	180.24	15.574

STD 8M-CXP				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
440-S8M-CXP-20	28.31	55	17.32	0.099
440-S8M-CXP-30	39.86	55	17.32	0.149
440-S8M-CXP-50	62.49	55	17.32	0.249
440-S8M-CXP-85	103.47	55	17.32	0.423
480-S8M-CXP-20	29.30	60	18.90	0.108
480-S8M-CXP-30	41.75	60	18.90	0.162
480-S8M-CXP-50	65.86	60	18.90	0.270
480-S8M-CXP-85	109.46	60	18.90	0.459
528-S8M-CXP-20	30.50	66	20.79	0.118
528-S8M-CXP-30	44.04	66	20.79	0.178
528-S8M-CXP-50	69.90	66	20.79	0.296
528-S8M-CXP-85	116.66	66	20.79	0.503
560-S8M-CXP-20	31.29	70	22.05	0.125
560-S8M-CXP-30	45.57	70	22.05	0.188
560-S8M-CXP-50	72.59	70	22.05	0.313
560-S8M-CXP-85	121.46	70	22.05	0.533
600-S8M-CXP-20	33.74	75	23.62	0.134
600-S8M-CXP-30	48.24	75	23.62	0.201
600-S8M-CXP-50	76.70	75	23.62	0.334
600-S8M-CXP-85	130.67	75	23.62	0.568
632-S8M-CXP-20	34.62	79	24.88	0.141
632-S8M-CXP-30	50.06	79	24.88	0.211
632-S8M-CXP-50	80.08	79	24.88	0.352
632-S8M-CXP-85	133.28	79	24.88	0.598
640-S8M-CXP-20	34.84	80	25.20	0.142
640-S8M-CXP-30	50.52	80	25.20	0.214
640-S8M-CXP-50	80.93	80	25.20	0.356
640-S8M-CXP-85	133.92	80	25.20	0.606
656-S8M-CXP-20	35.44	82	25.83	0.146
656-S8M-CXP-30	50.77	82	25.83	0.219
656-S8M-CXP-50	84.15	82	25.83	0.365
656-S8M-CXP-85	135.81	82	25.83	0.620
672-S8M-CXP-20	36.04	84	26.46	0.150
672-S8M-CXP-30	51.01	84	26.46	0.224
672-S8M-CXP-50	83.36	84	26.46	0.374
672-S8M-CXP-85	137.70	84	26.46	0.635
688-S8M-CXP-20	36.62	86	27.09	0.153
688-S8M-CXP-30	51.26	86	27.09	0.229
688-S8M-CXP-50	82.55	86	27.09	0.382
688-S8M-CXP-85	139.57	86	27.09	0.649

STD 8M-CXP				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
696-S8M-CXP-20	36.92	87	27.40	0.155
696-S8M-CXP-30	51.38	87	27.40	0.232
696-S8M-CXP-50	83.15	87	27.40	0.386
696-S8M-CXP-85	140.52	87	27.40	0.656
712-S8M-CXP-20	37.51	89	28.03	0.158
712-S8M-CXP-30	51.62	89	28.03	0.237
712-S8M-CXP-50	84.36	89	28.03	0.395
712-S8M-CXP-85	142.40	89	28.03	0.671
720-S8M-CXP-20	37.80	90	28.35	0.160
720-S8M-CXP-30	51.75	90	28.35	0.239
720-S8M-CXP-50	84.95	90	28.35	0.399
720-S8M-CXP-85	143.34	90	28.35	0.678
728-S8M-CXP-20	38.16	91	28.66	0.161
728-S8M-CXP-30	52.14	91	28.66	0.242
728-S8M-CXP-50	85.92	91	28.66	0.403
728-S8M-CXP-85	144.64	91	28.66	0.685
736-S8M-CXP-20	38.51	92	28.98	0.164
736-S8M-CXP-30	52.53	92	28.98	0.247
736-S8M-CXP-50	86.88	92	28.98	0.412
736-S8M-CXP-85	145.94	92	28.98	0.693
760-S8M-CXP-20	39.56	95	29.92	0.168
760-S8M-CXP-30	53.69	95	29.92	0.255
760-S8M-CXP-50	89.75	95	29.92	0.424
760-S8M-CXP-85	149.83	95	29.92	0.765
768-S8M-CXP-20	39.91	96	30.55	0.170
768-S8M-CXP-30	54.08	96	30.55	0.278
768-S8M-CXP-50	90.71	96	30.55	0.428
768-S8M-CXP-85	151.13	96	30.55	0.729
784-S8M-CXP-20	40.61	98	30.87	0.174
784-S8M-CXP-30	54.85	98	30.87	0.261
784-S8M-CXP-50	92.63	98	30.87	0.434
784-S8M-CXP-85	153.71	98	30.87	0.716
792-S8M-CXP-20	40.96	99	31.18	0.176
792-S8M-CXP-30	55.24	99	31.18	0.263
792-S8M-CXP-50	93.59	99	31.18	0.438
792-S8M-CXP-85	155.01	99	31.18	0.734
800-S8M-CXP-20	41.31	100	31.50	0.177
800-S8M-CXP-30	55.63	100	31.50	0.266
800-S8M-CXP-50	94.55	100	31.50	0.443
800-S8M-CXP-85	156.32	100	31.50	0.752

STD 8M-CXP				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
824-S8M-CXP-20	42.30	103	32.44	0.178
824-S8M-CXP-30	57.66	103	32.44	0.266
824-S8M-CXP-50	95.47	103	32.44	0.444
824-S8M-CXP-85	161.43	103	32.44	0.754
848-S8M-CXP-20	43.17	106	33.39	0.181
848-S8M-CXP-30	59.36	106	33.39	0.272
848-S8M-CXP-50	96.80	106	33.39	0.453
848-S8M-CXP-85	165.14	106	33.39	0.770
864-S8M-CXP-20	43.63	108	34.02	0.188
864-S8M-CXP-30	60.05	108	34.02	0.282
864-S8M-CXP-50	98.23	108	34.02	0.469
864-S8M-CXP-85	165.71	108	34.02	0.628
880-S8M-CXP-20	44.07	110	34.65	0.194
880-S8M-CXP-30	60.73	110	34.65	0.291
880-S8M-CXP-50	99.66	110	34.65	0.486
880-S8M-CXP-85	166.29	110	34.65	0.826
912-S8M-CXP-20	44.25	114	35.91	0.198
912-S8M-CXP-30	61.41	114	35.91	0.296
912-S8M-CXP-50	101.01	114	35.91	0.494
912-S8M-CXP-85	172.73	114	35.91	0.840
920-S8M-CXP-20	44.51	115	36.22	0.203
920-S8M-CXP-30	62.41	115	36.22	0.304
920-S8M-CXP-50	103.02	115	36.22	0.507
920-S8M-CXP-85	169.37	115	36.22	0.862
944-S8M-CXP-20	45.46	118	37.17	0.223
944-S8M-CXP-30	63.69	118	37.17	0.334
944-S8M-CXP-50	106.95	118	37.17	0.556
944-S8M-CXP-85	177.19	118	37.17	0.946
960-S8M-CXP-20	46.09	120	37.80	0.212
960-S8M-CXP-30	64.54	120	37.80	0.317
960-S8M-CXP-50	109.57	120	37.80	0.529
960-S8M-CXP-85	182.40	120	37.80	0.899
992-S8M-CXP-20	47.28	124	39.06	0.223
992-S8M-CXP-30	66.53	124	39.06	0.335
992-S8M-CXP-50	110.54	124	39.06	0.546
992-S8M-CXP-85	186.95	124	39.06	0.948
1000-S8M-CXP-20	47.58	125	39.37	0.224
1000-S8M-CXP-30	67.04	125	39.37	0.336
1000-S8M-CXP-50	110.79	125	39.37	0.550
1000-S8M-CXP-85	188.08	125	39.37	0.952

STD 8M-CXP				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
1056-S8M-CXP-20	49.31	132	41.57	0.232
1056-S8M-CXP-30	70.85	132	41.57	0.349
1056-S8M-CXP-50	113.65	132	41.57	0.581
1056-S8M-CXP-85	196.55	132	41.57	0.987
1064-S8M-CXP-20	49.42	133	41.89	0.234
1064-S8M-CXP-30	71.51	133	41.89	0.351
1064-S8M-CXP-50	114.46	133	41.89	0.585
1064-S8M-CXP-85	197.94	133	41.89	0.995
1072-S8M-CXP-20	49.45	134	42.20	0.236
1072-S8M-CXP-30	71.76	134	42.20	0.354
1072-S8M-CXP-50	115.21	134	42.20	0.590
1072-S8M-CXP-85	199.11	134	42.20	1.002
1120-S8M-CXP-20	49.63	140	44.09	0.246
1120-S8M-CXP-30	73.21	140	44.09	0.369
1120-S8M-CXP-50	119.65	140	44.09	0.615
1120-S8M-CXP-85	206.15	140	44.09	1.045
1136-S8M-CXP-20	50.44	142	44.72	0.249
1136-S8M-CXP-30	73.70	142	44.72	0.374
1136-S8M-CXP-50	121.55	142	44.72	0.623
1136-S8M-CXP-85	206.56	142	44.72	1.059
1160-S8M-CXP-20	51.66	145	45.67	0.254
1160-S8M-CXP-30	74.43	145	45.67	0.382
1160-S8M-CXP-50	124.38	145	45.67	0.636
1160-S8M-CXP-85	207.18	145	45.67	1.081
1168-S8M-CXP-20	51.88	146	45.98	0.256
1168-S8M-CXP-30	74.72	146	45.98	0.384
1168-S8M-CXP-50	124.11	146	45.98	0.640
1168-S8M-CXP-85	207.75	146	45.98	1.089
1176-S8M-CXP-20	52.10	147	46.30	0.258
1176-S8M-CXP-30	75.01	147	46.30	0.387
1176-S8M-CXP-50	124.79	147	46.30	0.645
1176-S8M-CXP-85	208.33	147	46.30	1.096
1184-S8M-CXP-20	52.34	148	46.61	0.260
1184-S8M-CXP-30	75.30	148	46.61	0.389
1184-S8M-CXP-50	125.46	148	46.61	0.649
1184-S8M-CXP-85	208.88	148	46.61	1.103
1200-S8M-CXP-20	52.78	150	47.24	0.263
1200-S8M-CXP-30	75.88	150	47.24	0.394
1200-S8M-CXP-50	126.82	150	47.24	0.657
1200-S8M-CXP-85	215.96	150	47.24	1.118

CONTI SYNCHROFORCE® CXP

STD 8M-CXP				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
1216-S8M-CXP-20	53.48	152	47.87	0.267
1216-S8M-CXP-30	77.17	152	47.87	0.400
1216-S8M-CXP-50	128.36	152	47.87	0.666
1216-S8M-CXP-85	212.69	152	47.87	1.133
1240-S8M-CXP-20	54.52	155	48.82	0.272
1240-S8M-CXP-30	79.12	155	48.82	0.408
1240-S8M-CXP-50	128.36	155	48.82	0.679
1240-S8M-CXP-85	216.68	155	48.82	1.155
1256-S8M-CXP-20	55.22	157	49.45	0.275
1256-S8M-CXP-30	80.41	157	49.45	0.413
1256-S8M-CXP-50	128.99	157	49.45	0.687
1256-S8M-CXP-85	219.34	157	49.45	1.170
1264-S8M-CXP-20	55.58	158	49.76	0.277
1264-S8M-CXP-30	81.05	158	49.76	0.416
1264-S8M-CXP-50	129.30	158	49.76	0.692
1264-S8M-CXP-85	220.68	158	49.76	1.177
1280-S8M-CXP-20	56.27	160	50.39	0.281
1280-S8M-CXP-30	82.35	160	50.39	0.421
1280-S8M-CXP-50	130.286	160	50.39	0.700
1280-S8M-CXP-85	223.33	160	50.39	1.192
1296-S8M-CXP-20	56.76	162	51.02	0.284
1296-S8M-CXP-30	83.43	162	51.02	0.426
1296-S8M-CXP-50	131.27	162	51.02	0.710
1296-S8M-CXP-85	225.89	162	51.02	1.207
1304-S8M-CXP-20	57.01	163	51.34	0.286
1304-S8M-CXP-30	83.97	163	51.34	0.429
1304-S8M-CXP-50	131.95	163	51.34	0.714
1304-S8M-CXP-85	227.16	163	51.34	1.214
1312-S8M-CXP-20	57.14	164	51.65	0.286
1312-S8M-CXP-30	84.24	164	51.65	0.431
1312-S8M-CXP-50	132.63	164	51.65	0.717
1312-S8M-CXP-85	228.44	164	51.65	1.218
1344-S8M-CXP-20	58.06	168	52.91	0.292
1344-S8M-CXP-30	85.61	168	52.91	0.448
1344-S8M-CXP-50	135.33	168	52.91	0.743
1344-S8M-CXP-85	233.55	168	52.91	1.255
1368-S8M-CXP-20	59.32	171	53.86	0.295
1368-S8M-CXP-30	86.81	171	53.86	0.454
1368-S8M-CXP-50	137.36	171	53.86	0.753
1368-S8M-CXP-85	237.37	171	53.86	1.271

STD 8M-CXP				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
1400-S8M-CXP-20	59.94	175	55.12	0.300
1400-S8M-CXP-30	88.44	175	55.12	0.459
1400-S8M-CXP-50	140.06	175	55.12	0.762
1400-S8M-CXP-85	242.48	175	55.12	1.285
1408-S8M-CXP-20	60.19	176	55.43	0.302
1408-S8M-CXP-30	88.84	176	55.43	0.461
1408-S8M-CXP-50	140.74	176	55.43	0.765
1408-S8M-CXP-85	243.76	176	55.43	1.288
1440-S8M-CXP-20	61.18	180	56.69	0.315
1440-S8M-CXP-30	90.46	180	56.69	0.472
1440-S8M-CXP-50	143.44	180	56.69	0.787
1440-S8M-CXP-85	248.86	180	56.69	1.338
1480-S8M-CXP-20	62.01	185	58.27	0.324
1480-S8M-CXP-30	90.66	185	58.27	0.485
1480-S8M-CXP-50	148.69	185	58.27	0.809
1480-S8M-CXP-85	254.53	185	58.27	1.375
1512-S8M-CXP-20	62.67	189	59.53	0.330
1512-S8M-CXP-30	90.82	189	59.53	0.495
1512-S8M-CXP-50	152.89	189	59.53	0.826
1512-S8M-CXP-85	259.06	189	59.53	1.404
1552-S8M-CXP-20	63.91	194	61.10	0.339
1552-S8M-CXP-30	93.43	194	61.10	0.508
1552-S8M-CXP-50	155.42	194	61.10	0.852
1552-S8M-CXP-85	261.68	194	61.10	1.441
1600-S8M-CXP-20	65.40	200	62.99	0.349
1600-S8M-CXP-30	96.59	200	62.99	0.524
1600-S8M-CXP-50	158.44	200	62.99	0.873
1600-S8M-CXP-85	264.82	200	62.99	1.485
1624-S8M-CXP-20	66.11	203	63.94	0.355
1624-S8M-CXP-30	97.42	203	63.94	0.532
1624-S8M-CXP-50	160.46	203	63.94	0.589
1624-S8M-CXP-85	267.35	203	63.94	1.507
1760-S8M-CXP-20	70.16	220	69.29	0.384
1760-S8M-CXP-30	102.16	220	69.29	0.576
1760-S8M-CXP-50	171.87	220	69.29	0.960
1760-S8M-CXP-85	281.62	220	69.29	1.631
1776-S8M-CXP-20	71.45	222	69.92	0.387
1776-S8M-CXP-30	103.25	222	69.92	0.581
1776-S8M-CXP-50	174.10	222	69.92	0.968
1776-S8M-CXP-85	286.74	222	69.92	1.646

CONTI SYNCHROFORCE® CXP




STD 8M-CXP				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
1800-S8M-CXP-20	73.39	225	70.87	0.393
1800-S8M-CXP-30	104.86	225	70.87	0.589
1800-S8M-CXP-50	177.42	225	70.87	0.981
1800-S8M-CXP-85	294.40	225	70.87	1.668
1816-S8M-CXP-20	74.08	227	71.50	0.396
1816-S8M-CXP-30	105.87	227	71.50	0.594
1816-S8M-CXP-50	178.90	227	71.50	0.990
1816-S8M-CXP-85	297.06	227	71.50	1.683
1912-S8M-CXP-20	78.22	239	75.28	0.417
1912-S8M-CXP-30	111.88	239	75.28	0.625
1912-S8M-CXP-50	187.77	239	75.28	1.042
1912-S8M-CXP-85	313.03	239	75.28	1.771
2240-S8M-CXP-20	89.32	280	88.19	0.433
2240-S8M-CXP-30	130.13	280	88.19	0.649
2240-S8M-CXP-50	212.17	280	88.19	1.082
2240-S8M-CXP-85	361.57	280	88.19	1.840
2392-S8M-CXP-20	93.95	299	94.17	0.520
2392-S8M-CXP-30	138.20	299	94.17	0.780
2392-S8M-CXP-50	222.50	299	94.17	1.300
2392-S8M-CXP-85	383.06	299	94.17	2.211
2800-S8M-CXP-20	109.72	350	110.24	0.568
2800-S8M-CXP-30	156.77	350	110.24	0.853
2800-S8M-CXP-50	261.35	350	110.24	1.423
2800-S8M-CXP-85	449.58	350	110.24	2.418
2848-S8M-CXP-20	111.51	356	112.13	0.574
2848-S8M-CXP-30	158.96	356	112.13	0.861
2848-S8M-CXP-50	265.77	356	112.13	1.437
2848-S8M-CXP-85	457.60	356	112.13	2.442

CONTI® SYNCHROFORCE CXA

CONTI® SYNCHROFORCE EXTREME

Heavy-duty synchronous belt


for sustained transmission of higher torque levels at low speed

HTD	STD	CTD
		
Profile	Profile	Profile
8M 14M	S8M	C8M

SIZES AVAILABLE ON REQUEST BY SPECIAL ORDER




Properties:

- ▶ conditionally resistant to oil
- ▶ temperature range, depending on application, from -4°F to 212°F (-20°C to +100°C)
- ▶ electrically conductive to ISO 9563
- ▶ suitable for tropical climates
- ▶ resistant to aging and ozone



Heavy-duty synchronous belt

for high acceleration forces and shock loads

HTD	STD	CTD
		
Profile	Profile	Profile
8M 14M	S8M	C8M

SIZES AVAILABLE ON REQUEST BY SPECIAL ORDER

Properties:




- ▶ largely oil-resistant
- ▶ temperature range, depending on application, from -24°F to +266°F (-30°C to +130°C)
- ▶ resistant to aging and ozone
- ▶ suitable for tropical climates



CONTI® SYNCHROBELT

Synchronous belt

for the lower and medium power range

MXL - XXH	HTD	STD
		 <div><div>Polyamide fabric</div><div>Polychloroprene teeth</div><div>Tension member glass cord</div><div>Synthetic rubber backing</div></div>
Profile	Profile	Profile
MXL	3M	S8M
XL	5M	
L	8M	
H	14M	
XH		
XXH		
Properties:		

- ▶ conditionally resistant to oil
- ▶ temperature range, depending on application, from -4°F to 212°F (-20°C to +100°C)
- ▶ suitable for tropical climates
- ▶ resistant to aging and ozone



CONTI SYNCHROBELT®

HTD 3M				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
111-3M-06	3.80	37	4.37	0.003
111-3M-09	4.96	37	4.37	0.005
111-3M-15	8.20	37	4.37	0.009
117-3M-06	3.82	39	4.61	0.003
117-3M-09	4.98	39	4.61	0.005
117-3M-15	8.25	39	4.61	0.009
129-3M-06	3.86	43	5.08	0.004
129-3M-09	5.02	43	5.08	0.006
129-3M-15	8.35	43	5.08	0.010
141-3M-06	3.90	47	5.55	0.005
141-3M-09	5.06	47	5.55	0.007
141-3M-15	8.45	47	5.55	0.011
144-3M-06	3.91	48	5.67	0.005
144-3M-09	5.07	48	5.67	0.007
144-3M-15	8.48	48	5.67	0.011
150-3M-06	4.04	50	5.91	0.005
150-3M-09	5.24	50	5.91	0.007
150-3M-15	8.50	50	5.91	0.012
156-3M-06	4.08	52	6.14	0.008
156-3M-09	5.39	52	6.14	0.012
156-3M-15	8.60	52	6.14	0.020
159-3M-06	4.12	53	6.26	0.005
159-3M-09	5.41	53	6.26	0.008
159-3M-15	8.61	53	6.26	0.013
168-3M-06	4.16	56	6.61	0.005
168-3M-09	5.45	56	6.61	0.008
168-3M-15	8.62	56	6.61	0.013
174-3M-06	4.17	58	6.85	0.006
174-3M-09	5.62	58	6.85	0.008
174-3M-15	8.71	58	6.85	0.014
177-3M-06	4.21	59	6.97	0.006
177-3M-09	5.68	59	6.97	0.008
177-3M-15	8.86	59	6.97	0.014
180-3M-06	4.23	60	7.09	0.006
180-3M-09	5.70	60	7.09	0.009
180-3M-15	8.96	60	7.09	0.014
186-3M-06	4.25	62	7.32	0.007
186-3M-09	5.71	62	7.32	0.105
186-3M-15	8.99	62	7.32	0.018
192-3M-06	4.28	64	7.56	0.008
192-3M-09	5.72	64	7.56	0.013
192-3M-15	9.02	64	7.56	0.021

HTD 3M				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
201-3M-06	4.31	67	7.91	0.010
201-3M-09	5.74	67	7.91	0.016
201-3M-15	9.05	67	7.91	0.026
204-3M-06	4.32	68	8.03	0.005
204-3M-09	5.75	68	8.03	0.009
204-3M-15	9.10	68	8.03	0.014
210-3M-06	4.35	70	8.27	0.006
210-3M-09	5.76	70	8.27	0.010
210-3M-15	9.19	70	8.27	0.015
213-3M-06	4.36	71	8.39	0.007
213-3M-09	5.77	71	8.39	0.010
213-3M-15	9.24	71	8.39	0.016
216-3M-06	4.37	72	8.50	0.007
216-3M-09	5.78	72	8.50	0.011
216-3M-15	9.29	72	8.50	0.018
225-3M-06	4.45	75	8.86	0.007
225-3M-09	5.88	75	8.86	0.011
225-3M-15	9.46	75	8.86	0.018
240-3M-06	4.47	80	9.45	0.008
240-3M-09	5.98	80	9.45	0.012
240-3M-15	9.52	80	9.45	0.020
246-3M-06	4.52	82	9.69	0.008
246-3M-09	6.00	82	9.69	0.012
246-3M-15	9.55	82	9.69	0.020
252-3M-06	4.61	84	9.92	0.008
252-3M-09	6.03	84	9.92	0.012
252-3M-15	9.76	84	9.92	0.021
255-3M-06	4.65	85	10.04	0.009
255-3M-09	6.05	85	10.04	0.013
255-3M-15	9.89	85	10.04	0.022
261-3M-06	4.66	87	10.28	0.009
261-3M-09	6.10	87	10.28	0.014
261-3M-15	10.00	87	10.28	0.022
267-3M-06	4.67	89	10.51	0.009
267-3M-09	6.15	89	10.51	0.013
267-3M-15	10.10	89	10.51	0.022
270-3M-06	4.68	90	10.63	0.009
270-3M-09	6.16	90	10.63	0.014
270-3M-15	10.12	90	10.63	0.023
285-3M-06	4.70	95	11.22	0.010
285-3M-09	6.21	95	11.22	0.015
285-3M-15	10.33	95	11.22	0.024

HTD 3M				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
294-3M-06	4.73	98	11.57	0.010
294-3M-09	6.28	98	11.57	0.015
294-3M-15	10.41	98	11.57	0.025
300-3M-06	4.75	100	11.81	0.010
300-3M-09	6.33	100	11.81	0.015
300-3M-15	10.46	100	11.81	0.025
312-3M-06	4.77	104	12.28	0.011
312-3M-09	6.43	104	12.28	0.017
312-3M-15	10.58	104	12.28	0.028
318-3M-06	4.83	106	12.52	0.010
318-3M-09	6.55	106	12.52	0.016
318-3M-15	10.70	106	12.52	0.026
321-3M-06	4.85	107	12.64	0.010
321-3M-09	6.55	107	12.64	0.016
321-3M-15	10.72	107	12.64	0.026
330-3M-06	4.92	110	12.99	0.011
330-3M-09	6.56	110	12.99	0.017
330-3M-15	10.77	110	12.99	0.027
336-3M-06	4.97	112	13.23	0.011
336-3M-09	6.57	112	13.23	0.017
336-3M-15	10.81	112	13.23	0.028
339-3M-06	5.01	113	13.35	0.011
339-3M-09	6.61	113	13.35	0.017
339-3M-15	10.92	113	13.35	0.028
357-3M-06	5.15	121	14.29	0.012
357-3M-09	6.62	121	14.29	0.018
357-3M-15	11.29	121	14.29	0.030
363-3M-06	5.16	128	15.12	0.013
363-3M-09	7.06	128	15.12	0.019
363-3M-15	11.69	128	15.12	0.032
384-3M-06	5.31	128	15.12	0.013
384-3M-09	7.27	128	15.12	0.019
384-3M-15	11.78	128	15.12	0.032
390-3M-06	5.33	130	15.35	0.013
390-3M-09	7.29	130	15.35	0.019
390-3M-15	11.80	130	15.35	0.032
393-3M-06	5.33	131	15.47	0.013
393-3M-09	7.30	131	15.47	0.019
393-3M-15	11.82	131	15.47	0.032
396-3M-06	5.34	132	15.59	0.130
396-3M-09	7.30	132	15.59	0.019
396-3M-15	11.83	132	15.59	0.325
420-3M-06	5.36	140	16.54	0.014
420-3M-09	7.34	140	16.54	0.021
420-3M-15	11.96	140	16.54	0.345

HTD 3M				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
432-3M-06	5.38	144	17.00	0.015
432-3M-09	7.37	144	17.00	0.022
432-3M-15	12.03	144	17.00	0.036
435-3M-06	5.39	145	17.13	0.015
435-3M-09	7.38	145	17.13	0.022
435-3M-15	12.04	145	17.13	0.036
447-3M-06	5.40	149	17.60	0.015
447-3M-09	7.39	149	17.60	0.022
447-3M-15	12.11	149	17.60	0.037
474-3M-06	5.42	158	18.66	0.016
474-3M-09	7.44	158	18.66	0.024
474-3M-15	12.25	158	18.66	0.039
477-3M-06	5.54	159	18.78	0.016
477-3M-09	7.50	159	18.78	0.024
477-3M-15	12.49	159	18.78	0.039
480-3M-06	5.66	160	18.90	0.016
480-3M-09	7.56	160	18.90	0.024
480-3M-15	12.73	160	18.90	0.040
486-3M-06	5.70	162	19.13	0.016
486-3M-09	7.58	162	19.13	0.024
486-3M-15	12.79	162	19.13	0.040
489-3M-06	5.72	163	19.25	0.016
489-3M-09	7.59	163	19.25	0.024
489-3M-15	12.82	163	19.25	0.040
495-3M-06	5.75	165	19.49	0.017
495-3M-09	7.60	165	19.49	0.025
495-3M-15	12.88	165	19.49	0.041
501-3M-06	5.79	167	19.72	0.017
501-3M-09	7.58	167	19.72	0.025
501-3M-15	12.94	167	19.72	0.042
513-3M-06	5.84	171	20.20	0.017
513-3M-09	7.62	171	20.20	0.026
513-3M-15	13.31	171	20.20	0.043
522-3M-06	5.90	174	20.55	0.017
522-3M-09	7.70	174	20.55	0.026
522-3M-15	13.36	174	20.55	0.043
525-3M-06	5.92	175	20.67	0.017
525-3M-09	7.73	175	20.67	0.026
525-3M-15	13.37	175	20.67	0.044
537-3M-06	5.98	179	21.14	0.018
537-3M-09	7.98	179	21.14	0.024
537-3M-15	13.38	179	21.14	0.045
564-3M-06	6.14	188	22.20	0.019
564-3M-09	8.06	188	22.20	0.028
564-3M-15	13.48	188	22.20	0.047

HTD 3M				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
570-3M-06	6.16	190	22.44	0.019
570-3M-09	8.12	190	22.44	0.028
570-3M-15	13.62	190	22.44	0.047
597-3M-06	6.20	199	23.50	0.021
597-3M-09	8.38	199	23.50	0.032
597-3M-15	13.75	199	23.50	0.053
600-3M-06	6.22	200	23.62	0.021
600-3M-09	8.41	200	23.62	0.032
600-3M-15	14.20	200	23.62	0.053
606-3M-06	6.23	202	23.86	0.020
606-3M-09	8.42	202	23.86	0.030
606-3M-15	14.28	202	23.86	0.050
612-3M-06	6.25	204	24.09	0.020
612-3M-09	8.44	204	24.09	0.031
612-3M-15	14.44	204	24.09	0.051
615-3M-06	6.26	205	24.21	0.020
615-3M-09	8.48	205	24.21	0.031
615-3M-15	14.45	205	24.21	0.052
633-3M-06	6.30	211	24.92	0.021
633-3M-09	8.75	211	24.92	0.032
633-3M-15	14.52	211	24.92	0.053
669-3M-06	6.38	223	26.34	0.022
669-3M-09	8.95	223	26.34	0.033
669-3M-15	15.07	223	26.34	0.056
708-3M-06	6.56	236	27.87	0.023
708-3M-09	9.27	236	27.87	0.035
708-3M-15	16.69	236	27.87	0.058
711-3M-06	6.57	237	27.99	0.024
711-3M-09	9.29	237	27.99	0.036
711-3M-15	15.25	237	27.99	0.059
738-3M-06	6.71	246	29.06	0.025
738-3M-09	9.47	246	29.06	0.037
738-3M-15	15.63	246	29.06	0.062
753-3M-06	6.79	251	29.65	0.026
753-3M-09	9.57	251	29.65	0.039
753-3M-15	15.84	251	29.65	0.066
822-3M-06	7.15	274	32.36	0.027
822-3M-09	10.05	274	32.36	0.041
822-3M-15	16.81	274	32.36	0.068
843-3M-06	7.18	281	33.19	0.028
843-3M-09	10.09	281	33.19	0.042
843-3M-15	17.11	281	33.19	0.070
882-3M-06	7.68	294	34.72	0.029
882-3M-09	10.25	294	34.72	0.044
882-3M-15	17.70	294	34.72	0.073

HTD 3M				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
945-3M-06	7.95	315	37.20	0.031
945-3M-09	10.72	315	37.20	0.047
945-3M-15	18.76	315	37.20	0.079
960-3M-06	8.02	320	37.80	0.031
960-3M-09	10.84	320	37.80	0.047
960-3M-15	18.90	320	37.80	0.079
1002-3M-06	8.20	334	39.45	0.032
1002-3M-09	11.19	334	39.45	0.050
1002-3M-15	19.29	334	39.45	0.082
1041-3M-06	8.38	347	40.98	0.034
1041-3M-09	11.50	347	40.98	0.051
1041-3M-15	19.65	347	40.98	0.084
1068-3M-06	8.50	356	42.05	0.035
1068-3M-09	11.72	356	42.05	0.052
1068-3M-15	19.90	356	42.05	0.086
1071-3M-06	8.51	357	42.17	0.036
1071-3M-09	11.75	357	42.17	0.054
1071-3M-15	19.93	357	42.17	0.090
1125-3M-06	8.75	375	44.29	0.037
1125-3M-09	12.19	375	44.29	0.056
1125-3M-15	20.43	375	44.29	0.094
1170-3M-06	8.95	390	46.06	0.038
1170-3M-09	12.56	390	46.06	0.057
1170-3M-15	20.85	390	46.06	0.095
1176-3M-06	8.98	392	46.30	0.039
1176-3M-09	12.61	392	46.30	0.058
1176-3M-15	20.90	392	46.30	0.097
1245-3M-06	9.28	415	49.02	0.040
1245-3M-09	13.17	415	49.02	0.060
1245-3M-15	21.54	415	49.02	0.099
1500-3M-06	10.42	500	59.06	0.044
1500-3M-09	15.25	500	59.06	0.063
1500-3M-15	23.90	500	59.06	0.108
1569-3M-06	10.72	523	61.77	0.050
1569-3M-09	15.81	523	61.77	0.073
1569-3M-15	24.54	523	61.77	0.121

HTD 5M				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
225-5M-09	7.77	45	8.86	0.017
225-5M-15	11.04	45	8.86	0.028
225-5M-25	17.50	45	8.86	0.047
265-5M-09	8.06	53	10.43	0.020
265-5M-15	11.86	53	10.43	0.033
265-5M-25	18.64	53	10.43	0.055
275-5M-09	8.13	55	10.83	0.021
275-5M-15	12.06	55	10.83	0.035
275-5M-25	18.93	55	10.83	0.058
295-5M-09	8.27	59	11.61	0.022
295-5M-15	12.47	59	11.61	0.037
295-5M-25	19.50	59	11.61	0.062
300-5M-09	8.31	60	11.81	0.023
300-5M-15	12.57	60	11.81	0.038
300-5M-25	19.64	60	11.81	0.063
330-5M-09	8.53	66	12.99	0.025
330-5M-15	13.18	66	12.99	0.041
330-5M-25	20.50	66	12.99	0.069
350-5M-09	8.67	70	13.78	0.026
350-5M-15	13.59	70	13.78	0.044
350-5M-25	21.07	70	13.78	0.073
375-5M-09	8.92	75	14.76	0.028
375-5M-15	13.78	75	14.76	0.047
375-5M-25	22.14	75	14.76	0.079
385-5M-09	9.07	77	15.16	0.029
385-5M-15	13.82	77	15.16	0.048
385-5M-25	22.27	77	15.16	0.081
390-5M-09	9.14	78	15.35	0.030
390-5M-15	13.84	78	15.35	0.049
390-5M-25	22.33	78	15.35	0.082
400-5M-09	9.29	80	15.75	0.030
400-5M-15	13.88	80	15.75	0.050
400-5M-25	22.46	80	15.75	0.084
405-5M-09	9.34	81	15.94	0.031
405-5M-15	13.98	81	15.94	0.051
405-5M-25	22.57	81	15.94	0.085
425-5M-09	9.52	85	16.73	0.032
425-5M-15	14.36	85	16.73	0.053
425-5M-25	23.00	85	16.73	0.089
450-5M-09	9.80	90	17.72	0.034
450-5M-15	15.06	90	17.72	0.057
450-5M-25	24.31	90	17.72	0.094

HTD 5M				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
460-5M-09	10.17	92	18.11	0.035
460-5M-15	15.53	92	18.11	0.058
460-5M-25	24.40	92	18.11	0.096
475-5M-09	10.29	95	18.70	0.036
475-5M-15	15.58	95	18.70	0.060
475-5M-25	24.54	95	18.70	0.100
500-5M-09	10.34	100	19.69	0.037
500-5M-15	16.14	100	19.69	0.062
500-5M-25	25.39	100	19.69	0.103
525-5M-09	10.55	105	20.67	0.039
525-5M-15	16.77	105	20.67	0.065
525-5M-25	27.18	105	20.67	0.108
535-5M-09	10.63	107	21.06	0.040
535-5M-15	16.98	107	21.06	0.066
535-5M-25	27.90	107	21.06	0.110
550-5M-09	10.76	110	21.65	0.041
550-5M-15	17.00	110	21.65	0.069
550-5M-25	28.32	110	21.65	0.114
565-5M-09	10.89	113	22.24	0.043
565-5M-15	17.02	113	22.24	0.071
565-5M-25	28.74	113	22.24	0.118
600-5M-09	11.32	120	23.62	0.044
600-5M-15	17.71	120	23.62	0.074
600-5M-25	29.91	120	23.62	0.123
615-5M-09	11.42	123	24.21	0.046
615-5M-15	18.16	123	24.21	0.077
615-5M-25	29.94	123	24.21	0.129
620-5M-09	11.58	124	24.41	0.047
620-5M-15	18.28	124	24.41	0.078
620-5M-25	30.09	124	24.41	0.132
630-5M-09	11.91	126	24.80	0.048
630-5M-15	18.51	126	24.80	0.079
630-5M-25	30.38	126	24.80	0.134
635-5M-09	12.07	127	25.00	0.048
635-5M-15	18.62	127	25.00	0.080
635-5M-25	30.52	127	25.00	0.135
665-5M-09	12.14	133	26.18	0.049
665-5M-15	18.79	133	26.18	0.082
665-5M-25	31.99	133	26.18	0.137
700-5M-09	12.43	140	5.51	0.052
700-5M-15	19.26	140	5.51	0.086
700-5M-25	32.05	140	5.51	0.144

HTD 5M				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
710-5M-09	12.51	142	27.95	0.053
710-5M-15	19.40	142	27.95	0.088
710-5M-25	32.06	142	27.95	0.146
740-5M-09	12.84	148	29.13	0.055
740-5M-15	20.62	148	29.13	0.091
740-5M-25	33.58	148	29.13	0.152
755-5M-09	13.03	151	29.72	0.056
755-5M-15	20.80	151	29.72	0.093
755-5M-25	33.92	151	29.72	0.155
800-5M-09	13.58	160	31.50	0.059
800-5M-15	21.34	160	31.50	0.099
800-5M-25	34.94	160	31.50	0.164
835-5M-09	13.87	167	32.87	0.063
835-5M-15	22.15	167	32.87	0.105
835-5M-25	36.41	167	32.87	0.175
840-5M-09	13.91	168	33.07	0.064
840-5M-15	22.24	168	33.07	0.106
840-5M-25	36.54	168	33.07	0.176
860-5M-09	14.06	172	33.86	0.065
860-5M-15	22.56	172	33.86	0.108
860-5M-25	37.03	172	33.86	0.182
890-5M-09	14.28	178	35.04	0.067
890-5M-15	23.13	178	35.04	0.112
890-5M-25	37.78	178	35.04	0.187
900-5M-09	14.50	180	35.43	0.068
900-5M-15	23.21	180	35.43	0.114
900-5M-25	38.22	180	35.43	0.190
925-5M-09	15.01	185	36.42	0.070
925-5M-15	23.41	185	36.42	0.116
925-5M-25	39.33	185	36.42	0.194
950-5M-09	15.14	190	37.40	0.070
950-5M-15	24.42	190	37.40	0.117
950-5M-25	40.03	190	37.40	0.195
1000-5M-09	15.74	200	39.37	0.074
1000-5M-15	24.79	200	39.37	0.123
1000-5M-25	40.60	200	39.37	0.206
1050-5M-09	16.43	210	41.34	0.079
1050-5M-15	26.26	210	41.34	0.132
1050-5M-25	42.17	210	41.34	0.220
1125-5M-09	16.82	225	44.29	0.085
1125-5M-15	28.00	225	44.29	0.142
1125-5M-25	45.16	225	44.29	0.236

HTD 5M				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
1200-5M-09	17.46	240	47.24	0.091
1200-5M-15	29.41	240	47.24	0.151
1200-5M-25	48.20	240	47.24	0.252
1270-5M-09	18.06	254	50.00	0.096
1270-5M-15	30.72	254	50.00	0.160
1270-5M-25	51.03	254	50.00	0.266
1420-5M-09	19.06	284	55.91	0.107
1420-5M-15	31.82	284	55.91	0.179
1420-5M-25	53.83	284	55.91	0.298
1500-5M-09	20.28	300	59.06	0.112
1500-5M-15	33.59	300	59.06	0.187
1500-5M-25	56.50	300	59.06	0.312
1595-5M-09	21.73	319	62.80	0.118
1595-5M-15	35.68	319	62.80	0.197
1595-5M-25	59.68	319	62.80	0.328
1690-5M-09	23.18	338	66.54	0.125
1690-5M-15	37.33	338	66.54	0.208
1690-5M-25	63.72	338	66.54	0.347
1800-5M-09	24.05	360	70.87	0.133
1800-5M-15	39.09	360	70.87	0.222
1800-5M-25	66.78	360	70.87	0.370
2000-5M-09	25.62	400	78.74	0.148
2000-5M-15	42.30	400	78.74	0.247
2000-5M-25	72.34	400	78.74	0.411

HTD 8M				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
288-8M-20	18.87	36	11.34	0.067
288-8M-30	25.09	36	11.34	0.100
288-8M-50	38.23	36	11.34	0.166
288-8M-85	62.05	36	11.34	0.283
304-8M-20	19.17	38	11.97	0.070
304-8M-30	25.67	38	11.97	0.105
304-8M-50	39.26	38	11.97	0.175
304-8M-85	63.89	38	11.97	0.298
352-8M-20	20.09	44	13.86	0.081
352-8M-30	27.43	44	13.86	0.120
352-8M-50	42.37	44	13.86	0.201
352-8M-85	69.43	44	13.86	0.342
376-8M-20	20.55	47	14.8	0.086
376-8M-30	28.31	47	14.8	0.128
376-8M-50	43.93	47	14.8	0.214
376-8M-85	72.20	47	14.8	0.364
400-8M-20	21.01	50	15.75	0.091
400-8M-30	29.19	50	15.75	0.136
400-8M-50	45.48	50	15.75	0.227
400-8M-85	74.97	50	15.75	0.386
416-8M-20	21.32	52	16.38	0.094
416-8M-30	29.78	52	16.38	0.141
416-8M-50	46.52	52	16.38	0.236
416-8M-85	76.82	52	16.38	0.400
424-8M-20	21.47	53	16.67	0.096
424-8M-30	30.07	53	16.67	0.144
424-8M-50	47.03	53	16.67	0.240
424-8M-85	77.74	53	16.67	0.408
472-8M-20	22.39	59	18.58	0.106
472-8M-30	31.83	59	18.58	0.159
472-8M-50	50.14	59	18.58	0.266
472-8M-85	83.28	59	18.58	0.452
480-8M-20	22.54	60	18.90	0.108
480-8M-30	32.12	60	18.90	0.162
480-8M-50	50.66	60	18.90	0.270
480-8M-85	84.20	60	18.90	0.459
560-8M-20	24.07	70	22.05	0.125
560-8M-30	35.05	70	22.05	0.188
560-8M-50	55.84	70	22.05	0.313
560-8M-85	93.43	70	22.05	0.533

HTD 8M				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
600-8M-20	25.96	75	23.62	0.134
600-8M-30	37.11	75	23.62	0.201
600-8M-50	59.00	75	23.62	0.334
600-8M-85	100.52	75	23.62	0.568
624-8M-20	26.46	78	24.57	0.139
624-8M-30	38.16	78	24.57	0.208
624-8M-50	60.95	78	24.57	0.347
624-8M-85	102.02	78	24.57	0.591
640-8M-20	26.80	80	25.20	0.142
640-8M-30	38.86	80	25.20	0.214
640-8M-50	62.25	80	25.20	0.356
640-8M-85	103.02	80	25.20	0.606
656-8M-20	27.26	82	25.83	0.146
656-8M-30	39.05	82	25.83	0.219
656-8M-50	64.73	82	25.83	0.365
656-8M-85	104.47	82	25.83	0.620
688-8M-20	28.17	86	27.09	0.153
688-8M-30	39.43	86	27.09	0.229
688-8M-50	63.50	86	27.09	0.382
688-8M-85	107.36	86	27.09	0.649
720-8M-20	29.08	90	28.35	0.160
720-8M-30	39.81	90	28.35	0.239
720-8M-50	65.35	90	28.35	0.399
720-8M-85	110.26	90	28.35	0.678
776-8M-20	30.97	97	30.55	0.172
776-8M-30	41.90	97	30.55	0.258
776-8M-50	70.52	97	30.55	0.430
776-8M-85	117.25	97	30.55	0.711
784-8M-20	31.24	98	30.87	0.174
784-8M-30	42.19	98	30.87	0.261
784-8M-50	71.25	98	30.87	0.434
784-8M-85	118.24	98	30.87	0.716
800-8M-20	31.78	100	31.50	0.177
800-8M-30	42.79	100	31.50	0.266
800-8M-50	72.73	100	31.50	0.443
800-8M-85	120.24	100	31.50	0.752
880-8M-20	33.90	110	34.65	0.194
880-8M-30	46.72	110	34.65	0.291
880-8M-50	76.66	110	34.65	0.486
880-8M-85	127.91	110	34.65	0.826

HTD 8M				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
912-8M-20	34.04	114	35.91	0.198
912-8M-30	47.24	114	35.91	0.296
912-8M-50	77.70	114	35.91	0.494
912-8M-85	132.87	114	35.91	0.840
920-8M-20	34.24	115	36.22	0.203
920-8M-30	48.01	115	36.22	0.304
920-8M-50	79.25	115	36.22	0.507
920-8M-85	130.28	115	36.22	0.862
960-8M-20	35.45	120	37.80	0.212
960-8M-30	49.65	120	37.80	0.317
960-8M-50	84.28	120	37.80	0.529
960-8M-85	140.31	120	37.80	0.899
1040-8M-20	37.75	130	40.94	0.229
1040-8M-30	53.48	130	40.94	0.343
1040-8M-50	86.16	130	40.94	0.572
1040-8M-85	149.05	130	40.94	0.972
1120-8M-20	38.18	140	44.09	0.246
1120-8M-30	56.32	140	44.09	0.369
1120-8M-50	92.04	140	44.09	0.615
1120-8M-85	158.57	140	44.09	1.045
1160-8M-20	39.74	145	45.67	0.254
1160-8M-30	57.26	145	45.67	0.382
1160-8M-50	95.68	145	45.67	0.636
1160-8M-85	159.37	146	45.67	1.081
1200-8M-20	40.60	150	47.24	0.263
1200-8M-30	58.37	150	47.24	0.394
1200-8M-50	97.55	150	47.24	0.657
1200-8M-85	161.56	150	47.24	1.118
1280-8M-20	43.28	160	50.39	0.281
1280-8M-30	63.35	160	50.39	0.421
1280-8M-50	99.94	160	50.39	0.701
1280-8M-85	171.79	160	50.39	1.192
1304-8M-20	43.85	163	51.34	0.286
1304-8M-30	64.59	163	51.34	0.429
1304-8M-50	101.50	163	51.34	0.714
1304-8M-85	174.74	163	51.34	1.214
1328-8M-20	44.14	166	52.28	0.289
1328-8M-30	65.22	166	52.28	0.442
1328-8M-50	103.06	166	52.28	0.734
1328-8M-85	177.68	166	52.28	1.243

HTD 8M				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
1360-8M-20	45.17	170	53.54	0.294
1360-8M-30	66.47	170	53.54	0.453
1360-8M-50	105.14	170	53.54	0.751
1360-8M-85	181.61	170	53.54	1.267
1424-8M-20	46.68	178	56.06	0.304
1424-8M-30	68.96	178	56.06	0.463
1424-8M-50	109.30	178	56.06	0.769
1424-8M-85	189.47	178	56.06	1.295
1440-8M-20	47.06	180	56.69	0.315
1440-8M-30	69.58	180	56.69	0.472
1440-8M-50	110.34	180	56.69	0.787
1440-8M-85	191.43	180	56.69	1.338
1520-8M-20	48.40	190	59.84	0.332
1520-8M-30	70.26	190	59.84	0.498
1520-8M-50	118.00	190	59.84	0.838
1520-8M-85	199.68	190	59.84	1.411
1600-8M-20	50.30	200	62.99	0.349
1600-8M-30	74.30	200	62.99	0.524
1600-8M-50	121.88	200	62.99	0.873
1600-8M-85	203.71	200	62.99	1.485
1760-8M-20	53.97	220	69.29	0.384
1760-8M-30	78.59	220	69.29	0.576
1760-8M-50	132.21	220	69.29	0.960
1760-8M-85	216.63	220	69.29	1.631
1800-8M-20	56.46	225	70.87	0.393
1800-8M-30	80.67	225	70.87	0.589
1800-8M-50	136.47	225	70.87	0.981
1800-8M-85	226.46	225	70.87	1.668
2000-8M-20	62.01	250	78.74	0.436
2000-8M-30	90.30	250	78.74	0.654
2000-8M-50	150.70	250	78.74	1.089
2000-8M-85	252.04	250	78.74	1.852
2248-8M-20	68.90	281	88.50	0.489
2248-8M-30	100.43	281	88.50	0.734
2248-8M-50	163.63	281	88.50	1.223
2248-8M-85	279.00	281	88.50	2.079
2400-8M-20	72.46	300	94.49	0.522
2400-8M-30	106.64	300	94.49	0.783
2400-8M-50	171.56	300	94.49	1.305
2400-8M-85	295.53	300	94.49	2.218

HTD 8M				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
2600-8M-20	78.64	325	102.36	0.545
2600-8M-30	113.53	325	102.36	0.818
2600-8M-50	186.87	325	102.36	1.364
2600-8M-85	320.13	325	102.36	2.318
2800-8M-20	84.40	350	110.24	0.568
2800-8M-30	120.59	350	110.24	0.853
2800-8M-50	201.04	350	110.24	1.423
2800-8M-85	345.83	350	110.24	2.418
3008-8M-20	90.39	376	118.43	0.592
3008-8M-30	127.93	376	118.43	0.889
3008-8M-50	215.78	376	118.43	1.484
3008-8M-85	372.56	376	118.43	2.522
3048-8M-20	91.55	381	120.00	0.597
3048-8M-30	129.34	381	120.00	0.896
3048-8M-50	218.62	381	120.00	1.496
3048-8M-85	377.70	381	120.00	2.542
3408-8M-20	101.92	426	134.17	0.638
3408-8M-30	142.04	426	134.17	0.959
3408-8M-50	244.13	426	134.17	0.160
3408-8M-85	423.97	426	134.17	2.722
3600-8M-20	107.45	450	141.73	0.660
3600-8M-30	148.82	450	141.73	0.993
3600-8M-50	257.73	450	141.73	1.659
3600-8M-85	448.64	450	141.73	2.818
3808-8M-20	113.45	476	149.92	0.684
3808-8M-30	156.16	476	149.92	1.030
3808-8M-50	272.47	476	149.92	1.720
3808-8M-85	475.37	476	149.92	2.922
4400-8M-20	130.51	550	173.23	0.751
4400-8M-30	177.06	550	173.23	1.134
4400-8M-50	314.42	550	173.23	1.895
4400-8M-85	551.44	550	173.23	3.218

HTD 14M				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
966-14M-40	172.33	69	38.03	0.940
966-14M-55	225.18	69	38.03	1.290
966-14M-85	322.21	69	38.03	1.990
966-14M-115	421.77	69	38.03	2.700
966-14M-170	629.31	69	38.03	3.990
1050-14M-40	179.02	75	41.34	0.952
1050-14M-55	231.92	75	41.34	1.307
1050-14M-85	335.55	75	41.34	2.017
1050-14M-115	440.99	75	41.34	2.734
1050-14M-170	658.99	75	41.34	4.041
1190-14M-40	190.17	85	46.85	0.971
1190-14M-55	243.14	85	46.85	1.335
1190-14M-85	357.79	85	46.85	2.063
1190-14M-115	473.03	85	46.85	2.791
1190-14M-170	708.45	85	46.85	4.127
1400-14M-40	202.78	100	55.12	1.139
1400-14M-55	266.59	100	55.12	1.565
1400-14M-85	393.00	100	55.12	2.419
1400-14M-115	515.28	100	55.12	3.273
1400-14M-170	778.86	100	55.12	4.839
1610-14M-40	216.89	115	63.39	1.305
1610-14M-55	300.18	115	63.39	1.794
1610-14M-85	436.64	115	63.39	2.773
1610-14M-115	589.71	115	63.39	3.751
1610-14M-170	822.51	115	63.39	5.545
1778-14M-40	239.80	127	70.00	0.356
1778-14M-55	308.74	127	70.00	0.489
1778-14M-85	460.95	127	70.00	0.756
1778-14M-115	603.80	127	70.00	1.023
1778-14M-170	885.69	127	70.00	1.512
1890-14M-40	249.56	135	74.41	1.528
1890-14M-55	323.49	135	74.41	2.101
1890-14M-85	475.70	135	74.41	3.247
1890-14M-115	655.79	135	74.41	4.393
1890-14M-170	955.69	135	74.41	6.494
2100-14M-40	262.86	150	82.68	1.695
2100-14M-55	362.11	150	82.68	2.331
2100-14M-85	527.68	150	82.68	3.602
2100-14M-115	725.41	150	82.68	4.873
2100-14M-170	1,014.00	150	82.68	7.204

HTD 14M				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
2310-14M-40	282.42	165	90.94	1.862
2310-14M-55	385.80	165	90.94	2.560
2310-14M-85	563.51	165	90.94	3.956
2310-14M-115	774.48	165	90.94	5.352
2310-14M-170	1,099.80	165	90.94	7.912
2450-14M-40	290.93	175	96.46	1.973
2450-14M-55	394.61	175	96.46	2.713
2450-14M-85	600.80	175	96.46	4.192
2450-14M-115	802.33	175	96.46	5.672
2450-14M-170	1,163.56	175	96.46	8.384
2590-14M-40	310.50	185	101.97	2.084
2590-14M-55	411.76	185	101.97	2.865
2590-14M-85	625.63	185	101.97	4.428
2590-14M-115	818.99	185	101.97	5.991
2590-14M-170	1,192.54	185	101.97	8.857
2800-14M-40	337.07	200	110.24	2.251
2800-14M-55	446.17	200	110.24	3.095
2800-14M-85	669.92	200	110.24	4.784
2800-14M-115	890.41	200	110.24	6.472
2800-14M-170	1,316.70	200	110.24	9.567
3150-14M-40	367.06	225	124.02	2.529
3150-14M-55	489.63	225	124.02	3.478
3150-14M-85	737.47	225	124.02	5.375
3150-14M-115	1,007.81	225	124.02	7.272
3150-14M-170	1,415.55	225	124.02	10.750
3360-14M-40	391.59	240	132.28	2.657
3360-14M-55	523.69	240	132.28	3.654
3360-14M-85	758.14	240	132.28	5.647
3360-14M-115	1,045.42	240	132.28	7.640
3360-14M-170	1,487.12	240	132.28	11.294
3500-14M-40	404.02	250	137.80	2.808
3500-14M-55	539.75	250	137.80	3.861
3500-14M-85	805.04	250	137.80	5.967
3500-14M-115	1,089.62	250	137.80	8.073
3500-14M-170	1,565.30	250	137.80	11.934
3668-14M-40	415.11	262	144.41	2.941
3668-14M-55	561.44	262	144.41	4.044
3668-14M-85	838.01	262	144.41	6.250
3668-14M-115	1,129.02	262	144.41	8.456
3668-14M-170	1,660.03	262	144.41	12.500

HTD 14M				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
3850-14M-40	427.13	275	151.57	3.086
3850-14M-55	584.94	275	151.57	4.243
3850-14M-85	873.72	275	151.57	6.557
3850-14M-115	1,171.70	275	151.57	8.871
3850-14M-170	1,762.66	275	151.57	13.114
4326-14M-40	491.32	309	170.31	3.465
4326-14M-55	652.68	309	170.31	4.764
4326-14M-85	971.86	309	170.31	7.362
4326-14M-115	1,334.98	309	170.31	9.961
4326-14M-170	1,962.79	309	170.31	14.724
4578-14M-40	503.09	327	180.24	3.664
4578-14M-55	690.42	327	180.24	5.039
4578-14M-85	1,036.58	327	180.24	7.787
4578-14M-115	1,390.14	327	180.24	10.535
4578-14M-170	1,979.53	327	180.24	15.574

STD 8M				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
440-S8M-20	21.78	55	17.32	0.099
440-S8M-30	30.66	55	17.32	0.149
440-S8M-50	48.07	55	17.32	0.249
440-S8M-85	79.59	55	17.32	0.423
464-S8M-20	22.24	58	18.27	0.104
464-S8M-30	31.54	58	18.27	0.157
464-S8M-50	49.62	58	18.27	0.262
464-S8M-85	82.36	58	18.27	0.445
480-S8M-20	22.54	60	18.90	0.108
480-S8M-30	32.12	60	18.90	0.162
480-S8M-50	50.66	60	18.90	0.270
480-S8M-85	84.20	60	18.90	0.459
528-S8M-20	23.46	66	20.79	0.118
528-S8M-30	33.88	66	20.79	0.178
528-S8M-50	53.77	66	20.79	0.296
528-S8M-85	89.74	66	20.79	0.503
560-S8M-20	24.07	70	22.05	0.125
560-S8M-30	35.05	70	22.05	0.188
560-S8M-50	55.84	70	22.05	0.313
560-S8M-85	93.43	70	22.05	0.533
600-S8M-20	25.96	75	23.62	0.134
600-S8M-30	37.11	75	23.62	0.201
600-S8M-50	59.00	75	23.62	0.334
600-S8M-85	100.52	75	23.62	0.568
632-S8M-20	26.63	79	24.88	0.140
632-S8M-30	38.51	79	24.88	0.209
632-S8M-50	61.60	79	24.88	0.349
632-S8M-85	102.52	79	24.88	0.595
640-S8M-20	26.80	80	25.20	0.142
640-S8M-30	38.86	80	25.20	0.214
640-S8M-50	62.25	80	25.20	0.356
640-S8M-85	103.02	80	25.20	0.606
656-S8M-20	27.26	82	25.83	0.146
656-S8M-30	39.05	82	25.83	0.219
656-S8M-50	64.73	82	25.83	0.365
656-S8M-85	104.47	82	25.83	0.620
672-S8M-20	27.72	84	26.46	0.150
672-S8M-30	39.24	84	26.46	0.224
672-S8M-50	64.12	84	26.46	0.374
672-S8M-85	105.92	84	26.46	0.635

STD 8M				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
688-S8M-20	28.17	86	27.09	0.153
688-S8M-30	39.43	86	27.09	0.229
688-S8M-50	63.50	86	27.09	0.382
688-S8M-85	107.36	86	27.09	0.649
696-S8M-20	28.40	87	27.40	0.155
696-S8M-30	39.52	87	27.40	0.232
696-S8M-50	63.96	87	27.40	0.386
696-S8M-85	108.09	87	27.40	0.656
712-S8M-20	28.85	89	28.03	0.158
712-S8M-30	39.71	89	28.03	0.237
712-S8M-50	64.89	89	28.03	0.395
712-S8M-85	109.54	89	28.03	0.671
720-S8M-20	29.08	90	28.35	0.160
720-S8M-30	39.81	90	28.35	0.239
720-S8M-50	65.35	90	28.35	0.399
720-S8M-85	110.26	90	28.35	0.678
728-S8M-20	29.35	91	28.66	0.161
728-S8M-30	40.11	91	28.66	0.242
728-S8M-50	66.09	91	28.66	0.403
728-S8M-85	111.26	91	28.66	0.683
736-S8M-20	29.62	92	28.98	0.163
736-S8M-30	40.41	92	28.98	0.245
736-S8M-50	66.83	92	28.98	0.408
736-S8M-85	112.26	92	28.98	0.688
760-S8M-20	30.43	95	29.92	0.168
760-S8M-30	41.30	95	29.92	0.253
760-S8M-50	69.04	95	29.92	0.421
760-S8M-85	115.25	95	29.92	0.702
768-S8M-20	30.70	96	30.24	0.170
768-S8M-30	41.60	96	30.24	0.255
768-S8M-50	69.78	96	30.24	0.426
768-S8M-85	116.25	96	30.24	0.706
784-S8M-20	31.24	98	30.87	0.174
784-S8M-30	42.19	98	30.87	0.261
784-S8M-50	71.25	98	30.87	0.434
784-S8M-85	118.24	98	30.87	0.716
792-S8M-20	31.51	99	31.18	0.176
792-S8M-30	42.49	99	31.18	0.263
792-S8M-50	71.99	99	31.18	0.438
792-S8M-85	119.24	99	31.18	0.734

STD 8M				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
800-S8M-20	31.78	100	31.50	0.177
800-S8M-30	42.79	100	31.50	0.266
800-S8M-50	72.73	100	31.50	0.443
800-S8M-85	120.24	100	31.50	0.752
824-S8M-20	32.54	103	32.44	0.177
824-S8M-30	44.35	103	32.44	0.266
824-S8M-50	73.44	103	32.44	0.444
824-S8M-85	124.18	103	32.44	0.754
840-S8M-20	33.04	105	33.07	0.178
840-S8M-30	45.39	105	33.07	0.267
840-S8M-50	73.90	105	33.07	0.445
840-S8M-85	126.81	105	33.07	0.756
848-S8M-20	33.21	106	33.39	0.181
848-S8M-30	45.66	106	33.39	0.272
848-S8M-50	74.46	106	33.39	0.453
848-S8M-85	127.03	106	33.39	0.770
864-S8M-20	33.56	108	34.02	0.188
864-S8M-30	46.19	108	34.02	0.282
864-S8M-50	75.56	108	34.02	0.469
864-S8M-85	127.47	108	34.02	0.798
880-S8M-20	33.90	110	34.65	0.194
880-S8M-30	46.72	110	34.65	0.291
880-S8M-50	76.66	110	34.65	0.486
880-S8M-85	127.91	110	34.65	0.826
912-S8M-20	34.04	114	35.91	0.198
912-S8M-30	47.24	114	35.91	0.296
912-S8M-50	77.70	114	35.91	0.494
912-S8M-85	132.87	114	35.91	0.840
920-S8M-20	34.24	115	36.22	0.203
920-S8M-30	48.01	115	36.22	0.304
920-S8M-50	79.25	115	36.22	0.507
920-S8M-85	130.28	115	36.22	0.862
944-S8M-20	34.97	118	37.17	0.208
944-S8M-30	48.99	118	37.17	0.312
944-S8M-50	82.27	118	37.17	0.520
944-S8M-85	136.30	118	37.17	0.884
960-S8M-20	35.45	120	37.80	0.212
960-S8M-30	49.65	120	37.80	0.317
960-S8M-50	84.28	120	37.80	0.529
960-S8M-85	140.31	120	37.80	0.899

STD 8M				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
992-S8M-20	36.37	124	39.06	0.218
992-S8M-30	51.18	124	39.06	0.328
992-S8M-50	85.03	124	39.06	0.546
992-S8M-85	143.81	124	39.06	0.928
1000-S8M-20	36.60	125	39.37	0.220
1000-S8M-30	51.57	125	39.37	0.330
1000-S8M-50	85.22	125	39.37	0.550
1000-S8M-85	144.68	125	39.37	0.936
1024-S8M-20	37.29	128	40.31	0.225
1024-S8M-30	52.72	128	40.31	0.338
1024-S8M-50	85.78	128	40.31	0.563
1024-S8M-85	147.30	128	40.31	0.958
1032-S8M-20	37.52	129	40.63	0.227
1032-S8M-30	53.10	129	40.63	0.341
1032-S8M-50	85.97	129	40.63	0.568
1032-S8M-85	148.18	129	40.63	0.928
1056-S8M-20	37.93	132	41.57	0.232
1056-S8M-30	54.50	132	41.57	0.348
1056-S8M-50	87.42	132	41.57	0.581
1056-S8M-85	151.19	132	41.57	0.987
1064-S8M-20	38.01	133	41.89	0.234
1064-S8M-30	55.01	133	41.89	0.351
1064-S8M-50	88.05	133	41.89	0.585
1064-S8M-85	152.26	133	41.89	0.995
1072-S8M-20	38.04	134	42.20	0.236
1072-S8M-30	55.20	134	42.20	0.354
1072-S8M-50	88.62	134	42.20	0.589
1072-S8M-85	153.16	134	42.20	1.002
1080-S8M-20	38.06	135	42.52	0.237
1080-S8M-30	55.38	135	42.52	0.356
1080-S8M-50	89.19	135	42.52	0.594
1080-S8M-85	154.06	135	42.52	1.009
1096-S8M-20	38.11	137	43.15	0.241
1096-S8M-30	55.76	137	43.15	0.361
1096-S8M-50	90.33	137	43.15	0.602
1096-S8M-85	155.87	137	43.15	1.023
1120-S8M-20	38.18	140	44.09	0.246
1120-S8M-30	56.32	140	44.09	0.369
1120-S8M-50	92.04	140	44.09	0.615
1120-S8M-85	158.57	140	44.09	1.045

STD 8M				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
1136-S8M-20	38.80	142	44.72	0.249
1136-S8M-30	56.69	142	44.72	0.374
1136-S8M-50	93.50	142	44.72	0.623
1136-S8M-85	158.89	142	44.72	1.059
1152-S8M-20	39.43	144	45.35	0.253
1152-S8M-30	57.07	144	45.35	0.379
1152-S8M-50	94.95	144	45.35	0.632
1152-S8M-85	159.21	144	45.35	1.074
1160-S8M-20	39.74	145	45.67	0.254
1160-S8M-30	57.26	145	45.67	0.382
1160-S8M-50	95.68	145	45.67	0.636
1160-S8M-85	159.37	145	45.67	1.081
1168-S8M-20	39.91	146	45.98	0.256
1168-S8M-30	57.48	146	45.98	0.384
1168-S8M-50	95.47	146	45.98	0.640
1168-S8M-85	159.81	146	45.98	1.089
1176-S8M-20	40.08	147	46.30	0.258
1176-S8M-30	57.70	147	46.30	0.387
1176-S8M-50	95.99	147	46.30	0.645
1176-S8M-85	160.25	147	46.30	1.096
1184-S8M-20	40.26	148	46.61	0.260
1184-S8M-30	57.92	148	46.61	0.389
1184-S8M-50	96.51	148	46.61	0.649
1184-S8M-85	160.68	148	46.61	1.103
1192-S8M-20	40.43	149	46.93	0.261
1192-S8M-30	58.14	149	46.93	0.392
1192-S8M-50	97.03	149	46.93	0.653
1192-S8M-85	161.12	149	46.93	1.110
1200-S8M-20	40.60	150	47.24	0.263
1200-S8M-30	58.37	150	47.24	0.394
1200-S8M-50	97.55	150	47.24	0.657
1200-S8M-85	161.56	150	47.24	1.118
1208-S8M-20	40.87	151	47.56	0.265
1208-S8M-30	58.86	151	47.56	0.397
1208-S8M-50	97.79	151	47.56	0.662
1208-S8M-85	162.58	151	47.56	1.125
1216-S8M-20	41.14	152	47.87	0.267
1216-S8M-30	59.36	152	47.87	0.400
1216-S8M-50	98.74	152	47.87	0.666
1216-S8M-85	163.61	152	47.87	1.133

STD 8M				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
1240-S8M-20	41.94	155	48.82	0.272
1240-S8M-30	60.86	155	48.82	0.408
1240-S8M-50	98.74	155	48.82	0.679
1240-S8M-85	166.68	155	48.82	1.155
1256-S8M-20	42.48	157	49.45	0.275
1256-S8M-30	61.85	157	49.45	0.413
1256-S8M-50	99.22	157	49.45	0.688
1256-S8M-85	168.72	157	49.45	1.170
1264-S8M-20	42.75	158	49.76	0.277
1264-S8M-30	62.35	158	49.76	0.416
1264-S8M-50	99.46	158	49.76	0.693
1264-S8M-85	169.75	158	49.76	1.177
1280-S8M-20	43.28	160	50.39	0.281
1280-S8M-30	63.35	160	50.39	0.421
1280-S8M-50	99.94	160	50.39	0.701
1280-S8M-85	171.79	160	50.39	1.192
1296-S8M-20	43.66	162	51.02	0.284
1296-S8M-30	64.18	162	51.02	0.426
1296-S8M-50	100.98	162	51.02	0.710
1296-S8M-85	173.76	162	51.02	1.207
1304-S8M-20	43.85	163	51.34	0.286
1304-S8M-30	64.59	163	51.34	0.429
1304-S8M-50	101.50	163	51.34	0.714
1304-S8M-85	174.74	163	51.34	1.214
1312-S8M-20	43.95	164	51.65	0.287
1312-S8M-30	64.80	164	51.65	0.433
1312-S8M-50	102.02	164	51.65	0.721
1312-S8M-85	175.72	164	51.65	1.224
1344-S8M-20	44.66	168	52.91	0.292
1344-S8M-30	65.85	168	52.91	0.448
1344-S8M-50	104.10	168	52.91	0.743
1344-S8M-85	179.65	168	52.91	1.255
1368-S8M-20	45.63	171	53.86	0.295
1368-S8M-30	66.78	171	53.86	0.454
1368-S8M-50	105.66	171	53.86	0.753
1368-S8M-85	182.59	171	53.86	1.271
1400-S8M-20	46.11	175	55.12	0.300
1400-S8M-30	68.03	175	55.12	0.459
1400-S8M-50	107.74	175	55.12	0.762
1400-S8M-85	186.52	175	55.12	1.285

STD 8M				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
1408-S8M-20	46.30	176	55.43	0.302
1408-S8M-30	68.34	176	55.43	0.461
1408-S8M-50	108.26	176	55.43	0.765
1408-S8M-85	187.51	176	55.43	1.288
1440-S8M-20	47.06	180	56.69	0.315
1440-S8M-30	69.58	180	56.69	0.472
1440-S8M-50	110.34	180	56.69	0.787
1440-S8M-85	191.43	180	56.69	1.338
1480-S8M-20	47.70	185	58.27	0.323
1480-S8M-30	69.74	185	58.27	0.485
1480-S8M-50	114.38	185	58.27	0.809
1480-S8M-85	195.79	185	58.27	1.375
1512-S8M-20	48.21	189	59.53	0.330
1512-S8M-30	69.86	189	59.53	0.495
1512-S8M-50	117.61	189	59.53	0.826
1512-S8M-85	199.28	189	59.53	1.404
1520-S8M-20	48.40	190	59.84	0.332
1520-S8M-30	70.26	190	59.84	0.498
1520-S8M-50	118.00	190	59.84	0.838
1520-S8M-85	199.68	190	59.84	1.411
1552-S8M-20	49.16	194	61.10	0.339
1552-S8M-30	71.88	194	61.10	0.508
1552-S8M-50	119.55	194	61.10	0.852
1552-S8M-85	201.29	194	61.10	1.440
1600-S8M-20	50.30	200	62.99	0.349
1600-S8M-30	74.30	200	62.99	0.524
1600-S8M-50	121.88	200	62.99	0.873
1600-S8M-85	203.71	200	62.99	1.485
1624-S8M-20	50.85	203	63.94	0.355
1624-S8M-30	74.94	203	63.94	0.532
1624-S8M-50	123.43	203	63.94	0.886
1624-S8M-85	205.65	203	63.94	1.507
1760-S8M-20	53.97	220	69.29	0.384
1760-S8M-30	78.59	220	69.29	0.576
1760-S8M-50	132.21	220	69.29	0.960
1760-S8M-85	216.63	220	69.29	1.631
1776-S8M-20	54.96	222	69.92	0.387
1776-S8M-30	79.42	222	69.92	0.581
1776-S8M-50	133.92	222	69.92	0.968
1776-S8M-85	220.57	222	69.92	1.646

STD 8M				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt. Ea. (Lbs.)
1800-S8M-20	56.46	225	70.87	0.393
1800-S8M-30	80.67	225	70.87	0.589
1800-S8M-50	136.47	225	70.87	0.981
1800-S8M-85	226.46	225	70.87	1.668
1816-S8M-20	56.99	227	71.50	0.396
1816-S8M-30	81.44	227	71.50	0.594
1816-S8M-50	137.61	227	71.50	0.990
1816-S8M-85	228.51	227	71.50	1.683
1912-S8M-20	60.17	239	75.28	0.417
1912-S8M-30	86.06	239	75.28	0.625
1912-S8M-50	144.44	239	75.28	1.042
1912-S8M-85	240.79	239	75.28	1.771
2000-S8M-20	63.09	250	78.74	0.436
2000-S8M-30	90.30	250	78.74	0.654
2000-S8M-50	150.70	250	78.74	1.089
2000-S8M-85	252.04	250	78.74	1.852
2240-S8M-20	68.71	280	88.19	0.487
2240-S8M-30	100.10	280	88.19	0.731
2240-S8M-50	163.21	280	88.19	1.219
2240-S8M-85	278.13	280	88.19	2.072
2272-S8M-20	69.46	284	89.45	0.494
2272-S8M-30	101.41	284	89.45	0.742
2272-S8M-50	164.88	284	89.45	1.236
2272-S8M-85	281.61	284	89.45	2.101
2392-S8M-20	72.27	299	94.17	0.520
2392-S8M-30	106.31	299	94.17	0.780
2392-S8M-50	171.15	299	94.17	1.300
2392-S8M-85	294.66	299	94.17	2.211
2800-S8M-20	84.40	350	110.24	0.568
2800-S8M-30	120.59	350	110.24	0.853
2800-S8M-50	201.04	350	110.24	1.423
2800-S8M-85	345.83	350	110.24	2.418
2848-S8M-20	85.78	356	112.13	0.574
2848-S8M-30	122.28	356	112.13	0.861
2848-S8M-50	204.44	356	112.13	1.437
2848-S8M-85	352.00	356	112.13	0.244

MXL				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
43.2MXL012	2.31	54	4.32	0.0033
43.2MXL019	2.81	54	4.32	0.0053
43.2MXL025	3.65	54	4.32	0.0070
44MXL012	2.32	55	4.40	0.0034
44MXL019	2.82	55	4.40	0.0054
44MXL025	3.66	55	4.40	0.0071
46.4MXL012	2.34	58	4.64	0.0036
46.4MXL019	2.83	58	4.64	0.0061
46.4MXL025	3.69	58	4.64	0.0075
48MXL012	2.35	60	4.80	0.0037
48MXL019	2.84	60	4.80	0.0059
48MXL025	3.71	60	4.80	0.0078
50.4MXL012	2.35	63	5.04	0.0039
50.4MXL019	2.84	63	5.04	0.0061
50.4MXL025	3.76	63	5.04	0.0081
54.4MXL012	2.86	68	5.44	0.0041
54.4MXL019	2.85	68	5.44	0.0065
54.4MXL025	3.84	68	5.44	0.0086
56MXL012	2.37	70	5.60	0.0042
56MXL019	2.86	70	5.60	0.0067
56MXL025	3.88	70	5.60	0.0088
56.8MXL012	2.38	71	5.68	0.0043
56.8MXL019	2.87	71	5.68	0.0068
56.8MXL025	3.89	71	5.68	0.0089
57.6MXL012	2.39	72	5.76	0.0044
57.6MXL019	2.88	72	5.76	0.0070
57.6MXL025	3.91	72	5.76	0.0092
60MXL012	2.39	75	6.00	0.0045
60MXL019	2.89	75	6.00	0.0072
60MXL025	3.93	75	6.00	0.0094
61.6MXL012	2.40	77	6.16	0.0046
61.6MXL019	2.90	77	6.16	0.0073
61.6MXL025	3.99	77	6.16	0.0095
64MXL012	2.41	80	6.40	0.0049
64MXL019	3.03	80	6.40	0.0077
64MXL025	4.00	80	6.40	0.0101
65.6MXL012	2.42	82	6.56	0.0050
65.6MXL019	3.06	82	6.56	0.0079
65.6MXL025	4.01	82	6.56	0.0103
68MXL012	2.43	85	6.80	0.0051
68MXL019	3.08	85	6.80	0.0082
68MXL025	4.03	85	6.80	0.0108
69.6MXL012	2.45	87	6.96	0.0053
69.6MXL019	3.09	87	6.96	0.0085
69.6MXL025	4.04	87	6.96	0.0111

MXL				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
70MXL012	2.45	88	7.00	0.0053
70MXL019	3.09	88	7.00	0.0085
70MXL025	4.04	88	7.00	0.0111
70.4MXL012	2.45	88	7.04	0.0054
70.4MXL019	3.10	88	7.04	0.0085
70.4MXL025	4.05	88	7.04	0.0112
72MXL012	2.46	90	7.20	0.0055
72MXL019	3.11	90	7.20	0.0086
72MXL025	4.06	90	7.20	0.0114
75.2MXL012	2.47	94	7.52	0.0057
75.2MXL013	3.11	94	7.52	0.0090
75.2MXL014	4.06	94	7.52	0.0118
76MXL012	2.48	95	7.60	0.0057
76MXL019	3.14	95	7.60	0.0090
76MXL025	4.09	95	7.60	0.0118
77.6MXL012	2.50	97	7.76	0.0058
77.6MXL019	3.15	97	7.76	0.0092
77.6MXL025	4.11	97	7.76	0.0120
80MXL012	2.53	100	8.00	0.0060
80MXL019	3.16	100	8.00	0.0095
80MXL025	4.13	100	8.00	0.0125
80.8MXL012	2.54	101	8.08	0.0061
80.8MXL019	3.17	101	8.08	0.0096
80.8MXL025	4.14	101	8.08	0.0126
82.4MXL012	2.55	103	8.24	0.0062
82.4MXL019	3.19	103	8.24	0.0098
82.4MXL025	4.16	103	8.24	0.0129
84MXL012	2.56	105	8.40	0.0063
84MXL019	3.19	105	8.40	0.0099
84MXL025	4.17	105	8.40	0.0130
84.8MXL012	2.57	106	8.48	0.0064
84.8MXL019	3.20	106	8.48	0.0101
84.8MXL025	4.18	106	8.48	0.0133
88MXL012	2.58	110	8.80	0.0065
88MXL019	3.21	110	8.80	0.0103
88MXL025	4.20	110	8.80	0.0135
89.6MXL012	2.59	112	8.96	0.0067
89.6MXL019	3.24	112	8.96	0.0106
89.6MXL025	4.29	112	8.96	0.0140
91.2MXL012	2.60	114	9.12	0.0068
91.2MXL019	3.25	114	9.12	0.0108
91.2MXL025	4.30	114	9.12	0.0142
94.4MXL012	2.60	118	9.44	0.0071
94.4MXL019	3.25	118	9.44	0.0110
94.4MXL025	4.30	118	9.44	0.0146

MXL				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
96MXL012	2.61	120	9.60	0.0072
96MXL019	3.26	120	9.60	0.0113
96MXL025	4.31	120	9.60	0.0149
97.6MXL012	2.62	122	9.76	0.0072
97.6MXL019	3.26	122	9.76	0.0113
97.6MXL025	4.31	122	9.76	0.0149
98MXL012	2.62	123	9.80	0.0072
98MXL019	3.27	123	9.80	0.0114
98MXL025	4.32	123	9.80	0.0150
98.4MXL012	2.63	123	9.84	0.0073
98.4MXL019	3.29	123	9.84	0.0116
98.4MXL025	4.33	123	9.84	0.0152
100MXL012	2.65	125	10.00	0.0074
100MXL019	3.33	125	10.00	0.0118
100MXL025	4.44	125	10.00	0.0155
100.8MXL012	2.66	126	10.08	0.0075
100.8MXL019	3.34	126	10.08	0.0119
100.8MXL025	4.46	126	10.08	0.0156
105.6MXL012	2.67	132	10.56	0.0075
105.6MXL019	3.35	132	10.56	0.0119
105.6MXL025	4.48	132	10.56	0.0156
112MXL012	2.68	140	11.20	0.0083
112MXL019	3.38	140	11.20	0.0132
112MXL025	4.52	140	11.20	0.0173
120MXL012	2.77	150	12.00	0.0090
120MXL019	3.48	150	12.00	0.0142
120MXL025	4.62	150	12.00	0.0187
124MXL012	2.78	155	12.40	0.0091
124MXL019	3.50	155	12.40	0.0145
124MXL025	4.67	155	12.40	0.0191
131.2MXL012	2.82	164	13.12	0.0096
131.2MXL019	3.53	164	13.12	0.0152
131.2MXL025	4.71	164	13.12	0.0200
132MXL012	2.83	165	13.20	0.0098
132MXL019	3.54	165	13.20	0.0155
132MXL025	4.72	165	13.20	0.0204
132.8MXL012	2.85	166	13.28	0.0099
132.8MXL019	3.57	166	13.28	0.0156
132.8MXL025	4.77	166	13.28	0.0206
136MXL012	2.87	170	13.60	0.0101
136MXL019	3.58	170	13.60	0.0160
136MXL025	4.84	170	13.60	0.0210
140MXL012	2.88	175	14.00	0.0104
140MXL019	3.60	175	14.00	0.0165
140MXL025	4.96	175	14.00	0.0217

MXL				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
144MXL012	2.89	180	14.40	0.0107
144MXL019	3.63	180	14.40	0.0170
144MXL025	4.98	180	14.40	0.0223
147.2MXL012	2.90	184	14.72	0.0109
147.2MXL019	3.66	184	14.72	0.0173
147.2MXL025	4.91	184	14.72	0.0227
180MXL012	3.10	225	18.00	0.0132
180MXL019	3.97	225	18.00	0.0209
180MXL025	5.39	225	18.00	0.0276
188.8MXL012	3.12	236	18.88	0.0133
188.8MXL019	3.99	236	18.88	0.0210
188.8MXL025	5.42	236	18.88	0.0278
200.8MXL012	3.26	251	20.08	0.0149
200.8MXL019	4.14	251	20.08	0.0236
200.8MXL025	5.69	251	20.08	0.0310
238.4MXL012	3.39	298	23.84	0.0196
238.4MXL019	4.61	298	23.84	0.0336
238.4MXL025	6.16	298	23.84	0.0417
277.6MXL012	3.53	347	27.76	0.0245
277.6MXL019	5.10	347	27.76	0.0440
277.6MXL025	6.65	347	27.76	0.0529
292MXL012	3.65	365	29.20	0.0263
292MXL019	5.28	365	29.20	0.0478
292MXL025	6.83	365	29.20	0.0570
296.8MXL012	3.70	371	29.68	0.0270
296.8MXL019	5.35	371	29.68	0.0492
296.8MXL025	6.90	371	29.68	0.0585
297.6MXL012	3.71	372	29.76	0.2330
297.6MXL019	5.38	372	29.76	0.0369
297.6MXL025	6.93	372	29.76	0.4860
320MXL012	3.89	400	32.00	0.0234
320MXL019	5.52	400	32.00	0.0370
320MXL025	7.05	400	32.00	0.0487
329.6MXL012	3.99	412	32.96	0.0240
329.6MXL019	5.60	412	32.96	0.0375
329.6MXL025	7.10	412	32.96	0.0493
347.2MXL012	4.10	434	34.72	0.0242
347.2MXL019	5.67	434	34.72	0.0379
347.2MXL025	7.18	434	34.72	0.0501
362.4MXL012	4.15	453	36.24	0.0244
362.4MXL019	5.73	453	36.24	0.0382
362.4MXL025	7.25	453	36.24	0.0512
370.4MXL012	4.17	463	37.04	0.0247
370.4MXL019	5.76	463	37.04	0.0386
370.4MXL025	7.28	463	37.04	0.0514

MXL				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
398.4MXL012	4.24	498	39.84	0.0249
398.4MXL019	5.86	498	39.84	0.0389
398.4MXL025	7.38	498	39.84	0.0519
402.4MXL012	4.25	503	40.24	0.0249
402.4MXL019	5.87	503	40.24	0.0389
402.4MXL025	7.39	503	40.24	0.0520
404MXL012	4.26	505	40.40	0.0250
404MXL019	5.88	505	40.40	0.0340
404MXL025	7.41	505	40.40	0.0521

XL				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
60XL025	4.01	30	6.00	0.0210
60XL037	5.22	30	6.00	0.0311
70XL025	4.11	35	7.00	0.0241
70XL037	5.44	35	7.00	0.0357
76XL025	4.12	38	7.60	0.0261
76XL037	5.46	38	7.60	0.0386
80XL025	4.13	40	8.00	0.0274
80XL037	5.61	40	8.00	0.0406
86XL025	4.17	43	8.60	0.0293
86XL037	5.68	43	8.60	0.0433
90XL025	4.24	45	9.00	0.0304
90XL037	5.71	45	9.00	0.0450
92XL025	4.25	46	9.20	0.0312
92XL037	5.72	46	9.20	0.0462
94XL025	4.26	47	9.40	0.0317
94XL037	5.76	47	9.40	0.0469
96XL025	4.27	48	9.60	0.0325
96XL037	5.80	48	9.60	0.0481
100XL025	4.44	50	10.00	0.0339
100XL037	5.89	50	10.00	0.0501
102XL025	4.46	51	10.20	0.0343
102XL037	5.93	51	10.20	0.0508
106XL025	4.48	53	10.60	0.0357
106XL037	5.94	53	10.60	0.0529
108XL025	4.49	54	10.80	0.0363
108XL037	5.97	54	10.80	0.0537
110XL025	4.55	55	11.00	0.0370
110XL037	6.07	55	11.00	0.0547

XL				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
112XL025	4.57	56	11.20	0.0378
112XL037	6.14	56	11.20	0.0559
114XL025	4.58	57	11.40	0.0601
114XL037	6.17	57	11.40	0.0889
116XL025	4.59	58	11.60	0.0388
116XL037	6.18	58	11.60	0.0574
118XL025	4.61	59	11.80	0.0396
118XL037	6.21	59	11.80	0.0585
120XL025	4.62	60	12.00	0.0403
120XL037	6.24	60	12.00	0.0596
124XL025	4.65	62	12.40	0.0415
124XL037	6.27	62	12.40	0.0613
126XL025	4.68	63	12.60	0.0420
126XL037	6.28	63	12.60	0.0622
130XL025	4.77	65	13.00	0.0456
130XL037	6.46	65	13.00	0.0675
134XL025	4.80	67	13.40	0.0448
134XL037	6.47	67	13.40	0.0663
136XL025	4.85	68	13.60	0.0455
136XL037	6.49	68	13.60	0.0673
138XL025	4.86	69	13.80	0.0463
138XL037	6.51	69	13.80	0.0685
140XL025	4.94	70	14.00	0.0467
140XL037	6.59	70	14.00	0.0692
148XL025	4.98	74	14.80	0.0493
148XL037	6.65	74	14.80	0.0729
150XL025	5.10	75	15.00	0.0499
150XL037	6.81	75	15.00	0.0739
156XL025	5.13	78	15.60	0.0519
156XL037	6.82	78	15.60	0.0768
160XL025	5.14	80	16.00	0.0532
160XL037	6.95	80	16.00	0.0787
162XL025	5.18	81	16.20	0.0541
162XL037	6.97	81	16.20	0.0800
166XL025	5.19	83	16.60	0.0552
166XL037	6.98	83	16.60	0.0817
168XL025	5.20	84	16.80	0.0588
168XL037	7.03	84	16.80	0.0870
170XL025	5.22	85	17.00	0.0565
170XL037	7.08	85	17.00	0.0836
174XL025	5.26	87	17.40	0.0579
174XL037	7.12	87	17.40	0.0856
176XL025	5.28	88	17.60	0.0582
176XL037	7.14	88	17.60	0.0862

XL				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
178XL025	5.30	89	17.80	0.0591
178XL037	7.16	89	17.80	0.0875
180XL025	5.35	90	18.00	0.0597
180XL037	7.27	90	18.00	0.0884
182XL025	5.40	91	18.20	0.0602
182XL037	7.30	91	18.20	0.0890
184XL025	5.42	92	18.40	0.0607
184XL037	7.38	92	18.40	0.0899
188XL025	5.51	94	18.80	0.0622
188XL037	7.43	94	18.80	0.0921
190XL025	5.55	95	19.00	0.0629
190XL037	7.45	95	19.00	0.0931
196XL025	5.63	98	19.60	0.0649
196XL037	7.60	98	19.60	0.0960
200XL025	5.68	100	20.00	0.0661
200XL037	7.70	100	20.00	0.0979
210XL025	5.73	105	21.00	0.0692
210XL037	7.87	105	21.00	0.1025
220XL025	5.88	110	22.00	0.0759
220XL037	7.95	110	22.00	0.1124
230XL025	6.10	115	23.00	0.0759
230XL037	8.12	115	23.00	0.1123
232XL025	6.11	116	23.20	0.0765
232XL037	8.17	116	23.20	0.1132
240XL025	6.12	120	24.00	0.0791
240XL037	8.40	120	24.00	0.1171
244XL025	6.13	122	24.40	0.0803
244XL037	8.41	122	24.40	0.1188
248XL025	6.16	124	24.80	0.0815
248XL037	8.42	124	24.80	0.1206
250XL025	6.18	125	25.00	0.0821
250XL037	8.43	125	25.00	0.1215
260XL025	6.28	130	26.00	0.0854
260XL037	8.62	130	26.00	0.1264
270XL025	6.41	135	27.00	0.0888
270XL037	8.78	135	27.00	0.1314
272XL025	6.43	136	27.20	0.0895
272XL037	8.83	136	27.20	0.1324
274XL025	6.46	137	27.40	0.0901
274XL037	8.84	137	27.40	0.1334
280XL025	6.62	140	28.00	0.0920
280XL037	9.05	140	28.00	0.1361
286XL025	6.67	143	28.60	0.0939
286XL037	9.22	143	28.60	0.1390

XL				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
290XL025	6.71	145	29.00	0.0952
290XL037	9.33	145	29.00	0.1409
300XL025	6.86	150	30.00	0.0984
300XL037	9.37	150	30.00	0.1456
306XL025	6.88	153	30.60	0.1005
306XL037	9.41	153	30.60	0.1487
316XL025	6.96	158	31.60	0.1036
316XL037	9.69	158	31.60	0.1533
322XL025	7.14	161	32.20	0.1055
322XL037	9.72	161	32.20	0.1562
330XL025	7.27	165	33.00	0.1082
330XL037	9.97	165	33.00	0.1601
340XL025	7.37	170	34.00	0.1113
340XL037	10.14	170	34.00	0.1647
344XL025	7.40	172	34.40	0.1124
344XL037	10.19	172	34.40	0.1664
350XL025	7.47	175	35.00	0.1147
350XL037	10.39	175	35.00	0.1698
380XL025	7.74	190	38.00	0.1242
380XL037	10.82	190	38.00	0.1839
382XL025	7.76	191	38.20	0.1249
382XL037	10.85	191	38.20	0.1848
388XL025	7.83	194	38.80	0.1268
388XL037	10.92	194	38.80	0.1883
392XL025	7.87	196	39.20	0.1281
392XL037	10.97	196	39.20	0.1895
412XL025	8.08	206	41.20	0.1345
412XL037	11.23	206	41.20	0.1990
414XL025	8.10	207	41.40	0.1351
414XL037	11.26	207	41.40	0.2000
438XL025	8.37	219	43.80	0.1430
438XL037	11.60	219	43.80	0.2116
460XL025	8.74	230	46.00	0.1503
460XL037	12.21	230	46.00	0.2225
498XL025	9.14	249	49.80	0.1624
498XL037	12.80	249	49.80	0.2403
506XL025	9.22	253	50.60	0.1649
506XL037	12.92	253	50.60	0.2440
580XL025	10.75	290	58.00	0.1889
580XL037	15.02	290	58.00	0.2796
630XL025	11.65	315	63.00	0.2048
630XL037	16.16	315	63.00	0.3032

L				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
124L050	10.44	33	12.40	0.1224
124L075	14.66	33	12.40	0.1836
124L100	19.09	33	12.40	0.2448
150L050	11.57	40	15.00	0.1472
150L075	16.32	40	15.00	0.2208
150L100	21.08	40	15.00	0.2944
187L050	12.50	50	18.70	0.1817
187L075	18.15	50	18.70	0.2725
187L100	23.17	50	18.70	0.3633
210L050	13.72	56	21.00	0.2039
210L075	19.81	56	21.00	0.3059
210L100	25.68	56	21.00	0.4079
225L050	13.88	60	22.50	0.2184
225L075	20.38	60	22.50	0.3276
225L100	26.03	60	22.50	0.4368
236L050	14.56	63	23.60	0.2285
236L075	21.16	63	23.60	0.3427
236L100	27.26	63	23.60	0.4570
240L050	14.81	64	24.00	0.2322
240L075	21.44	64	24.00	0.3483
240L100	27.71	64	24.00	0.4643
244L050	14.87	65	24.40	0.2360
244L075	21.51	65	24.40	0.3540
244L100	27.85	65	24.40	0.4719
255L050	15.05	68	25.50	0.2464
255L075	21.71	68	25.50	0.3696
255L100	28.24	68	25.50	0.4928
270L050	15.74	72	27.00	0.2607
270L075	22.80	72	27.00	0.3910
270L100	29.72	72	27.00	0.5213
285L050	16.18	76	28.50	0.2751
285L075	23.60	76	28.50	0.4127
285L100	30.81	76	28.50	0.5502
300L050	16.95	80	30.00	0.2894
300L075	24.59	80	30.00	0.4340
300L100	32.19	80	30.00	0.5787
322L050	17.39	86	32.20	0.3105
322L075	25.72	86	32.20	0.4657
322L100	33.67	86	32.20	0.6210
345L050	18.15	92	34.50	0.3321
345L075	26.68	92	34.50	0.4981
345L100	35.28	92	34.50	0.6641

L				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
367L050	18.80	98	36.70	0.3530
367L075	27.68	98	36.70	0.5295
367L100	36.46	98	36.70	0.7059
390L050	19.84	104	39.00	0.3746
390L075	29.72	104	39.00	0.5618
390L100	38.25	104	39.00	0.7491
420L050	21.03	112	42.00	0.4033
420L075	31.30	112	42.00	0.6049
420L100	40.62	112	42.00	0.8065
450L050	21.90	120	45.00	0.4315
450L075	32.63	120	45.00	0.6473
450L100	42.82	120	45.00	0.8630
454L050	22.08	121	45.40	0.4353
454L075	32.87	121	45.40	0.6530
454L100	43.10	121	45.40	0.8707
480L050	23.27	128	48.00	0.4602
480L075	34.46	128	48.00	0.6903
480L100	44.89	128	48.00	0.9204
510L050	23.80	136	51.00	0.4887
510L075	35.21	136	51.00	0.7330
510L100	46.35	136	51.00	0.9774
540L050	24.98	144	54.00	0.5167
540L075	37.64	144	54.00	0.7751
540L100	50.09	144	54.00	1.0334
600L050	27.34	160	60.00	0.5727
600L075	42.50	160	60.00	0.8591
600L100	57.57	160	60.00	1.1455

H				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
240H075	21.93	48	24.00	0.4399
240H100	28.60	48	24.00	0.5865
240H150	41.04	48	24.00	0.8798
240H200	54.31	48	24.00	1.1730
240H300	79.64	48	24.00	1.7596
255H075	22.81	51	25.50	0.4669
255H100	29.54	51	25.50	0.6226
255H150	42.79	51	25.50	0.9339
255H200	56.07	51	25.50	1.2452
255H300	82.63	51	25.50	1.8677
270H075	23.69	54	27.00	0.4940
270H100	30.48	54	27.00	0.6586
270H150	44.54	54	27.00	0.9879
270H200	57.82	54	27.00	1.3173
270H300	85.64	54	27.00	1.9759
300H075	25.20	60	30.00	0.5481
300H100	32.61	60	30.00	0.7307
300H150	47.57	60	30.00	1.0961
300H200	62.36	60	30.00	1.4615
300H300	92.14	60	30.00	2.1922
330H075	26.98	66	33.00	0.6021
330H100	34.89	66	33.00	0.8029
330H150	51.08	66	33.00	1.2043
330H200	67.09	66	33.00	1.6057
330H300	99.16	66	33.00	2.4086
335H075	27.27	67	33.50	0.6110
335H100	35.37	67	33.50	0.8147
335H150	51.62	67	33.50	1.2221
335H200	67.75	67	33.50	1.6294
335H300	100.31	67	33.50	2.4441
360H075	28.70	72	36.00	0.6555
360H100	37.79	72	36.00	0.8740
360H150	54.34	72	36.00	1.3111
360H200	71.07	72	36.00	1.7481
360H300	106.06	72	36.00	2.6221
370H075	29.29	74	37.00	0.6734
370H100	38.29	74	37.00	0.8979
370H150	55.18	74	37.00	1.3469
370H200	73.91	74	37.00	1.7958
370H300	108.21	74	37.00	2.6938

H				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
390H075	30.57	78	39.00	0.7089
390H100	39.93	78	39.00	0.9452
390H150	58.17	78	39.00	1.4178
390H200	75.81	78	39.00	1.8905
390H300	112.18	78	39.00	2.8357
420H075	32.29	84	42.00	0.7634
420H100	41.94	84	42.00	1.0178
420H150	61.85	84	42.00	1.5267
420H200	80.95	84	42.00	2.0356
420H300	118.92	84	42.00	3.0534
450H075	34.07	90	45.00	0.8171
450H100	44.00	90	45.00	1.0895
450H150	65.16	90	45.00	1.6342
450H200	84.65	90	45.00	2.1789
450H300	126.59	90	45.00	3.2684
480H075	35.75	96	48.00	0.8715
480H100	46.46	96	48.00	1.1620
480H150	68.04	96	48.00	1.7430
480H200	90.05	96	48.00	2.3240
480H300	132.36	96	48.00	3.4861
510H075	36.89	102	51.00	0.9249
510H100	47.54	102	51.00	1.2332
510H150	69.95	102	51.00	1.8498
510H200	92.05	102	51.00	2.4664
510H300	137.36	102	51.00	3.6996
540H075	38.63	108	54.00	0.9776
540H100	50.42	108	54.00	1.3035
540H150	74.54	108	54.00	1.9552
540H200	97.64	108	54.00	2.6070
540H300	146.97	108	54.00	3.9104
570H075	40.06	114	57.00	1.0320
570H100	52.51	114	57.00	1.3761
570H150	77.44	114	57.00	2.0641
570H200	102.44	114	57.00	2.7521
570H300	149.94	114	57.00	4.1282
600H075	42.66	120	60.00	1.0858
600H100	55.58	120	60.00	1.4477
600H150	81.95	120	60.00	2.1716
600H200	107.01	120	60.00	2.8954
600H300	161.03	120	60.00	4.3431

H				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
630H075	43.58	126	63.00	1.1402
630H100	57.40	126	63.00	1.5203
630H150	84.40	126	63.00	2.2804
630H200	110.75	126	63.00	3.0405
630H300	164.15	126	63.00	4.5608
660H075	45.39	132	66.00	1.1943
660H100	60.48	132	66.00	1.5924
660H150	88.64	132	66.00	2.3886
660H200	117.36	132	66.00	3.1848
660H300	172.76	132	66.00	4.7771
700H075	47.68	140	70.00	1.2652
700H100	63.41	140	70.00	1.6870
700H150	92.93	140	70.00	2.5305
700H200	123.59	140	70.00	3.3740
700H300	180.88	140	70.00	5.0610
730H075	48.98	146	73.00	1.3193
730H100	64.04	146	73.00	1.7591
730H150	93.98	146	73.00	2.6387
730H200	125.24	146	73.00	3.5182
730H300	186.93	146	73.00	5.2773
750H075	50.47	150	75.00	1.3552
750H100	66.34	150	75.00	1.8069
750H150	98.02	150	75.00	2.7103
750H200	127.56	150	75.00	3.6137
750H300	192.49	150	75.00	5.4206
800H075	53.29	160	80.00	1.4437
800H100	70.81	160	80.00	1.9249
800H150	105.19	160	80.00	2.8874
800H200	136.34	160	80.00	3.8498
800H300	202.53	160	80.00	5.7747
850H075	56.13	170	85.00	1.5346
850H100	73.72	170	85.00	2.0462
850H150	107.78	170	85.00	3.0692
850H200	144.42	170	85.00	4.0923
850H300	214.20	170	85.00	6.1385
900H075	59.38	180	90.00	1.6238
900H100	78.22	180	90.00	2.1651
900H150	115.15	180	90.00	3.2477
900H200	151.17	180	90.00	4.3302
900H300	226.61	180	90.00	6.4954

H				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
1000H075	64.74	200	100.00	1.8030
1000H100	85.00	200	100.00	2.4040
1000H150	127.21	200	100.00	3.6059
1000H200	166.14	200	100.00	4.8079
1000H300	247.18	200	100.00	7.2119
1100H075	69.90	220	110.00	1.9824
1100H100	92.85	220	110.00	2.6433
1100H150	136.98	220	110.00	3.9649
1100H200	183.28	220	110.00	5.2865
1100H300	271.56	220	110.00	7.9298
1250H075	78.37	250	125.00	2.2518
1250H100	103.29	250	125.00	3.0024
1250H150	154.14	250	125.00	4.5036
1250H200	204.68	250	125.00	6.0048
1250H300	307.05	250	125.00	9.0073
1400H075	87.91	280	140.00	2.5205
1400H100	114.22	280	140.00	3.3607
1400H150	170.98	280	140.00	5.0410
1400H200	228.32	280	140.00	6.7213
1400H300	337.30	280	140.00	10.0820
1700H075	103.84	340	170.00	3.0593
1700H100	136.64	340	170.00	4.0790
1700H150	205.24	340	170.00	6.1185
1700H200	269.75	340	170.00	8.1580
1700H300	406.64	340	170.00	12.2370

XH				
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)	Wt.Ea.(Lbs.)
507XH200	222.48	58	50.70	5.0449
507XH300	312.89	58	50.70	7.5674
507XH400	403.73	58	50.70	10.0898
534XH200	230.00	61	53.40	5.3084
534XH300	323.65	61	53.40	7.9626
534XH400	416.10	61	53.40	10.6167
560XH200	237.24	64	56.00	5.5621
560XH300	334.02	64	56.00	8.3431
560XH400	428.02	64	56.00	11.1242
630XH200	254.64	72	63.00	6.2446
630XH300	354.16	72	63.00	9.3669
630XH400	457.55	72	63.00	12.4892
700XH200	270.72	80	70.00	6.9262
700XH300	390.18	80	70.00	10.3893
700XH400	502.23	80	70.00	13.8524
770XH200	287.78	88	77.00	7.6096
770XH300	410.52	88	77.00	11.4144
770XH400	527.49	88	77.00	15.2192
840XH200	309.46	96	84.00	8.2931
840XH300	440.51	96	84.00	12.4396
840XH400	573.40	96	84.00	16.5861
980XH200	345.45	112	98.00	9.6562
980XH300	495.51	112	98.00	14.4844
980XH400	643.46	112	98.00	19.3125
1120XH200	374.73	128	112.00	11.0158
1120XH300	534.27	128	112.00	16.5236
1120XH400	697.89	128	112.00	22.0315
1260XH200	411.61	144	126.00	12.3817
1260XH300	589.06	144	126.00	18.5726
1260XH400	773.35	144	126.00	24.7634
1400XH200	453.63	160	140.00	16.4950
1400XH300	654.54	160	140.00	24.7425
1400XH400	844.17	160	140.00	32.9900
1540XH200	477.92	176	154.00	15.1145
1540XH300	691.12	176	154.00	22.6718
1540XH400	889.48	176	154.00	30.2291
1750XH200	543.99	200	175.00	17.1611
1750XH300	786.81	200	175.00	25.7417
1750XH400	1,021.17	200	175.00	34.3223


XXH			
Order Code	Suggested List Price (USD)	No. of Teeth	Pitch length (In.)
700XXH200	570.68	56	70.00
700XXH300	822.50	56	70.00
700XXH400	1,058.70	56	70.00
700XXH500	1,294.90	56	70.00
800XXH200	625.76	64	80.00
800XXH300	902.11	64	80.00
800XXH400	1161.67	64	80.00
800XXH500	1,421.24	64	80.00
900XXH200	680.84	72	90.00
900XXH300	981.72	72	90.00
900XXH400	1,264.65	72	90.00
900XXH500	1,547.57	72	90.00
1000XXH200	735.92	80	10.00
1000XXH300	1,061.33	80	10.00
1000XXH400	1,367.62	80	10.00
1000XXH500	1,673.91	80	10.00
1200XXH200	846.08	96	12.00
1200XXH300	1,220.55	96	12.00
1200XXH400	1,573.56	96	12.00
1200XXH500	1,926.58	96	12.00
1400XXH200	956.25	112	14.00
1400XXH300	1,379.77	112	14.00
1400XXH400	1,779.51	112	14.00
1400XXH500	2,179.25	112	14.00
1600XXH200	1,066.42	128	16.00
1600XXH300	1,538.99	128	16.00
1600XXH400	1,985.46	128	16.00
1600XXH500	2,431.92	128	16.00
1800XXH200	1176.60	144	18.00
1800XXH300	1,698.21	144	18.00
1800XXH400	2,191.41	144	18.00
1800XXH500	2,684.59	144	18.00

CONTI® SYNCHROCOLOR

Silicone-free synchronous belt

free of substances that damage paintwork

HTD



Profile

8M

14M

SIZES AVAILABLE ON REQUEST BY SPECIAL ORDER

Properties:

- free of silicon and paintable
- conditionally resistant to oil
- temperature range, depending on application, from -4°F to +212°F (-20°C to +100°C)
- ozone-resistant
- suitable for tropical climates
- electrically conductive to ISO 9563




Heavy-duty **CONTI® SYNCHROCOLOR CXP** and **CONTI® SYNCHROCOLOR CXA** types are available on request.

CONTI® SYNCHROTWIN

Double-sided synchronous belts

for compact drives with reverse rotation

DHTD




Profile

D5M

D8M

D14M


DSTD



Profile

DS8M

DH



Profile

DH

Properties:

- conditionally resistant to oil
- temperature range, depending on application, from -4°F to +212°F (-20°C to +100°C)
- suitable for tropical climates
- resistant to aging and ozone



D5M		
Order Code	Suggested List Price (USD)	Pitch length (In.)
565-D5M-09	49.72	22.24
565-D5M-15	71.69	22.24
565-D5M-25	108.30	22.24
600-D5M-09	52.75	23.62
600-D5M-15	74.60	23.62
600-D5M-25	111.01	23.62
615-D5M-09	54.06	24.21
615-D5M-15	75.85	24.21
615-D5M-25	112.17	24.21
620-D5M-09	54.49	24.41
620-D5M-15	76.27	24.41
620-D5M-25	112.56	24.41
630-D5M-09	54.88	24.80
630-D5M-15	76.73	24.80
630-D5M-25	113.14	24.80
635-D5M-09	55.07	25.00
635-D5M-15	76.95	25.00
635-D5M-25	113.43	25.00
665-D5M-09	56.23	26.18
665-D5M-15	78.33	26.18
665-D5M-25	115.17	26.18
700-D5M-09	57.94	27.56
700-D5M-15	81.23	27.56
700-D5M-25	120.05	27.56
710-D5M-09	58.42	27.95
710-D5M-15	82.05	27.95
710-D5M-25	121.44	27.95
740-D5M-09	58.36	29.13
740-D5M-15	84.46	29.13
740-D5M-25	127.97	29.13
755-D5M-09	58.34	29.72
755-D5M-15	85.67	29.72
755-D5M-25	131.24	29.72
800-D5M-09	58.31	31.50
800-D5M-15	87.23	31.50
800-D5M-25	135.43	31.50
835-D5M-09	60.43	32.87
835-D5M-15	90.07	32.87
835-D5M-25	139.48	32.87
840-D5M-09	60.72	33.07
840-D5M-15	90.48	33.07
840-D5M-25	140.07	33.07

D5M		
Order Code	Suggested List Price (USD)	Pitch length (In.)
860-D5M-09	61.96	33.86
860-D5M-15	92.12	33.86
860-D5M-25	142.38	33.86
890-D5M-09	63.78	35.04
890-D5M-15	94.56	35.04
890-D5M-25	145.87	35.04
900-D5M-09	64.77	35.43
900-D5M-15	96.61	35.43
900-D5M-25	149.68	35.43
925-D5M-09	65.03	36.42
925-D5M-15	97.13	36.42
925-D5M-25	150.63	36.42
950-D5M-09	69.60	37.40
950-D5M-15	100.89	37.40
950-D5M-25	292.51	37.40
1000-D5M-09	75.49	3.94
1000-D5M-15	109.07	3.94
1000-D5M-25	165.04	3.94
1050-D5M-09	75.49	4.13
1050-D5M-15	109.07	4.13
1050-D5M-25	165.04	4.13
1125-D5M-09	77.61	4.41
1125-D5M-15	112.46	4.41
1125-D5M-25	170.54	4.41
1200-D5M-09	83.30	4.72
1200-D5M-15	118.65	4.72
1200-D5M-25	177.57	4.72
1270-D5M-09	76.09	5.00
1270-D5M-15	118.38	5.00
1270-D5M-25	188.87	5.00
1420-D5M-09	79.80	5.59
1420-D5M-15	124.14	5.59
1420-D5M-25	198.06	5.59
1500-D5M-09	83.47	5.91
1500-D5M-15	131.73	5.91
1500-D5M-25	212.17	5.91
1595-D5M-09	97.56	6.26
1595-D5M-15	143.72	6.26
1595-D5M-25	220.67	6.26
1690-D5M-09	100.26	6.65
1690-D5M-15	149.05	6.65
1690-D5M-25	230.36	6.65
2000-D5M-09	109.07	7.87
2000-D5M-15	166.41	7.87
2000-D5M-25	261.98	7.87

D8M			
Order Code	Suggested List Price (USD)	Pitch length (In.)	Wt. Ea. (Lbs.)
600-D8M-20	71.81	22.05	0.1836
600-D8M-30	99.71	22.05	0.2754
600-D8M-50	161.05	22.05	0.4591
600-D8M-85	265.59	22.05	0.7804
624-D8M-20	73.72	24.57	0.1906
624-D8M-30	104.90	24.57	0.2858
624-D8M-50	169.21	24.57	0.4764
624-D8M-85	285.63	24.57	0.8099
640-D8M-20	75.00	25.20	0.1952
640-D8M-30	108.36	25.20	0.2928
640-D8M-50	174.65	25.20	0.4880
640-D8M-85	298.99	25.20	0.8295
656-D8M-20	76.55	25.83	0.1981
656-D8M-30	103.24	25.83	0.3000
656-D8M-50	177.05	25.83	0.5000
656-D8M-85	300.65	25.83	0.8500
720-D8M-20	82.77	28.35	0.2193
720-D8M-30	114.81	28.35	0.3289
720-D8M-50	186.63	28.35	0.5482
720-D8M-85	307.28	28.35	0.9320
776-D8M-20	88.95	30.55	0.2357
776-D8M-30	126.33	30.55	0.3535
776-D8M-50	197.53	30.55	0.5892
776-D8M-85	322.89	30.55	1.0016
784-D8M-20	89.83	30.87	0.2380
784-D8M-30	127.97	30.87	0.3570
784-D8M-50	200.46	30.87	0.5951
784-D8M-85	344.48	30.87	1.0116
800-D8M-20	91.60	31.50	0.2427
800-D8M-30	131.26	31.50	0.3641
800-D8M-50	206.31	31.50	0.6068
800-D8M-85	353.78	31.50	1.0315
880-D8M-20	97.79	34.65	0.2661
880-D8M-30	139.53	34.65	0.3992
880-D8M-50	224.99	34.65	0.6653
880-D8M-85	381.35	34.65	1.1310
912-D8M-20	100.18	35.91	0.2758
912-D8M-30	141.75	35.91	0.4138
912-D8M-50	226.98	35.91	0.6896
912-D8M-85	386.23	35.91	1.1723

D8M			
Order Code	Suggested List Price (USD)	Pitch length (In.)	Wt. Ea. (Lbs.)
920-D8M-20	100.78	36.22	0.2783
920-D8M-30	142.30	36.22	0.4174
920-D8M-50	227.48	36.22	0.6957
920-D8M-85	387.45	36.22	1.1827
960-D8M-20	102.12	37.80	0.2898
960-D8M-30	144.07	37.80	0.4348
960-D8M-50	235.26	37.80	0.7246
960-D8M-85	402.64	37.80	1.2318
1040-D8M-20	110.23	40.94	0.3136
1040-D8M-30	155.24	40.94	0.4705
1040-D8M-50	247.94	40.94	0.7841
1040-D8M-85	422.66	40.94	1.3330
1120-D8M-20	113.80	44.09	0.3375
1120-D8M-30	165.74	44.09	0.5062
1120-D8M-50	260.30	44.09	0.8436
1120-D8M-85	437.75	44.09	1.4342
1200-D8M-20	117.77	47.24	0.3612
1200-D8M-30	169.68	47.24	0.5417
1200-D8M-50	262.17	47.24	0.9029
1200-D8M-85	452.47	47.24	1.5350
1280-D8M-20	120.72	50.39	0.3846
1280-D8M-30	176.10	50.39	0.5769
1280-D8M-50	279.71	50.39	0.9615
1280-D8M-85	476.91	50.39	1.6345
1304-D8M-20	121.47	51.34	0.3917
1304-D8M-30	177.00	51.34	0.5876
1304-D8M-50	282.75	51.34	0.9793
1304-D8M-85	480.85	51.34	1.6648
1328-D8M-20	122.23	52.28	0.3988
1328-D8M-30	178.30	52.28	0.5983
1328-D8M-50	285.79	52.28	0.9971
1328-D8M-85	484.79	52.28	1.6951
1360-D8M-20	123.24	53.54	0.4083
1360-D8M-30	179.77	53.54	0.6125
1360-D8M-50	289.85	53.54	1.0209
1360-D8M-85	490.04	53.54	1.7355
1424-D8M-20	125.25	56.06	0.4274
1424-D8M-30	182.71	56.06	0.6410
1424-D8M-50	297.96	56.06	1.0684
1424-D8M-85	500.54	56.06	1.8163

D8M			
Order Code	Suggested List Price (USD)	Pitch length (In.)	Wt. Ea. (Lbs.)
1440-D8M-20	125.75	56.69	0.4321
1440-D8M-30	183.44	56.69	0.6482
1440-D8M-50	299.99	56.69	1.0803
1440-D8M-85	503.16	56.69	1.8365
1600-D8M-20	139.80	62.99	0.4793
1600-D8M-30	198.83	62.99	0.7190
1600-D8M-50	323.68	62.99	1.1983
1600-D8M-85	547.69	62.99	2.0372
1760-D8M-20	149.65	69.29	0.5269
1760-D8M-30	213.67	69.29	0.7903
1760-D8M-50	351.32	69.29	1.3171
1760-D8M-85	599.42	69.29	2.2391
1800-D8M-20	152.35	70.87	0.5383
1800-D8M-30	222.37	70.87	0.8075
1800-D8M-50	356.91	70.87	1.3458
1800-D8M-85	616.12	70.87	2.2879
2000-D8M-20	166.33	78.74	0.5976
2000-D8M-30	240.54	78.74	0.8964
2000-D8M-50	409.11	78.74	1.4940
2000-D8M-85	694.38	78.74	2.5398
2248-D8M-20	183.53	88.50	0.6709
2248-D8M-30	266.12	88.50	1.0064
2248-D8M-50	440.95	88.50	1.6673
2248-D8M-85	754.35	88.50	2.8514
2400-D8M-20	194.07	94.49	0.7159
2400-D8M-30	281.80	94.49	1.0738
2400-D8M-50	460.48	94.49	1.7897
2400-D8M-85	791.11	94.49	3.0424
2600-D8M-20	207.87	102.36	0.7266
2600-D8M-30	311.54	102.36	1.0899
2600-D8M-50	508.49	102.36	1.8165
2600-D8M-85	873.03	102.36	3.0881

D14M			
Order Code	Suggested List Price (USD)	Pitch length (In.)	Wt. Ea. (Lbs.)
966-D14M-40	501.90	38.03	0.9593
966-D14M-55	668.39	38.03	1.3190
966-D14M-85	989.98	38.03	2.0385
966-D14M-115	1,259.17	38.03	2.7579
966-D14M-170	1,930.07	38.03	4.0769
1190-D14M-40	539.70	46.85	1.1731
1190-D14M-55	734.53	46.85	1.6130
1190-D14M-85	1,058.72	46.85	2.4928
1190-D14M-115	1,387.75	46.85	3.3726
1190-D14M-170	2,052.34	46.85	4.9856
1400-D14M-40	582.63	55.12	1.3733
1400-D14M-55	774.82	55.12	1.8883
1400-D14M-85	1,166.80	55.12	2.9183
1400-D14M-115	1,569.51	55.12	3.9483
1400-D14M-170	2,229.15	55.12	5.8366
1610-D14M-40	592.43	63.39	1.5727
1610-D14M-55	804.14	63.39	2.1625
1610-D14M-85	1,197.85	63.39	3.3420
1610-D14M-115	1,603.84	63.39	4.5215
1610-D14M-170	2,344.42	63.39	6.6840
1778-D14M-40	655.51	70.00	1.7329
1778-D14M-55	862.76	70.00	2.3828
1778-D14M-85	1,257.62	70.00	3.6825
1778-D14M-115	1,661.48	70.00	4.9822
1778-D14M-170	2,426.54	70.00	7.3650
1890-D14M-40	666.34	74.41	1.8390
1890-D14M-55	901.54	74.41	2.5286
1890-D14M-85	1,302.98	74.41	3.9078
1890-D14M-115	1,754.15	74.41	5.2871
1890-D14M-170	2,565.17	74.41	7.8157
2100-D14M-40	716.33	82.68	2.0397
2100-D14M-55	970.18	82.68	2.8045
2100-D14M-85	1,419.76	82.68	4.3343
2100-D14M-115	1,880.81	82.68	5.8640
2100-D14M-170	2,759.84	82.68	8.6685
2310-D14M-40	766.33	90.94	2.2403
2310-D14M-55	1,038.82	90.94	3.0804
2310-D14M-85	1,536.53	90.94	4.7607
2310-D14M-115	2,007.48	90.94	6.4409
2310-D14M-170	2,954.52	90.94	9.5214
2450-D14M-40	799.66	96.46	2.3741
2450-D14M-55	1,084.59	96.46	3.2644
2450-D14M-85	1,614.38	96.46	5.0450
2450-D14M-115	2,091.92	96.46	6.8256
2450-D14M-170	3,084.30	96.46	10.0900

DS8M			
Order Code	Suggested List Price (USD)	Pitch length (In.)	Wt. Ea. (Lbs.)
600-DS8M-20	71.11	23.62	0.183
600-DS8M-30	105.13	23.62	0.275
600-DS8M-50	168.67	23.62	0.458
600-DS8M-85	294.84	23.62	0.983
640-DS8M-20	75.00	25.20	0.195
640-DS8M-30	108.36	25.20	0.293
640-DS8M-50	174.65	25.20	0.488
640-DS8M-85	298.99	25.20	0.830
656-DS8M-20	76.56	25.83	0.200
656-DS8M-30	109.65	25.83	0.300
656-DS8M-50	177.05	25.83	0.500
656-DS8M-85	300.65	25.83	0.911
720-DS8M-20	82.77	28.35	0.219
720-DS8M-30	114.81	28.35	0.329
720-DS8M-50	186.63	28.35	0.548
720-DS8M-85	307.28	28.35	0.932
760-DS8M-20	87.19	29.92	0.231
760-DS8M-30	123.04	29.92	0.346
760-DS8M-50	196.47	29.92	0.578
760-DS8M-85	330.53	29.92	0.983
800-DS8M-20	91.60	31.50	0.243
800-DS8M-30	131.26	31.50	0.364
800-DS8M-50	206.31	31.50	0.607
800-DS8M-85	353.78	31.50	1.031
848-DS8M-20	95.32	33.39	0.258
848-DS8M-30	136.22	33.39	0.385
848-DS8M-50	217.52	33.39	0.642
848-DS8M-85	370.32	33.39	1.091
880-DS8M-20	97.79	34.65	0.266
880-DS8M-30	139.53	34.65	0.399
880-DS8M-50	224.99	34.65	0.665
880-DS8M-85	381.35	34.65	1.131
960-DS8M-20	102.12	37.80	0.290
960-DS8M-30	144.07	37.80	0.435
960-DS8M-50	235.26	37.80	0.725
960-DS8M-85	402.64	37.80	1.232
1000-DS8M-20	105.04	39.37	0.302
1000-DS8M-30	149.49	39.37	0.453
1000-DS8M-50	241.52	39.37	0.755
1000-DS8M-85	411.41	39.37	1.282

DS8M			
Order Code	Suggested List Price (USD)	Pitch length (In.)	Wt. Ea. (Lbs.)
1056-DS8M-20	109.13	41.57	0.318
1056-DS8M-30	157.07	41.57	0.478
1056-DS8M-50	250.28	41.57	0.797
1056-DS8M-85	423.70	41.57	1.354
1064-DS8M-20	109.72	41.89	0.321
1064-DS8M-30	158.15	41.89	0.481
1064-DS8M-50	251.53	41.89	0.802
1064-DS8M-85	425.46	41.89	1.363
1072-DS8M-20	110.30	42.20	0.323
1072-DS8M-30	159.24	42.20	0.486
1072-DS8M-50	252.78	42.20	0.809
1072-DS8M-85	427.22	42.20	1.374
1120-DS8M-20	113.80	44.09	0.337
1120-DS8M-30	165.74	44.09	0.506
1120-DS8M-50	260.30	44.09	0.844
1120-DS8M-85	437.75	44.09	1.434
1136-DS8M-20	114.60	44.72	0.343
1136-DS8M-30	166.52	44.72	0.513
1136-DS8M-50	260.67	44.72	0.855
1136-DS8M-85	440.69	44.72	1.454
1160-DS8M-20	115.79	45.67	0.350
1160-DS8M-30	167.71	45.67	0.525
1160-DS8M-50	261.24	45.67	0.873
1160-DS8M-85	445.11	45.67	1.486
1168-DS8M-20	116.18	45.98	0.355
1168-DS8M-30	168.10	45.98	0.529
1168-DS8M-50	261.42	45.98	0.879
1168-DS8M-85	446.58	45.98	1.496
1176-DS8M-20	116.58	46.30	0.354
1176-DS8M-30	168.50	46.30	0.531
1176-DS8M-50	261.61	46.30	0.885
1176-DS8M-85	448.06	46.30	1.506
1184-DS8M-20	116.98	46.61	0.357
1184-DS8M-30	168.89	46.61	0.536
1184-DS8M-50	261.80	46.61	0.892
1184-DS8M-85	449.53	46.61	1.515
1200-DS8M-20	117.77	47.24	0.361
1200-DS8M-30	169.68	47.24	0.542
1200-DS8M-50	262.17	47.24	0.903
1200-DS8M-85	452.47	47.24	1.535

DS8M			
Order Code	Suggested List Price (USD)	Pitch length (In.)	Wt. Ea. (Lbs.)
1216-DS8M-20	118.36	47.87	0.367
1216-DS8M-30	170.97	47.87	0.550
1216-DS8M-50	265.68	47.87	0.915
1216-DS8M-85	457.36	47.87	1.556
1240-DS8M-20	119.24	48.82	0.374
1240-DS8M-30	172.89	48.82	0.559
1240-DS8M-50	270.94	48.82	0.933
1240-DS8M-85	464.69	48.82	1.586
1256-DS8M-20	119.83	49.45	0.378
1256-DS8M-30	174.18	49.45	0.566
1256-DS8M-50	274.45	49.45	0.944
1256-DS8M-85	472.02	49.45	1.606
1264-DS8M-20	120.13	49.76	0.380
1264-DS8M-30	174.82	49.76	0.570
1264-DS8M-50	276.20	49.76	0.950
1264-DS8M-85	447.59	49.76	1.615
1280-DS8M-20	120.72	50.39	0.385
1280-DS8M-30	176.10	50.39	0.577
1280-DS8M-50	279.71	50.39	0.961
1280-DS8M-85	476.91	50.39	1.634
1296-DS8M-20	121.22	51.02	0.389
1296-DS8M-30	176.84	51.02	0.584
1296-DS8M-50	281.74	51.02	0.973
1296-DS8M-85	479.54	51.02	1.655
1304-DS8M-20	121.47	51.34	0.392
1304-DS8M-30	177.20	51.34	0.588
1304-DS8M-50	282.75	51.34	0.979
1304-DS8M-85	480.85	51.34	1.665
1312-DS8M-20	121.72	51.65	0.394
1312-DS8M-30	177.57	51.65	0.591
1312-DS8M-50	283.77	51.65	0.985
1312-DS8M-85	482.16	51.65	1.675
1344-DS8M-20	122.73	52.91	0.404
1344-DS8M-30	179.04	52.91	0.605
1344-DS8M-50	287.82	52.91	1.009
1344-DS8M-85	487.41	52.91	1.715
1368-DS8M-20	123.48	53.86	0.411
1368-DS8M-30	180.14	53.86	0.616
1368-DS8M-50	290.86	53.86	1.027
1368-DS8M-85	491.35	53.86	1.746

DS8M			
Order Code	Suggested List Price (USD)	Pitch length (In.)	Wt. Ea. (Lbs.)
1400-DS8M-20	124.49	55.12	0.420
1400-DS8M-30	181.61	55.12	0.630
1400-DS8M-50	294.92	55.12	1.051
1400-DS8M-85	496.60	55.12	1.786
1408-DS8M-20	124.74	55.43	0.423
1408-DS8M-30	181.97	55.43	0.634
1408-DS8M-50	295.93	55.43	1.057
1408-DS8M-85	497.91	55.43	1.796
1440-DS8M-20	125.75	56.69	0.432
1440-DS8M-30	183.44	56.69	0.648
1440-DS8M-50	299.99	56.69	1.080
1440-DS8M-85	503.16	56.69	1.836
1480-DS8M-20	129.26	58.27	0.444
1480-DS8M-30	187.29	58.27	0.665
1480-DS8M-50	305.91	58.27	1.110
1480-DS8M-85	514.29	58.27	1.887
1512-DS8M-20	132.07	59.53	0.453
1512-DS8M-30	190.37	59.53	0.680
1512-DS8M-50	310.65	59.53	1.133
1512-DS8M-85	523.20	59.53	1.927
1552-DS8M-20	135.58	61.10	0.465
1552-DS8M-30	194.22	61.10	0.698
1552-DS8M-50	316.57	61.10	1.163
1552-DS8M-85	534.33	61.10	1.988
1600-DS8M-20	139.80	62.99	0.479
1600-DS8M-30	198.83	62.99	0.719
1600-DS8M-50	323.68	62.99	1.198
1600-DS8M-85	547.69	62.99	2.037
1624-DS8M-20	141.28	63.94	0.486
1624-DS8M-30	201.06	63.94	0.730
1624-DS8M-50	327.82	63.94	1.216
1624-DS8M-85	555.45	63.94	2.067
1760-DS8M-20	149.65	69.29	0.527
1760-DS8M-30	213.67	69.29	0.790
1760-DS8M-50	351.32	69.29	1.317
1760-DS8M-85	599.42	69.29	2.239
1776-DS8M-20	150.73	69.92	0.531
1776-DS8M-30	217.15	69.92	0.797
1776-DS8M-50	353.56	69.92	1.329
1776-DS8M-85	606.10	69.92	2.259

DS8M			
Order Code	Suggested List Price (USD)	Pitch length (In.)	Wt. Ea. (Lbs.)
1800-DS8M-20	152.35	70.87	0.538
1800-DS8M-30	222.37	70.87	0.807
1800-DS8M-50	356.91	70.87	1.346
1800-DS8M-85	616.12	70.87	2.288
1912-DS8M-20	159.91	75.28	0.572
1912-DS8M-30	246.75	75.28	0.856
1912-DS8M-50	372.53	75.28	1.424
1912-DS8M-85	662.87	75.28	2.423
2240-DS8M-20	182.05	88.19	0.673
2240-DS8M-30	318.14	88.19	1.000
2240-DS8M-50	418.29	88.19	1.654
2240-DS8M-85	799.77	88.19	2.817
2392-DS8M-20	192.31	94.17	0.719
2392-DS8M-30	351.22	94.17	1.066
2392-DS8M-50	439.50	94.17	1.760
2392-DS8M-85	863.21	94.17	3.000

DH			
Order Code	Suggested List Price (USD)	Pitch length (In.)	Wt. Ea. (Lbs.)
270DH075	94.63	27.00	0.5295
270DH100	120.92	27.00	0.7060
270DH150	176.02	27.00	1.0590
270DH200	231.94	27.00	1.4119
270DH300	337.76	27.00	2.1179
300DH075	97.73	30.00	0.5861
300DH100	127.82	30.00	0.7814
300DH150	184.37	30.00	1.1721
300DH200	248.63	30.00	1.5628
300DH300	367.42	30.00	2.3442
330DH075	106.63	12.99	0.6440
330DH100	137.14	12.99	0.8580
330DH150	197.56	12.99	1.2870
330DH200	261.79	12.99	1.7170
330DH330	388.15	12.99	2.5750
335DH075	108.11	13.19	0.6530
335DH100	138.69	13.19	0.8710
335DH150	199.76	13.19	1.3070
335DH200	263.99	13.19	1.7420
335DH300	391.61	13.19	2.6130
360DH075	115.53	36.00	0.7014
360DH100	146.45	36.00	0.9352
360DH150	210.76	36.00	1.4029
360DH200	274.96	36.00	1.8705
360DH300	408.88	36.00	2.8057
370DH075	118.44	37.00	0.7205
370DH100	147.10	37.00	0.9607
370DH150	220.93	37.00	1.4411
370DH200	292.17	37.00	1.9215
370DH300	437.49	37.00	2.8822
390DH075	121.28	39.00	0.7591
390DH100	154.60	39.00	1.0122
390DH150	231.31	39.00	1.5183
390DH200	293.76	39.00	2.0243
390DH300	438.10	39.00	3.0365
420DH075	124.96	42.00	0.8168
420DH100	161.38	42.00	1.0891
420DH150	237.89	42.00	1.6336
420DH200	320.12	42.00	2.1782
420DH300	466.24	42.00	3.2673


DH			
Order Code	Suggested List Price (USD)	Pitch length (In.)	Wt. Ea. (Lbs.)
450DH075	135.55	45.00	0.8738
450DH100	177.02	45.00	1.1650
450DH150	248.21	45.00	1.7475
450DH200	329.11	45.00	2.3300
450DH300	499.42	45.00	3.4951
480DH075	136.67	48.00	0.9315
480DH100	182.50	48.00	1.2419
480DH150	272.31	48.00	1.8629
480DH200	356.90	48.00	2.4839
480DH300	526.86	48.00	3.7258
510DH075	142.28	51.00	0.9884
510DH100	183.30	51.00	1.3179
510DH150	281.18	51.00	1.9768
510DH200	358.27	51.00	2.6357
510DH300	547.01	51.00	3.9536
540DH075	149.91	54.00	1.0461
540DH100	198.95	54.00	1.3948
540DH150	293.41	54.00	2.0922
540DH200	377.55	54.00	2.7896
540DH300	586.54	54.00	4.1844
570DH075	154.08	57.00	1.1038
570DH100	207.20	57.00	1.4717
570DH150	294.76	57.00	2.2076
570DH200	397.66	57.00	2.9434
570DH300	594.48	57.00	4.4151
600DH075	166.80	60.00	1.1607
600DH100	217.62	60.00	1.5476
600DH150	313.96	60.00	2.3215
600DH200	428.43	60.00	3.0953
600DH300	640.37	60.00	4.6429
630DH075	172.57	63.00	1.2188
630DH100	228.27	63.00	1.6251
630DH150	331.48	63.00	2.4376
630DH200	439.54	63.00	3.2501
630DH300	658.32	63.00	4.8752
660DH075	178.81	66.00	1.2761
660DH100	230.30	66.00	1.7015
660DH150	342.94	66.00	2.5522
660DH200	465.26	66.00	3.4030
660DH300	684.25	66.00	5.1044

DH			
Order Code	Suggested List Price (USD)	Pitch length (In.)	Wt. Ea. (Lbs.)
700DH075	185.70	70.00	1.3522
700DH100	241.79	70.00	1.8029
700DH150	367.68	70.00	2.7043
700DH200	471.03	70.00	3.6058
700DH300	730.14	70.00	5.4087
730DH075	192.46	73.00	1.4102
730DH100	251.51	73.00	1.8803
730DH150	378.29	73.00	2.8204
730DH200	486.25	73.00	3.7606
730DH300	733.10	73.00	5.6409
750DH075	196.06	75.00	1.4481
750DH100	264.22	75.00	1.9308
750DH150	389.30	75.00	2.8961
750DH200	501.65	75.00	3.8615
750DH300	765.10	75.00	5.7923

CONTI® SYNCHROTWIN CXP

Heavy-duty double-sided synchronous belt

for high speeds



Profile	Profile
D5M	DS8M
D8M	
D14M	

SIZES AVAILABLE ON REQUEST BY SPECIAL ORDER

Properties:

- conditionally resistant to oil
- temperature range, depending on application, from -4°F to +212°F (-20°C to +100°C)
- electrically conductive to ISO 9563
- suitable for tropical climates
- resistant to aging and ozone




Heavy-duty variant **CONTI® SYNCHROTWIN CXA** for low speeds and high torque on request.

CONTI® SYNCHROLINE

Open-ended rubber synchronous belt

for use in automatic sliding doors and other linear motion applications



Profile	Profile
5M	S8M
8M	

Properties:

- conditionally resistant to oil
- temperature range, depending on application, from -4°F to +212°F (-20°C to +100°C)
- ozone-resistant
- maintenance-free

CONTI® SYNCHROLINE CXP

heavy-duty type on request.




HTD 5M		HTD 8M		STD S8M	
Order Code	Suggested List Price (USD) Per Meter	Order Code	Suggested List Price (USD) Per Meter	Order Code	Suggested List Price (USD) Per Meter
HTD 5 10 OER	7.03	HTD 8 10 OER	9.14	STD 8 10 OER	9.14
HTD 5 12 OER	8.95	HTD 8 12 OER	11.64	STD 8 12 OER	11.64
HTD 5 15 OER	11.83	HTD 8 15 OER	15.38	STD 8 15 OER	15.38
HTD 5 20 OER	16.63	HTD 8 20 OER	21.95	STD 8 20 OER	21.95

Standard Roll Length - 30 Meters

CONTI® SYNCHRODRIVE

Open-ended polyurethane synchronous belts

for material flow, linear and transport technology, entry systems

HTD	STD	XL-H
		
Profile	Profile	Profile
3M T5	S3M	XL
5M T10	S5M	L
8M AT5	S8M	H
14M AT10		
AT20		

Other profiles upon request

Properties:

- ▶ wear-resistant
- ▶ oil and grease-resistant
- ▶ resistant to fuel and benzene
- ▶ hydrolysis-resistant
- ▶ resistant to UV and ozone
- ▶ temperature range from -24°F to +176°F (-30°C to +80°C)
(please request technical advice for temperatures below -10°C and above +50°C)
- ▶ can be welded with thermoplastics
- ▶ raw materials and production are silicone free



CONTI SYNCHRODRIVE®

T		
Order Code	Suggested List Price (USD) Per Meter	Wt. Per Meter (Lbs.)
T5 – Polyurethane and standard steel cord (HP)		
T5-10-OEP	16.93	0.0491
T5-15-OEP	25.40	0.0744
T5-20-OEP	32.90	0.0997
T5-25-OEP	37.09	0.1235
T5-32-OEP	48.34	0.1577
T5-50-OEP	69.32	0.2455
T5-100-OEP	137.43	0.4969
T5 – Polyurethane/standard steel HP- Polyamide Tooth PAZ		
T5-10-OEP PAZ	129.52	0.0491
T5-25-OEP PAZ	263.94	0.1250
T5-50-OEP PAZ	129.52	0.2484
T5-100-OEP PAZ	263.94	0.4969
T10 – Polyurethane/Standard Steel HP		
T10-20-OEP	29.85	0.1636
T10-25-OEP	36.67	0.2053
T10-32-OEP	45.25	0.2455
T10-50-OEP	67.71	0.4091
T10-75-OEP	98.68	0.6144
T10-100-OEP	127.53	0.8108

AT		
Order Code	Suggested List Price (USD) Per Meter	Wt. Per Meter (Lbs.)
AT3 - Polyurethane/Standard steel HP		
AT3-5-OEP	19.12	
AT3-10-OEP	28.39	
AT3-20-OEP	38.81	
AT3-25-OEP	43.64	
AT3-50-OEP	84.66	
AT5 - Polyurethane/Standard steel HP		
AT5-10-OEP	19.12	0.0625
AT5-15-OEP	28.39	0.0922
AT5-20-OEP	38.81	0.1235
AT5-25-OEP	43.64	0.1532
AT5-32-OEP	57.95	0.1964
AT5-50-OEP	84.66	0.3065
AT10 - Polyurethane/Standard steel HP		
AT10-20-OEP	52.95	0.1904
AT10-25-OEP	56.10	0.2380
AT10-32-OEP	71.09	0.2678
AT10-40-OEP	79.33	0.3347
AT10-50-OEP	83.20	0.4761
AT10-75-OEP	124.62	0.7126
AT10-100-OEP	150.99	0.9492
AT10 - Polyurethane/standard steel HP- Polyamide Tooth PAZ		
AT10-25-OEP PAZ	107.05	0.2380
AT10-32-OEP PAZ	135.65	0.2856
AT10-100-OEP PAZ	281.16	0.9551
AT20 - Polyurethane/Standard steel HP		
AT20-25-OEP	160.87	0.4493
AT20-32-OEP	205.94	0.5757
AT20-50-OEP	294.89	0.8986
AT20-75-OEP	435.67	1.3508
AT20-100-OEP	571.89	1.7971

Standard Roll Length - 30 Meters

HTD 3M/5M/8M		
Order Code	Suggested List Price (USD) Per Meter	Wt. Per Meter (Lbs.)
3M - Polyurethane/Standard steel HP		
3HTD-10-OEP	8.74	
3HTD-15-OEP	13.13	
3HTD-20-OEP	17.16	
3HTD-25-OEP	21.20	
3HTD-50-OEP	38.23	
3M - Tooth Polyurethane/standard steel HP- Polyamide Tooth PAZ		
3HTD-10-OEP PAZ	16.77	
3HTD-15-OEP PAZ	25.14	
3HTD-20-OEP PAZ	32.25	
3HTD-25-OEP PAZ	39.36	
3HTD-50-OEP PAZ	74.24	
5M - Polyurethane/Standard steel HP		
5HTD-10-OEP	11.65	0.0610
5HTD-15-OEP	17.50	0.0922
5HTD-20-OEP	22.89	0.1265
5HTD-25-OEP	28.27	0.1532
5HTD-50-OEP	50.97	0.3050
5M - Tooth Polyurethane/standard steel HP- Polyamide Tooth PAZ		
5HTD-10-OEP PAZ	22.36	0.0580
5HTD-15-OEP PAZ	33.52	0.0788
5HTD-20-OEP PAZ	43.00	0.1131
5HTD-25-OEP PAZ	52.48	0.1532
5HTD-50-OEP PAZ	98.99	0.3050
8M - Polyurethane/standard steel HP		
8HTD-15-OEP	45.16	0.1268
8HTD-20-OEP	56.11	0.1647
8HTD-25-OEP	71.29	0.2001
8HTD-50-OEP	206.26	0.7438
8M - Polyurethane/standard steel HP- Polyamide Tooth PAZ		
8HTD-15-OEP PAZ	53.13	0.1413
8HTD-20-OEP PAZ	66.01	0.1889
8HTD-25-OEP PAZ	83.87	0.2365
8HTD-50-OEP PAZ	242.66	0.9492
8M - Polyurethane/standard steel HP- Polyamide Backing PAR		
8HTD-20-OEP PAR	63.52	0.1904
8HTD-100-OEP PAR	230.31	0.9492

HTD 14M		
Order Code	Suggested List Price (USD) Per Meter	Wt. Per Meter (Lbs.)
14M - Polyurethane/Standard steel HP		
14HTD-20-50M-OEP	109.49	0.4130
14HTD-25-50M-OEP	198.98	0.4850
14HTD-45-50M-OEP	301.33	0.8420
14HTD-100-50M-OEP	371.81	1.6856
14M - Polyurethane/standard steel HP- Polyamide Tooth PAZ		
14HTD-25-50M-OEP PAZ	121.65	0.4830
14HTD-50-50M-OEP PAZ	221.09	0.8420
14HTD-75-50M-OEP PAZ	334.81	1.2645
14HTD-100-50M-OEP PAZ	413.12	1.6856


STD S3M/S5M/S8M/S14M		
Order Code	Suggested List Price (USD) Per Meter	Wt. Per Meter (Lbs.)
S3M - Polyurethane/Standard steel HP		
3STD-10-OEP	11.65	
3STD-15-OEP	17.50	
3STD-25-OEP	28.27	
3STD-50-OEP	50.97	
S5M - Polyurethane/Standard steel HP		
5STD-10-OEP	17.89	0.0610
5STD-15-OEP	26.82	0.0922
5STD-25-OEP	41.98	0.1532
5STD-50-OEP	79.19	0.3050
S5M - Tooth Polyurethane/standard steel HP- Polyamide Tooth PAZ		
5STD-10-OEP PAZ	22.36	0.0580
5STD-15-OEP PAZ	33.52	0.0788
5STD-25-OEP PAZ	52.48	0.1532
5STD-50-OEP PAZ	98.99	0.3050
S8M - Polyurethane/Standard steel HP		
8STD-15-OEP	45.16	0.1413
8STD-20-OEP	56.11	0.1889
8STD-25-OEP	71.29	0.2365
8STD-50-OEP	116.28	0.4678
S8M - Tooth Polyurethane/standard steel HP- Polyamide Tooth PAZ		
8STD-15-OEP PAZ	53.13	0.1413
8STD-20-OEP PAZ	66.01	0.1889
8STD-25-OEP PAZ	83.87	0.2365
8STD-50-OEP PAZ	136.80	0.7435
8STD-100-OEP PAZ	242.66	0.9492
S14M - Tooth Polyurethane/standard steel HP- Polyamide Tooth PAZ		
14STD-25-50M-OEP PAZ	121.65	0.4135
14STD-50-50M-OEP PAZ	221.09	0.8420
14STD-75-50M-OEP PAZ	334.81	1.2645
14STD-100-50M-OEP PAZ	413.12	1.6856

XL/L/H		
Order Code	Suggested List Price (USD) Per Meter	Wt. Per Meter (Lbs.)
XL - Polyurethane/Flexible steel HF		
XL-025-OEP	6.03	0.0193
XL-032-OEP	7.00	0.0298
XL-050-OEP	9.67	0.0104
XL-100-OEP	18.21	0.0223
XL-150-OEP	26.50	0.0342
XL-200-OEP	33.24	0.1651
L - Polyurethane/Flexible steel HF		
L-075-OEP	10.17	0.1041
L-100-OEP	12.72	0.1398
L-150-OEP	18.64	0.2098
L-200-OEP	25.31	0.2827
H - Polyurethane/Flexible steel HF		
H-075-OEP	9.32	0.1294
H-100-OEP	12.05	0.1726
H-150-OEP	18.14	0.2589
H-200-OEP	23.93	0.3481

CONTI® SYNCHROFLEX

Polyurethane synchronous belts

for the lower and medium power range



Profile

AT 3	T 10
AT 5	T 10-DL
AT 10	T 20
AT 20	M (MXL)
T 2	K 1
T 2,5	K 1,5
T 2,5-DL	
T 5	
T 5-DL	

FOR DETAILED SIZES, SEE SYNCHROFLEX CATALOG

Properties:

- constant length
- low-noise
- wear-resistance
- high flexibility
- fatigue-resistant
- hydrolysis-resistant
- aging-resistant
- temperature range from -24°F to +176°F (-30°C to +80°C) (please request technical advice for range under -10°C and above +50°C)
- resistant to oils, grease and fuel
- conditionally resistant to acid and lye
- raw materials and production are silicone free



CONTI® SYNCHROFLEX GEN III


Polyurethane heavy-duty timing belts

for high power transmission at high speeds with balanced two-filament tension member in S and Z design

CONTI® SYNCHRODRIVE N10

Self-guiding nubbed belts

for transport and linear technology



Profile

N10

* Fabric cover on nubs and backing (PAN/PAR) upon request

SIZES AVAILABLE ON REQUEST BY SPECIAL ORDER

Properties:

- wear-resistant
- oil and grease-resistant
- resistant to fuel and benzene
- hydrolysis-resistant
- resistant to UV and ozone
- temperature range from -24°F to +176°F (-30°C to +80°C) (please request technical advice for temperatures below -10°C and above +50°C)
- can be welded with thermoplastics
- raw materials and production are silicone free



CONTI® N10			
Part No.	List Price (USD) Per Meter	Part No.	List Price (USD) Per Meter
N10-20-HF	\$19.98	N10-60-HF	\$77.94
N10-30-HF	\$31.29	N10-70-HF	\$80.81
N10-40-HF	\$46.32	N10-80-HF	\$83.67
N10-50-HF	\$45.74	N10-90-HF	\$86.54
		N10-100-HF	\$89.40

Standard Roll Length - 30 Meters

CONTI® POLYFLAT


Flat belt

for space-saving drive configurations in lift systems

F



F



Polyurethane pulley side

Tension member/Steel cord

Polyurethane backing

Versions

- HF - High Flexibility
- HP - Standard Strength
- HS - High Strength
- XHP - Very High Strength
- XHS - Extremely High Strength
- XXHS - Aramid Cord, Highest Strength

Properties:

- wear-resistant
- oil and grease-resistant
- resistant to fuel and benzene
- hydrolysis-resistant
- resistant to UV and ozone
- temperature range from -24°F to +176°F (-30°C to +80°C)
(please request technical advice for temperatures below -10°C and above +50°C)
- can be welded with thermoplastics
- raw materials and production are silicone free

grooveless on both sides, on request



CONTI POLYFLAT®


HP		
Order Code	Suggested List Price (USD) Per Meter	Width (mm)
F 10 HP	61.97	10
F 15 HP	65.04	15
F 20 HP	68.12	20
F 25 HP	71.27	25
F 30 HP	74.28	30
F 40 HP	80.44	40
F 50 HP	86.59	50
F 60 HP	92.75	60
F 85 HP	108.13	85
F 100 HP	117.37	100
F 120 HP	129.68	120

XHP		
Order Code	Suggested List Price (USD) Per Meter	Width (mm)
F 15 XHP	108.41	15
F 20 XHP	113.53	20
F 25 XHP	118.67	25
F 30 XHP	123.79	30
F 40 XHP	134.05	40
F 50 XHP	144.31	50
F 60 XHP	154.57	60
F 85 XHP	180.23	80
F 100 XHP	195.61	85
F 120 XHP	216.13	100

Standard Roll Length - 30 Meters

Tension Gauges

CONTI® VSM-1/VSM-3



Electronically measurable belt tension – security for every drive

The right initial tension in force - and form-locked belt drives is a prerequisite for trouble-free, long-term operation of drives in industrial applications. The CONTI® VSM-1 and VSM-3 tension gauges are fully electronic measuring instruments designed specially to measure the initial tension of timing belts, multiple V-ribbed belts and V-belts. They can be used to set the static strand force of belt drives, irrespective of their tension members, simply and precisely.

Properties:

VSM-1

- non-contact measurement
- flexible sensor arm permits monitoring even where access is difficult
- precise readings using optoelectronic measurement method


VSM-3

- non-contact measurement
- exceptionally compact design for reliable measurements, even in hard-to reach areas
- precise measurements by means of optoelectronic measurements process
- sturdy and durable housing

The electronically measurable initial belt tension ensures that every industrial drive is operating safely.



Design Software CONTI® SUITE



Selecting the right drive components in the right size is as important as having a heavy-duty drive belt. Over and undersized drives are inefficient and not as durable. Our **CONTI® SUITE** software package enables specialists in trade and industry to determine the optimum ContiTech drive belt design.

The software's parameter-smart functional algorithm always ensures the greatest possible belt selection efficiency.

ContiTech has developed the **DRIVE ALIVE** module for uncomplicated optimum design of drives involving more than two pulleys and tensioning systems. The multi-pulley module takes into account the load of a belt operating with up to ten separate pulleys.


With this software it is possible to infinitely modify and adapt certain drive parameters. In this way alternative solutions and requirements can be tested and checked out promptly.

The software is logically structured and processes data input directly so that changes can be made directly in the drive system without the need for fresh calculations. The software covers all positive and non-positive elastomer drive components.

Commercial users can download CONTI® SUITE at www.contitech.de/ppp

Interchange Guide

To assure an optimum drive performance as well as a maximum life-length of the belt, choosing the right synchronous belt for the right synchronous sprocket is critical. This Interchange Guide will support you in picking the right belt for the right sprocket for original drive designs or replacements of existing drive designs.



Registered Trademarks of ContiTech:

- ▶ **CONTI SYNCHROBELT®**
- ▶ **CONTI SYNCHROFORCE® CXP**
- ▶ **CONTI SYNCHROCHAIN®**
- ▶ **CONTI SYNCHRODRIVE®**
- ▶ **CONTI SYNCHROFLEX®**
- ▶ **CONTI SYNCHROLINE®**
- ▶ **CONTI SYNCHROTWIN®**

Other trademarks:

- **Trademarks of the Gates corporation**
HTD®, STD®, PowerGrip®, Poly Chain®, GT®, PowerGrip® GT2
- **Trademarks of the Carlisle corporation**
RPP®, RPP Plus®, Synchro-Cog®, Panther RPP®
- **Trademarks of the Goodyear corporation**
Hawk®, Super Torque PD®, Positive Drive Pd®, Black Hawk®, Falcon Pd®
- **Trademarks of the Jason Industrial Incorporation**
HTB®, Tiger®, and Platinum®
- **Trademarks of the Optibelt corporation**
Omega® and Omega HP®
- **Trademarks of the BANDO corporation**
Synchro-Link®, Synchro-Link HT®, Synchro-Link STS® and High Performance STS®

▶ Original Design – optimal choice:

This marks the belts which are originally designed for the sprockets and can be used as original equipment or replacements.

▶ Replacement:

This marks the belts which can be used as a replacement for the original belt.

▶ Limited Replacement:

This marks belts which can be used as a replacement in some cases. Please seek advice from our technical experts.

▶ Not recommended:

This marks belts which are not recommended for the sprockets, due to potentially reduced service life and a reduced performance.

▶ No match:






This marks belts which are not compatible with the displayed sprocket, because they do not fit into the sprocket.

Belt Sprocket Matrix






HTD Sprockets

valid for pitches: 3M/5M		valid for pitches: 8M/14M	
SYNCHROBELT® HTD Original design - optimal choice		SYNCHROBELT® HTD Original design - optimal choice	
		SYNCHROBELT® STD Not recommended	
		SYNCHROFORCE® CXP HTD Original design - optimal choice	
		SYNCHROFORCE® CXP STD Not recommended	
		SYNCHROCHAIN® Limited Replacement	

STD Sprockets

valid for pitches: S8M/S14M	
SYNCHROBELT® HTD No match	
SYNCHROBELT® STD Original design - optimal choice	
SYNCHROFORCE® CXP HTD No match	
SYNCHROFORCE® CXP STD Original design - optimal choice	
SYNCHROCHAIN® No match	

CTD Sprockets

valid for pitches: 8M/14M	
SYNCHROBELT® HTD No match	
SYNCHROBELT® STD No match	
SYNCHROFORCE® CXP HTD No match	
SYNCHROFORCE® CXP STD No match	
SYNCHROCHAIN® Original design - optimal choice	

Belt Sprocket Matrix

PG GT2 Sprockets

valid for pitches: 8M/14M	
SYNCHROBELT® HTD ▶ Limited Replacement	
SYNCHROBELT® STD ▶ Not recommended	
SYNCHROFORCE® CXP HTD ▶ Limited Replacement	
SYNCHROFORCE® CXP STD ▶ Not recommended	
SYNCHROCHAIN® ▶ No match	

GT PC Sprockets

valid for pitches: 8M/14M	
SYNCHROBELT® HTD ▶ No match	
SYNCHROBELT® STD ▶ No match	
SYNCHROFORCE® CXP HTD ▶ No match	
SYNCHROFORCE® CXP STD ▶ No match	
SYNCHROCHAIN® ○ Original design - optimal choice	

RPP Sprockets

valid for pitches: 3M/5M		valid for pitches: 8M/14M	
SYNCHROBELT® HTD ▶ No match		SYNCHROBELT® HTD ▶ Limited Replacement	
SYNCHROBELT® STD ○ Limited Replacement		SYNCHROBELT® STD ▶ Limited Replacement	
SYNCHROFORCE® CXP HTD ▶ No match		SYNCHROFORCE® CXP HTD ○ Limited Replacement	
SYNCHROFORCE® CXP STD ○ Limited Replacement		SYNCHROFORCE® CXP STD ○ Limited Replacement	
		SYNCHROCHAIN® ○ Replacement	

Interchange Matrix

Belt Replacement with SYNCHROBELT® HT

- ▶ Belt Pitch: 3M & 5M

Company	Product Trade Name
Gates	PowerGrip®
GOODYEAR	Hawk (5M)
Carlisle	RPP
Jason Industrial Inc.	HTB (5M)
optibelt	Omega
BANDO	Synchro-Link HT

Belt Replacement with SYNCHROBELT® HTD

- ▶ Belt Pitch: 8M & 14M

Company	Product Trade Name
Browning	HPT
GOODYEAR	Hawk
Carlisle	RPP
Jason Industrial Inc.	HTB (14M)
optibelt	Omega
BANDO	Synchro-Link HT

Belt Replacement with SYNCHROBELT® STD

- ▶ Belt Pitch: S8M

Company	Product Trade Name
GOODYEAR	Super Torque Pd
BANDO	Synchro Link STS

Belt Replacement with SYNCHROBELT® Trapez

- ▶ Belt Pitch: MXL / XL / H / XH / XXH

Company	Product Trade Name
Gates	PowerGrip®
GOODYEAR	Positive Drive Pd
Carlisle	Synchro-Cog
Jason Industrial Inc.	HTB
optibelt	Omega
BANDO	Synchro-Link

Belt Replacement with SYNCHROFORCE® CXP HTD

- ▶ Belt Pitch: 8M & 14M

Company	Product Trade Name
Gates	PowerGrip® GT2
GOODYEAR	Black Hawk
Carlisle	RPP Plus
optibelt	Omega HP
BANDO	Synchro-Link XP
Jason®	Tiger

Belt Replacement with SYNCHROFORCE® CXP STD

- ▶ Belt Pitch:S8M

Company	Product Trade Name
BANDO	High Performance STS

Belt Replacement with SYNCHROCHAIN®

- ▶ Belt Pitch: 8M & 14M

Company	Product Trade Name
Gates	Polychain® GT Carbon
GOODYEAR	Falcon HTC
Jason®	Platinum
MBL	Gigatorque

NOTES

This image shows a single sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.

NOTES

[illegible]

www.crpindustrial.com

CRP Industries Inc.
35 Commerce Drive
Cranbury, NJ 08512 USA

Toll Free 800.526.4066
Phone 609.578.4100
Telefax 609.578.4112

drivebelts@crpindustries.com

© 2012 CRP Industries® Inc.
All rights reserved.

Catalog Disclaimer

The Industrial Synchronous Belts Catalog from CRP Industries is intended to assist you in obtaining the belt designed to best meet your needs for your industrial application. We have made every effort to assure the accuracy of the information provided in this catalog. CRP Industries assumes no responsibility for any loss or damage due to errors or omissions. All references to part numbers and manufacturers are supplied for informational purposes only and are not intended to imply any affiliation with or approval by the manufacturers.



The ContiTech division of the Continental Corporation is a development partner and original equipment supplier to numerous industries for high-quality functional parts, components, and systems. With its know-how in rubber and plastics technology, ContiTech contributes significantly to industrial progress and mobility that is safe, comfortable, and eco-friendly.



www.crpindustrial.com

CRP Industries Inc.
35 Commerce Drive
Cranbury, NJ 08512 USA

Toll Free 800.526.4066
Phone 609.578.4100
Telefax 609.578.4112

drivebelts@crpindustries.com

© 2012 CRP Industries® Inc.
All rights reserved.

Cranbury, NJ

Fremont, CA

Mississauga, ON

Puebla, Mexico

Continental 
CONTITECH