



CONTI® SYNCHROCOLOR

Silicone-free timing belt - free of substances that damage paintwork

Properties:

- ▶ free of silicon and paintable
- ▶ conditionally resistant to oil
- ▶ temperature range, depending on application, from -20°C to +100°C
- ▶ ozone-resistant
- ▶ suitable for tropical climates
- ▶ electrically conductive to ISO 9563
- ▶ maintenance-free
- ▶ suitable by counterbending



Heavy-duty
CONTI® SYNCHROCOLOR CXP and
CONTI® SYNCHROCOLOR CXA
types are available on request.

HTD

Profile	Length range L_p (mm)
HTD 8M Color	480 - 2800
HTD 14M Color	966 - 3500

HTD CXP

Profile	Length range L_p (mm)
HTD 8M Color CXP	480 - 2800
HTD 14M Color CXP	966 - 3150

HTD CXA

Profile	Length range L_p (mm)
HTD 8M Color CXA	480 - 3408
HTD 14M Color CXA	1190 - 4578

Power Transmission Group

Market segment
Industry

Contact
ContiTech Antriebssysteme GmbH
D-30169 Hannover
Phone +49 511 938 - 71
industrie.as@ptg.contitech.de

The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright © 2012 ContiTech AG. All rights reserved. For complete information go to: www.contitech.de/disclosure